OAK CREEK WATER AND SEWER UTILITY OAK CREEK, WISCONSIN WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER MARCH 2011



G-00-101 THRU G-00-103 E-00-101 THRU E-30-302 S-10-101 THRU S-20-103



C-20-101 PR-00-101 THRU PR-30-101




A-00-101 THRU A-30-104 (ARCHITECTURAL ONLY)




A-00-101 THRU A-30-104 (STRUCTURAL ONLY)



P-00-101 THRU P-30-201 HV-00-101 THRU HV-30-202 S-10-101 THRU S-20-103







PROJECT LOCATION MAP

FOR CONSTRUCTION

Clank Dietz

DESIGN FIRM REGISTRATION

125 WEST CHURCH STREE CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT
AND LOW LIFT PUMP STATION
STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

1/21/11 ISSUED FOR CONS 1/3/11 ISSUED FOR BIDS NATE REVISION

COVER SHEET

PROJECT No. 00130014

DRAWING No

G-00-101

085

086

087

880

S-20-101

S-20-102

S-20-103

ADMINISTRATION AND FILTRATION FACILITY - BUILDING SECTIONS

LOW LIFT PUMP STATION - BUILDING SECTION

LOW LIFT PUMP STATION - BUILDING SECTION

LOW LIFT PUMP STATION - BUILDING SECTIONS



DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER WATI AND L

•	•			
DESIGNED BY:	SEM			
DRAWN BY:	JRF			
CHECKED BY:	CEC			
DATE CHECKED:	01/11			
NOTE: DIMENSION	IAL DATA			

SCALING ANY PORTION OF

THIS DRAWING.


3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION


DRAWINGS ОF INDEX

PROJECT No O0130014

SHEET 002 OF 088 SHEETS

G-00-102





- 1. THE CONTRACTOR IS RESPONSIBLE FOR DUST AND MUD CONTROL
- ROADWAY SURFACING AND BASE MATERIALS OR ANY OTHER PROPERTY REMOVED OR DAMAGED SHALL BE REPLACED OR REPAIRED AS PROVIDED FOR IN THE SPECIFICATIONS OR OTHER CONTRACT DOCUMENTS
- 3. THE CONTRACTOR IS RESPONSIBLE FOR ALL CONSTRUCTION TRAFFIC CONTROL.
- 4. IT IS INTENDED THAT GRADING BE PROVIDED TO ASSURE ADEQUATE DRAINAGE AWAY FROM THE BUILDING AND STRUCTURES. ALL GRADING SHALL BE APPROVED BY THE OWNER.
- 5. ALL EQUIPMENT SHOWN ON THIS DRAWING IS EXISTING AND TO REMAIN AS CURRENTLY INSTALLED, UNLESS OTHERWISE NOTED.

DEMOLITION KEYNOTES

- RELOCATE EXISTING STORAGE CONTAINER WITH (18) 900 LB. BAGS OF CARBON.
- RELOCATE EXISTING CARBON FEEDER. REMOVE (4) CONCRETE PADS FOR CARBON FEEDER SUPPORT LEGS. FILL HOLES AND PATCH CONCRETE SLAB TO MATCH EXISTING SURFACE.
- 3. REMOVE EXISTING STEEL PIPE BOLLARD. FILL HOLE AND PATCH CONCRETE SLAB TO MATCH EXISTING SURFACE.
- 4. REMOVE EXISTING CONCRETE CURB AND GUTTER.
- 5. REMOVE EXISTING CHAIN LINK FENCE DOOR.
- 6. REMOVE SECTION OF CHAIN LINK FENCE.
- 7. REMOVE EXISTING STORM SEWER CATCH BASIN. PROVIDE PIPE TO EXTEND 12" TO 15" PIPE AND INFILL MANHOLE. PATCH CONCRETE SLAB TO MATCH EXISTING SURFACE.

KEYNOTES

- 1. EXISTING CONCRETE SLAB.
- PROVIDE CONCRETE SLAB TO MATCH EXISTING SLAB AND DOWEL INTO SLAB EVERY 24" (CONCRETE SLAB SHALL BE FLAT TO ALLOW STORAGE TRAILER DOORS TO PROPERLY OPEN). EXCAVATE AND REMOVE EXISTING DIRT/GRAVEL AREA AS REQUIRED FOR INSTALLATION OF NEW SLAB.
- 3. PROVIDE CONCRETE CURB AND GUTTER. LOCATE CURB AS CLOSE AS POSSIBLE TO EXISTING CHAIN LINK FENCE.
- 4. EXISTING CHAIN LINK FENCE.
- PROVIDE 36"x16" STORM SEWER CATCH BASIN TO MATCH EXISTING BEING REMOVED.
- 6. EXISTING GARBAGE DUMPSTER.
- RELOCATED STORAGE TRAILER. LOCATE CONTAINER 8' NORTH OF CARBON FEEDER TO ALLOW ACCESS BY FORK LIFT AND AS CLOSE AS POSSIBLE TO CONCRETE CURB.
- 8. RELOCATED CARBON FEEDER. LOCATE CARBON FEEDER 4' NORTH OF NORTH SIDE OF BUILDING TO ALLOW ACCESS BY FORK LIFT. SEE STRUCTUAL PLAN 3/A-20-402.
- 9. PROVIDE CHAIN LINK FENCE TO MATCH EXISTING FENCE.
- 10. REGRADE AND PROVIDE GRAVEL TO MATCH EXISTING SURFACE.
- 11. EXISTING 12" STORM SEWER.
- 12. EXISTING 15" STORM SEWER.
- 13. EXISTING 15" STORM SEWER TO BE MODIFIED AS REQUIRED TO REMOVE EXISTING CATCH BASIN AND ADD NEW ONE.
- 14. EXISTING 30" INLET FROM LAKE.
- 15. EXISTING 42" INLET FROM LAKE.
- 16. EXISTING 14" STORM SEWER TO LAKE.
- 17. EXISTING STORM SEWER CATCH BASIN.
- 18. EXISTING UNDERGROUND INCOMING TELEPHONE SERVICE.
- 19. EXISTING UNDERGROUND WE ENERGIES GAS SERVICE.
- 20. EXISTING CONDUIT WITH INCOMING TELEPHONE CABLE.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: JLE/SEM
DRAWN BY: JRF
CHECKED BY: TKB

DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

LIFT PUMP STATION CIVIL SITE PLAN

PROJECT No. 00130014

ŏ O

.....

C-20-101

SHEET 004 OF 088 SHEETS

ARCHITECTURAL GENERAL NOTES

- DIMENSIONS ON FLOOR PLAN ARE BASED ON FACE OF FINISHED WALL TO FACE OF FINISHED WALL (NOMINAL).
- 2. VERIFY ALL DIMENSIONS AND CONDITIONS AT JOB SITE. PORTIONS OF EXISTING CONSTRUCTION MAY HAVE BEEN REMOVED BY OWNER.
- MAINTAIN CONTINUOUS UTILITY SERVICE TO WALL SPACES IN THE BUILDING NOT AFFECTED BY THIS WORK. COORDINATE WITH OWNER ANY MODIFICATION TO EXISTING PIPING, DUCTWORK, AND ANY ASSOCIATED EQUIPMENT OR ANY DISRUPTION IN SERVICES REQUIRED TO PERFORM WORK.
- 4. ALL THE FOLLOWING EQUIPMENT (PIPING, VALVES, DUCTWORK, CONDUIT, BOXES, HANGERS AND SUPPORTS, ETC.) BEING ADDED OR MODIFIED SHALL BE PAINTED TO MATCH EXISTING EQUIPMENT COLORS AT THE FACILITIES. ALL MAJOR EQUIPMENT (GENERATORS, TRANSFER SWITCHES, MOTOR CONTROL CENTERS, PANELBOARDS, PUMPS, MOTORS, MIXING TANK, MIXER, ETC.) SHALL BE FACTORY PAINTED WITH MANUFACTURER'S STANDARD COLORS UNLESS OTHERWISE NOTED.

ARCHITECTURAL DEMOLITION GENERAL NOTES

- DEMOLITION DRAWINGS ARE PROVIDED AS A REFERENCE TO ESTABLISH THE GENERAL SCOPE OF DEMOLITION WORK. CONTRACTOR IS RESPONSIBLE TO COMPLETE ALL DEMOLITION WORK WHERE REQUIRED TO ACCOMMODATE NEW CONSTRUCTION AND PROTECT THE STRUCTURAL INTEGRITY OF EXISTING—TO—REMAIN.
- 2. MAINTAIN THE STRUCTURAL INTEGRITY OF THE EXISTING BUILDING AND MEZZANINE TO REMAIN. IMMEDIATELY CONTACT THE ARCHITECT IF SCHEDULED DEMOLITION WORK WILL COMPROMISE STRUCTURAL INTEGRITY OF EXISTING BUILDING OR MEZZANINE PRIOR TO DEMOLITION.
- 3. VERIFY EXISTING STRUCTURAL SUPPORTS AND LOCATION OF ALL STRUCTURAL SUPPORTING WALLS PRIOR TO DEMOLITION. ALL EXISTING STRUCTURAL SUPPORTS ARE TO REMAIN UNLESS NOTED OTHERWISE ON DEMOLITION PLAN.
- 4. COORDINATE ALL DEMOLITION WORK OUTLINED ON DEMOLITION PLAN WITH NEW FLOOR PLAN LAYOUT TO ALLOW FOR PROTECTION OF EXISTING—TO—REMAIN.
- GENERAL CONTRACTOR IS REQUIRED TO COORDINATE WITH ALL OTHER CONTRACTORS FOR ALL DEMOLITION WORK. GENERAL CONTRACTOR SHALL PROVIDE NECESSARY ACCESS FOR OTHER CONTRACTORS REQUIRED TO PERFORM DEMOLITION WORK AS PART OF THEIR SCOPE.
- 6. CONTRACTOR IS RESPONSIBLE FOR PATCHING WALLS, FLOORS, ETC. AND LEVELING EXISTING SURFACES AS REQUIRED TO MATCH ALL ADJACENT SURFACES WHERE REMOVAL WORK HAS OCCURRED, ESPECIALLY WHERE REMOVED WALLS INTERSECT WALLS TO REMAIN AND EXISTING FLOORS SCHEDULED FOR NEW FINISHES
- SAWCUT, REMOVE AND PATCH ALL WALLS AND FLOORS AS REQUIRED FOR NEW MECHANICAL, PLUMBING AND ELECTRICAL WORK.
- 8. ALL REFERENCES TO MECHANICAL, PLUMBING AND ELECTRICAL DEMOLITION ARE FOR REFERENCE ONLY. CONTRACTORS ARE RESPONSIBLE TO REFER TO MECHANICAL, PLUMBING AND ELECTRICAL DOCUMENTS FOR FULL SCOPE OF REQUIRED DEMOLITION.
- 9. OWNER IS TO REMOVE ALL LOOSE FURNITURE, EQUIPMENT AND ACCESSORIES THAT ARE TO BE SALVAGED PRIOR TO CONSTRUCTION.
- 10. BUILDING WILL REMAIN OPERATIONAL THROUGHOUT PROJECT DURATION.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT
AND LOW LIFT PUMP STATION
STANDBY POWER

THIS DRAWING.

DATE CHECKED BY: 10C

DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

ARCHITECTURAL GENERAL NOTES

PROJECT No. 00130014

DRAWING No.

A-00-101

SHEET 005 OF 088 SHEETS

- 1. THE BUILDING CODE APPLICABLE TO THIS PROJECT IS THE INTERNATIONAL BUILDING CODE
- 2. ALL DETAILS AND SECTIONS SHOWN ON THE DRAWINGS ARE TYPICAL AND SHALL BE USED WHEREVER A SIMILAR CONDITION OCCURS UNLESS NOTED OTHERWISE.
- 3. CONTRACTOR SHALL FIELD VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS AS IT RELATES TO NEW CONSTRUCTION. CONTRACTOR SHALL REPORT ANY DISCREPANCIES TO THE
- 4. THE STABILITY AND STRENGTH OF THE COMPLETED STRUCTURE DEPENDS UPON THE INTERACTION OF VARIOUS CONNECTED PARTS SUCH AS DIAPHRAGMS, BRACES AND/OR SHEAR WALLS. CONTRACTOR SHALL PROVIDE TEMPORARY BRACING AND/OR SHORING AS NECESSARY TO COMPLETE THE WORK.
- 5. DESIGN LOADS:

WATER TREATMENT PLANT:		
DEAD LOAD	ACTUAL WEIG	SHT
LIVE LOAD, GENERATOR ROOM SLAB-ON-GRADE	150	PSF
EQUIPMENT:		
GENERATOR ON SLAB-ON-GRADE	24,000	POUNDS
TRANSFORMER	20,000	POUNDS
LOW LIFT PUMP STATION:		
DEAD LOAD:	ACTUAL WEIG	SHT
MEZANNINE LIVE LOAD ABOVE GENERATOR ROOM	100	PSF
GENERATOR ROOM SLAB-ON-GRADE	150	PSF
EQUIPMENT:		
GENERATOR ON SLAB-ON-GRADE	24,000	POUNDS

REMOVAL AND PROTECTION

- 1. SAW CUT CONCRETE TO LINES AND SHAPES ON DRAWINGS. DO NOT CUT EXISTING REINFORCING BARS WHERE THEY ARE SHOWN TO BE CLEANED AND PRESERVED FOR INCORPORATION INTO NEW CONSTRUCTION.
- 2. PROVIDE SHORING AND BRACING FOR STRUCTURAL ELEMENTS DURING PARTIAL REMOVAL TO AVOID ANY DAMAGE TO THE EXISTING FACILITIES.
- 3. EXISTING STRUCTURES SHALL BE PROTECTED FROM OVERLOADING DUE TO CONSTRUCTION HEAVY EQUIPMENT SHALL NOT BE OPERATED CLOSE TO EXISTING TANKS TO AVOID HIGH LATERAL EARTH PRESSURES ON WALLS.
- 4. DAMAGE TO ADJACENT FACILITIES DURING CONSTRUCTION SHALL BE REPAIRED AT NO ADDITIONAL COST TO THE OWNER.

STRUCTURAL STEEL

- 1. FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE AISC "CODE OF STANDARD PRACTICE FOR STEEL BUILDINGS AND
- 2. NEW MEMBERS ARE INDICATED AS (N) ON THE DRAWINGS AND ARE INCLUDED IN THIS CONTRACT. ALL OTHER MEMBERS SHOWN ARE EXISTING.
- 3. ALL WIDE FLANGE STRUCTURAL SHAPES SHALL CONFORM TO ASTM A992. ALL OTHER HOT ROLLED SHAPES SHALL CONFORM TO ASTM A36. ALL ANCHOR RODS SHALL CONFORM EITHER TO ASTM F1554 (GR. 36) WITH WELDABILITY SUPPLEMENT S1 OR ASTM A36
- 4. ALL SQUARE AND RECTANGULAR HOLLOW STRUCTURAL SECTIONS (HSS) SHALL CONFORM TO ASTM A500 GRADE B, Fy = 46 KSI.
- 5. UNLESS OTHERWISE SHOWN ON THE DRAWINGS ALL BOLTED CONNECTIONS SHALL BE MADE WITH 3/4" DIAMETER ASTM A325 BOLTS AND SHALL BE SNUG TIGHTENED (ASTM
- 6. CONNECTIONS INDICATED AS BEING SLIP CRITICAL (SC) SHALL BE FULLY PRETENSIONED IN ACCORDANCE WITH THE AISC SPECIFICATIONS. BOLT INSTALLATION SHALL BE INSPECTED USING THE TURN OF NUT METHOD, OR AS AN ALTERNATE, TWIST-OFF TYPE A325 BOLTS MAY BE USED.
- 7. WELDED CONNECTIONS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF ANSI/AWS D1.1 STRUCTURAL WELDING CODE, MADE WITH E70XX ELECTRODES AND PERFORMED BY CERTIFIED WELDERS.
- 8. ALL STRUCTURAL STEEL SHALL BE GIVEN ONE COAT OF PRIMER BEFORE LEAVING THE SHOP, IN ACCORDANCE WITH THE SPECIFICATIONS. STRUCTURAL STEEL SHALL BE GIVEN TWO COATS OF FIELD PAINT. FIELD PAINT SHALL BE BY THE SAME MANUFACTURER OF THE PRIME COAT. OWNER TO APPROVE COLORS AND PAINT MANUFACTURER.
- 9. ALL SURFACES OF EXISTING BASE METAL IN CONTACT WITH NEW BASE METAL SHALL BE CLEANED OF ALL DIRT, RUST, AND OTHER FOREIGN MATTER EXCEPT ADHERENT PAINT. SURFACES TO BE WELDED SHALL BE THOROUGHLY CLEANED OF ALL FOREIGN MATTER INCLUDING PAINT FOR AT LEAST 2" FROM THE ROOT OF WELDS.
- 10. ALL BEAMS SHALL BE FABRICATED WITH NATURAL CAMBER UP. PROVIDE ADDITIONAL CAMBER AS NOTED ON THE DRAWINGS.

CAST-IN-PLACE CONCRETE

- 1. CONCRETE WORK ON THIS PROJECT SHALL CONFORM TO ALL REQUIREMENTS OF ACI 301-02. STANDARD SPECIFICATIONS FOR STRUCTURAL CONCRETE, PUBLISHED BY THE AMERICAN CONCRETE INSTITUTE (ACI), DETROIT, MICHIGAN, EXCEPT AS MODIFIED BY THE REQUIREMENTS OF THESE CONTRACT DOCUMENTS.
- 2. ALL CONCRETE SHALL BE PROVIDED WITH A MINIMUM ULTIMATE COMPRESSIVE STRENGTH AT 28 DAYS (f'c) OF 4000 PSI.
- 3. ALL EXTERIOR CONCRETE, BUILDING FOUNDATIONS AND CONCRETE SUBJECT TO FREEZE-THAW SHALL HAVE 4% TO 7% AIR CONTENT BY VOLUME MEASURED IN ACCORDANCE WITH ASTM C231. AIR ENTRAINING ADMIXTURES SHALL CONFORM TO ASTM THE SLUMP SHALL NOT EXCEED 4 INCHES MEASURED IN ACCORDANCE WITH

- 4. REINFORCING STEEL SHALL CONFORM TO ASTM A615 GRADE 60. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A185.
- 5. SUBMIT SHOP DRAWINGS OF THE REINFORCEMENT BARS PREPARED IN ACCORDANCE WITH ACI 315, DETAILS AND DETAILING OF CONCRETE REINFORCEMENT.
- 6. FOR ALL EXPOSED CONCRETE PROVIDE CLASS 1 (PLASTIC PROTECTED) BAR SUPPORTS AND SPACERS IN ACCORDANCE WITH THE ACI 315 DETAILING MANUAL.
- 7. EXTEND ALL SLAB AND BEAM REINFORCEMENT INTO THE SUPPORT IN ACCORDANCE WITH IF SUCH EXTENSIONS ARE NOT OBTAINABLE, THE BAR SHALL TERMINATE WITH STANDARD HOOK.
- 8. WELDING OF REINFORCING BARS SHALL NOT BE PERMITTED.
- 9. NO CALCIUM CHLORIDE WILL BE USED IN CONCRETE.
- 10 DUSTING WITH ANY MATERIAL TO ABSORB SURFACE WATER IS PROHIBITED
- 11. CURING PROCEDURES IN ACCORDANCE WITH ACI 301 SHALL CONTINUE FOR A PERIOD OF AT LEAST 7 DAYS
- 12. DO NOT MIX SALT, CHEMICALS OR OTHER FOREIGN MATERIALS WITH THE CONCRETE TO PREVENT FREEZING. MAINTAIN THE TEMPERATURE OF THE CONCRETE ABOVE 50 DEGREES FAHRENHEIT FOR FIVE DAYS AFTER PLACEMENT.
- 13. COVER FOR REINFORCEMENT FOR CAST-IN-PLACE CONCRETE SHALL BE AS FOLLOWS:

	MINIMUM COVER, INCHES
CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH	3
CONCRETE EXPOSED TO EARTH OR WEATHER: #6 THROUGH #18 BARS #5 BAR, W31 OR D31 WIRE, AND SMALLER	2 1 1/2
CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH GROUND: SLABS, WALLS, JOISTS:	
#11 BARS AND SMALLER #14 AND #18 BARS	3/4 1 1/2
BEAMS, COLUMNS: PRIMARY REINFORCEMENT, TIES, STIRRUPS, SPIRALS	1 1/2

14. UNLESS SHOWN OTHERWISE ON PLANS, LAP SPLICES OF UNCOATED REINFORCEMENT BARS SHALL BE AS FOLLOWS:

LAP LENGTH, INCHES (SMALLER BAR)*

BAR SIZE	<u>#3</u>	<u>#4</u>	<u>#5</u>	<u>#6</u>	<u>#7</u>	<u>#8</u>	<u>#9</u>	<u>#10</u>	<u>#11</u>
A) HORIZONTAL BARS SO PLACED THAT MORE THAN 12 INCHES OF CONCRETE WILL BE CAST BELOW THE BARS	25	33	41	49	71	81	91	102	114
B) HORIZONTAL BARS SO PLACED THAT LESS THAN 12 INCHES OF CONCRETE WILL BE CAST BELOW THE BARS	19	25	31	37	54	62	70	79	85
C) VERTICAL BARS	19	25	31	37	54	62	70	79	85

- *LAP LENGTHS ARE CALCULATED FOR UNCOATED BARS IN ACCORDANCE WITH ACI 318-99, CLASS B SPLICES AND f'c = 4000 PSI. MINIMUM CLEAR SPACING BETWEEN BARS IS TWO BAR DIAMETERS AND MINIMUM COVER IS ONE BAR DIAMETER. FOR OTHER CONDITIONS, CALCULATE SPLICES IN ACCORDANCE WITH ACI 318-02. CLASS B SPLICES REQUIRED UNLESS NOTED OTHERWISE
- 16. OBTAIN ENGINEER'S WRITTEN APPROVAL FOR ANY ADDITIONAL OR RELOCATED CONSTRUCTION JOINTS OTHER THAN THOSE SHOWN ON DRAWINGS.
- 17. UNLESS SHOWN OTHERWISE, CHAMFER ALL EXPOSED EDGES OF CONCRETE 3/4 INCH.
- 18 CONCRETE BEAMS AND ADJACENT SLABS SHALL BE POLIRED MONOLITHICALLY SO THAT NO HORIZONTAL CONSTRUCTION JOINTS ARE PROVIDED, EXCEPT WHERE SHOWN ON
- 19. SEE MECHANICAL, ELECTRICAL, ARCHITECTURAL, AND PIPING DRAWINGS, AND EQUIPMENT MANUFACTURER'S SHOP DRAWINGS FOR LOCATION OF SLEEVES, HOLES, OPENINGS, RECESSES IN SLABS AND WALLS, CASTINGS, ANCHOR BOLTS, ETC.
- 20. SEE DRAWING S-## FOR CONSTRUCTION DETAILS FOR BONDING OF NEW CONCRETE TO EXISTING CONCRETE WITH BONDING COMPOUND. ALL NEW CONCRETE PLACED AGAINST EXISTING SURFACES SHALL HAVE EXISTING COATINGS INCLUDING PAINT AND WATERPROOFING REMOVED, ROUGHENED, CLEANED, AND BONDING AGENT APPLIED. SPECIFICATIONS.
- 21. PROVIDE CONTROL JOINTS IN ALL NON-STRUCTURAL SLABS ON GRADE. SPECIFICATIONS.
- 22. CONTRACTOR SHALL MAKE 4 CONCRETE CYLINDERS FOR EACH POUR. ONE CYLINDER WILL BE TESTED AT 7 DAYS AND THE OTHER TWO AT 28 DAYS TO VERIFY THE REQUIRED COMPRESSIVE STRENGTH. ONE CYLINDER WILL BE A SPARE. ALL TESTING WILL BE IN ACCORDANCE WITH ASTM STANDARDS AND WILL BE AT THE CONTRACTOR'S ADDITIONAL TESTING OR REMOVAL AND REPLACEMENT OF DEFECTIVE CONCRETE WILL BE AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL SUBMIT TEST REPORTS TO THE OWNER WITHIN TWO (2) DAYS OF COMPLETION FOR EACH TEST.

ALUMINUM

- 1. ALL ALUMINUM SHALL CORRESPOND TO ALLOY 6061-T6. SEE SPECIFICATIONS.
- 2. ALUMINUM IN DIRECT CONTACT WITH DISSIMILAR METALS, CONCRETE, OR MASONRY SHALL COATED WITH A HEAVY-BODIED BITUMINOUS PAINT OR COVERED WITH NON-ABSORPTIVE INSULATING TAPE OR GASKET.
- 3. ALL BOLTED CONNECTIONS OF ALUMINUM SHALL BE MADE WITH STAINLESS STEEL BOLTS, 5/8" NOMINAL DIAMETER UNLESS SHOWN OTHERWISE.

MASONRY

- 1. MASONRY WORK ON THIS PROJECT SHALL CONFORM TO ALL REQUIREMENTS OF ACI 530.1, SPECIFICATION FOR MASONRY STRUCTURES, PUBLISHED BY THE AMERICAN CONCRETE INSTITUTE (ACI), DETROIT, MICHIGAN, EXCEPT AS MODIFIED BY THE REQUIREMENTS OF THESE CONTRACT DOCUMENTS.
- 2. CONCRETE MASONRY UNITS SHALL BE IN ACCORDANCE WITH ASTM C90 AND HAVE A MINIMUM COMPRESSIVE STRENGTH OF 1900 PSI.
- 3. EXISTING BRICK AT THE WATER TREATMENT PLANT SHALL BE SALVAGED AND CLEANED IN SUFFICIENT QUANTITY TO BE INCORPORATED INTO NEW WORK
- 4. MORTAR SHALL CONFORM TO ASTM C270, TYPE S MORTAR.
- 5. COMPRESSIVE STRENGTH OF CONCRETE MASONRY (f'm) SHALL BE 1500 PSI MINIMUM.
- 6. COMPRESSIVE STRENGTH OF BRICK MASONRY (f'm) SHALL BE 1500 PSI MINIMUM.
- 7. BAR REINFORCEMENT SHALL CONFORM TO ASTM A615 GRADE 60.
- 8. LENGTH OF BAR SPLICES SHALL BE EQUAL TO 48 BAR DIAMETERS.
- 9. JOINT REINFORCEMENT SHALL BE MADE OF COLD DRAWN WIRE AND SHALL CONFORM TO ASTM A82. JOINT REINFORCEMENT SHALL BE:
 - 3-9 GA, WIRE, TRUSS TYPE $_$ FOR CAVITY WALLS

 - $3\!-\!9$ GA, WIRE, LADDER TYPE $_$ FOR COMPOSITE WALLS 2-9 GA, WIRE, LADDER TYPE $_$ FOR SINGLE WYTHE WALLS
- 10. JOINT REINFORCEMENT, TIES AND ANCHORS SHALL BE GALVANIZED IN ACCORDANCE WITH ACI 530.1.
- 11. JOINT REINFORCEMENT SHALL BE PLACED IN ALL MASONRY WALLS AND SPACED 16" O.C., UNLESS OTHERWISE NOTED.
- 12. ALL CELLS WITH REINFORCEMENT, BOND BEAMS, MASONRY LINTELS AND SILLS SHALL BE FULLY GROUTED. GROUT SHALL CONFORM TO ASTM C476 AND SHALL HAVE 28-DAY COMPRESSIVE STRENGTH OF 2000 PSI MINIMUM.
- 13 MASONRY CONTROL JOINTS SHALL BE PLACED IN REGULAR INTERVALS. AS SHOWN ON ARCHITECTURAL DRAWINGS. BOND BEAM REINFORCEMENT SHALL BE CARRIED THROUGH CONTROL JOINTS.
- 14. LAY CONCRETE MASONRY UNITS WITH FULL MORTAR COVERAGE ON HORIZONTAL AND VERTICAL FACE SHELLS AND WEBS.
- 15. WYTHES IN REINFORCED COMPOSITE BRICK WALLS SHALL BE BONDED WITH 9 GA. WIRE TIES SPACED 16" O.C. VERTICALLY AND 32" HORIZONTALLY. TIES IN ALTERNATE COURSES SHALL BE STAGGERED
- 16. WYTHES IN MULTIPLE-WYTHE BRICK WALLS SHALL BE BONDED BY MEANS OF MASONRY
- 17 ALL BRICK/CMLL WALLS WITH NO CAVITY ARE COMPOSITE PARGE (BACKPLASTER) FIRST WYTHE LAID WITH MORTAR NOT LESS THAN 3/8" THICK.

ALUMINIUM GRATING

- 1. ALUMINUM GRATING SHALL BE A SWAGE-LOCKED RECTANGULAR DESIGN. MAIN BEARING BARS ARE TO BE SPACED 1 3/16" CENTER TO CENTER. CROSS BARS SHALL BE SPACED AT 4" CENTER TO CENTER AND SHALL BE LOCKED TO BEARING BARS. HEIGHT OF BEARING BARS SHALL BE SELECTED TO MATCH EXISTING GRATING HEIGHT AT LOW LIFT STATION MEZZANINE. UNLESS OTHERWISE SHOWN MAIN BEARING BARS SHALL BE 3/6" THICK FOR THE DEPTH SHOWN ON THE PLANS.
- 2. ALUMINUM SHALL BE ACCORDING TO ASTM B221. BEARING BARS SHALL BE PROVIDED WITH A PLAIN FINISH.
- 3. GRATING SHALL BE BANDED.

MIN

MINIMIJM

4. GRATING SHALL BE FASTENED TO SUPPORTS BY MECHANICAL FASTENERS RECOMMENDED BY GRATING MANUFACTURER.

ABBREVIATIONS

ADD'L	=	ADDITIONAL	N.T.S.	=	NOT TO SCALE
ALUM	=	ALUMINUM	0.C.	=	ON CENTER
ARCH	=	ACHITECTURAL	OPEN'G	=	OPENING
BOT	=	BOTTOM	₽	=	PLATE
Q.	=	CENTERLINE	REQ'D	=	REQUIRED
DIA	=	DIAMETER	S.S.	=	STAINLESS STEEL
DWG	=	DRAWING	SSL	=	SHORT SLOTTED
EA	=	EACH			HOLES
EL	=	ELEVATION	STD	=	STANDARD
EF	=	EACH FACE	T&B	=	TOP AND BOTTOM
EMBED	_	EMBEDMENT	TYP	=	TYPICAL
GALV	_	GALVANIZED	W.S.	_	WATERSTOP
LLBB	=	LONG LEGS BACK	Ø	=	DIAMETER
		TO BACK	•	=	DEGREES
LLS	=	LONG SLOTTED HOLES		_	DEGREES
MANV	_	NA A VINALINA			

DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER AND

DESIGNED BY: SMM DRAWN BY: CHECKED BY: DATE CHECKED: 01/1

NOTE: DIMENSIONAL DATA SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS REVISION

STRUCTURAL GENERAL NOTES AND ABBREVIATIONS

PROJECT No O0130014

A-00-102 SHEET 006 OF 088 SHEETS

NOTES

- 1. SEE DRAWING A-00-101 ARCHITECTURAL GENERAL NOTES.
- 2. CONTRACTOR SHALL USE EXTREME CAUTION WHEN CUTTING AND REMOVING CONCRETE FLOOR TO NOT DAMAGE UNDERGROUND CONDUITS AND UTILITIES. EXTREME CAUTION WILL NEED TO BE TAKEN DUE TO CONDUITS IN FLOOR THAT WILL NEED TO BE PROTECTED. CONTRACTOR SHALL TRACE ALL UNDERGROUND CONDUITS IN BUILDING AND GROUNDS ROOM AND MARK LOCATION ON CONCRETE FLOOR PRIOR TO REMOVAL OF FLOOR.
- 3. SEE DRAWING E-10-201 FOR WORK REQUIRED TO REMOVE CONCRETE FLOOR FOR GENERATOR AND SWITCHBOARD BEING REMOVED IN PUMP ROOM
- 4. EXISTING CONCRETE FLOOR IS 7" THICK CONCRETE SLAB WITH 6x6WW MESH MEMBRANE ON 5" SAND CUSHION. CONCRETE SLAB IS THICKENED RUNNING EAST—WEST BELOW WALL BETWEEN BUILDING AND GROUNDS AND MECHANICAL ROOM.
- 5. AFTER EXISTING UNDERGROUND CONDUITS ARE LOCATED AND MARKED ON THE FLOOR, CONTRACTOR SHALL COORDINATE FINAL LOCATION OF ALL SAWCUTTING AND AREAS OF FLOOR REMOVAL WITH OWNER AND ENGINEER AND GET APPROVAL PRIOR TO PROCEEDING.

DEMOLITION KEYNOTES

- 1. REMOVE WALLS AND ALL ASSOCIATED COMPONENTS. PATCH AND PREPARE SURFACES TO ACCEPT NEW PLAN. SALVAGE BRICK.
- 2. SEE ELECTRICAL DRAWINGS FOR DEMOLITION REQUIREMENTS. TERMINATE ALL CONNECTIONS AS NECESSARY PER CODE.
- 3. REMOVE WINDOWS AND ASSOCIATED COMPONENTS. PREPARE SURFACES TO ACCEPT NEW PLAN.
- 4. REMOVE DOOR, FRAME AND ASSOCIATED COMPONENTS. MAINTAIN WALL ABOVE OPENING. PREPARE SURFACES TO ACCEPT NEW PLAN.
- 5. REMOVE DOOR AND FRAME AND WALL ABOVE OPENING. REMOVE CMU WALL CONSTRUCTION TO ROOF STRUCTURE ABOVE. PREPARE SURFACES TO ACCEPT NEW PLAN.
- 6. REMOVE CONCRETE FLOOR AND PREPARE SURFACES TO ACCEPT NEW PLAN.
- 7. REMOVE CONCRETE EQUIPMENT PAD AND PREPARE SURFACES TO ACCEPT NEW PLAN.
- 8. REMOVE STEEL ANGLE IRON AROUND BRICK OPENING. PATCH AND PREPARE SURFACES TO ACCEPT NEW PLAN.
- REMOVE 12" CMU WALL AND ALL ASSOCIATED COMPONENTS. PATCH AND PREPARE SURFACES TO ACCEPT NEW PLAN.
- 10. PROVIDE PERMANENT SHORING TO EXCAVATE EARTH FOR PIPE TROUGH ADJACENT TO EXISTING 12" CMU WALL AND SLAB TO REMAIN IN PLACE.
- 11. REMOVE EXISTING CEILING TILES AND GRID AS NECESSARY IN THIS AREA TO INSTALL NEW PIPING.
- 12. REMOVE CEILING AS REQUIRED FOR INSTALLATION OF NEW DOOR AND WALL ABOVE.
- 13. REMOVE PAINT FROM REMAINING EXPOSED CONCRETE FLOORS.
- 14. REMOVE DOOR AND FRAME.

KEYNOTES

- 1. EXISTING CONCRETE SLAB TO REMAIN.
- 2. EXISTING CONCRETE EQUIPMENT PAD TO REMAIN.
- 3. EXISTING 12" CMU WALL TO REMAIN.
- 4. PROVIDE TEMPORARY WALL MADE FROM PLYWOOD WITH DOOR TO BUILDING AND GROUNDS ROOM FOR DUST CONTROL THROUGHOUT CONSTRUCTION.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: KLW/TOC
DRAWN BY: KLW/JOF
CHECKED BY: TOC

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

ADMINISTRATION AND FILTRATION FACILITY
ENLARGED FIRST FLOOR ARCHITECTURAL DEMOLITION PLAN

PROJECT No. 00130014

DRAWING N

A-10-101

KEY PLAN

- 1. SEE DRAWING A-00-101 FOR ARCHITECTURAL GENERAL NOTES.
- 2. ALL WALLS, FLOORS, AND CEILINGS IN ELECTRICAL ROOM AND MECHANICAL ROOM SHALL BE PAINTED TO MATCH EXISTING SURFACE COLORS.
- 3. PROVIDE 2-HOUR FIRE RATED SEAL AROUND ALL EXISTING AND NEW WALL PENETRATIONS IN ELECTRICAL ROOM WALLS.
- 4. PROVIDE LAMINATE SIGNS (TYPE TO MATCH EXISTING SIGNS) ON ELECTRICAL ROOM AND MECHANICAL ROOM INTERIOR DOORS.
- 5. GENERATOR SHALL BE MOVED TO THE EAST IN THE ELECTRICAL ROOM TO PROVIDE 36" CLEARANCE BETWEEN GENERATOR CONTROL PANEL AND OPENED DAMPER BLADES AND ACTUATOR. FINAL LOCATION SHALL BE DETERMINED IN THE FIELD.

KEYNOTES

- 1. EXISTING CONCRETE SLAB.
- 2. EXISTING CONCRETE EQUIPMENT PAD.
- 3. PROVIDE CONCRETE EQUIPMENT PAD (COORDINATE EXACT SIZE WITH SELECTED EQUIPMENT).
- 4. PROVIDE CONCRETE SLAB TO MATCH EXISTING.
- 5. PROVIDE 6" CMU WALL.
- 6. PROVIDE DOOR AND GLASS PANELS, DOOR C.
- 7. PROVIDE REMOVABLE LOUVER.
- 8. PROVIDE SMOOTH FACE CMU/BRICK WALL.
- 9. PROVIDE 3'-0" x 7'-0" x 1 3/4", 1 1/2 HOUR FIRE RATED DOOR AND FRAME, DOOR A.
- 10. EXISTING 12" CMU WALL.
- 11. EXISTING DOOR.
- 12. PIPE TROUGH.
- 13. REPLACE CEILING TILE AND GRID IN THIS AREA FOLLOWING COMPLETION OF PIPE WORK ABOVE.
- 14. PROVIDE 3'-0" \times 7'-0" \times 1 3/4", 1 1/2 HOUR FIRE RATED DOOR AND FRAME, <u>DOOR B</u>. FIELD VERIFY EXISTING SIZE. DOOR IS LOCATED AT BOTTOM OF STAIR.
- 15. INSTALL DOUBLE 3 1/2" x 3 1/2" STEEL ANGLE LINTEL ABOVE DOOR WITH 8" CMU TO EXTEND TIGHT TO BOTTOM OF PRECAST CONCRETE



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE: 217.373.8900 FAX: 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: KLW/TOC
DRAWN BY: KLW/JRF
CHECKED BY: TOC

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF


HIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY ENLARGED FIRST FLOOR ARCHITECTURAL PLAN

PROJECT No O0130014

A-10-201 SHEET 008 OF 088 SHEETS



ENLARGED ROOF ARCHITECTURAL PLAN (ELEV. 109.0)

NOTES

1. SEE DRAWING A-00-101 FOR ARCHITECTURAL GENERAL NOTES.

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION


ADMINISTRATION AND FILTRATION FACILITY ENLARGED ROOF ARCHITECTURAL PLAN

PROJECT No. O0130014

A-10-202 SHEET 009 OF 088 SHEETS

KEYNOTES

- 1. GENERATOR EXHAUST THIMBLE.
- 2. ROOF MOUNTED EXHAUST FAN. SEE DETAIL 4/A-30-101.
- 3. WATER HEATER VENT PIPING. SEE DETAIL 5/A-30-101.
- 4. BOILER VENT PIPING. SEE DETAIL 5/A-30-101.
- 5. UNIT HEATER VENT PIPING. SEE DETAIL 5/A-30-101.
- 6. SANITARY VENT PIPING. SEE DETAIL 5/A-30-101.
- 7. GENERATOR CRANKCASE FUME DISPOSAL. SEE DETAIL 5/A-30-101.
- 8. PATCH ROOF AND DECK AT MECHANICAL EQUIPMENT REMOVAL. SEE DETAIL 6/A-30-101.
- 9. ROOF MOUNTED EXHAUST FAN. MODIFY EXISTING OPENING AND CURB AS REQUIRED FOR NEW FAN.
- 10. INTAKE AIR LOUVER. SEE DETAIL 4/A-30-101.
- 11. STEEL I-BEAM SUPPORT RAIL OVER B.U.R. TRAFFIC PAD. SEE DETAIL 7/A-30-101.



Clank Dietz

DESIGN FIRM REGISTRATION No. 184-000450

> 125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: KLW/TOC
DRAWN BY: KLW/JRF
CHECKED BY: TOC
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION


ADMINISTRATION AND FILTRATION FACILITY ARCHITECTURAL EXTERIOR ELEVATIONS

PROJECT No.

O0130014

A-10-301

SHEET 010 OF 088 SHEETS



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SMM


SCALING ANY PORTION OF

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION


AND ADMINISTRATION AND FILTRATION FACILITY TRUCTURAL SECTIONS AN DETAILS

PROJECT No


A-10-401




SECTION — WALL AND SLAB DETAILS





SECTION - WALL AND GRATING SUPPORT





SECTION - SHELF SUPPORT





NOTES

- 1. SEE SHEET A-00-102 FOR STRUCTURAL GENERAL NOTES.
- 2. SEE SHEET A-30-103 FOR STRUCTURAL STANDARD DETAILS.
- 3. CONNECTIONS NOT SHOWN ARE SIMILAR TO THOSE SHOWN IN SECTIONS.
- 4. NO MORE THAN ONE EXPANSION ANCHORS PER CMU CELL IS PERMITTED. EXPANSION ANCHORS SHALL BE A MINIMUM OF 2" FROM GROUTED JOINTS. VERIFY ARRANGEMENT OF CMU AND REVISE DIMENSIONS PRIOR TO SHOP DRAWING SUBMITTAL AND FABRICATION.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SMM
DRAWN BY: SMM CHECKED BY:

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ADMINISTRATION AND
FILTRATION FACILITY
STRUCTURAL SECTIONS AND
DETAILS

PROJECT No O0130014

A-10-402

SHEET 012 OF 088 SHEETS

1. SEE DRAWING A-00-101 FOR ARCHITECTURAL GENERAL NOTES.

DEMOLITION KEYNOTES

- 1. REMOVE WALLS AND ALL ASSOCIATED COMPONENTS. PATCH AND PREPARE SURFACES TO ACCEPT NEW PLAN.
- 2. REMOVE WALLS AND ALL ASSOCIATED COMPONENTS TO 10'-0" AFF. PATCH AND PREPARE SURFACES TO ACCEPT NEW PLAN.
- 3. REMOVE DOORS AND ASSOCIATED COMPONENTS. PREPARE SURFACES TO ACCEPT NEW PLAN. SALVAGE DOOR HARDWARE FOR REUSE.
- 4. REMOVE CRANE BEAM, ALL ASSOCIATED COMPONENTS, AND STRUCTURAL SUPPORTS. PATCH CEILING AND EXTERIOR SURFACES TO MATCH ADJACENT EXISTING TO REMAIN.
- 5. REMOVE EXISTING CONCRETE CONTAINMENT CURB.
- 6. REMOVE EXISTING 24" X 24" STEEL GRATING AND INFILL DEPRESSION IN SLAB WITH CONCRETE TO MATCH EXISTING SURFACE.
- 7. REMOVE EXISTING CONCRETE EQUIPMENT PAD. PATCH AND FINISH SURFACE TO MATCH EXISTING.
- 8. REMOVE RAIL TO ACCOMMODATE NEW PLAN. MAINTAIN EXISTING RAIL IN CONDITION TO ACCEPT RAIL FOR NEW WORK.
- 9. RELOCATE EXISTING STAIR STRINGERS, ALUMINUM GRATING STAIR TREADS, AND ALUMINUM PIPE RAILS.
- 10. REMOVE EXISTING STAIR STRINGER SUPPORT ANCHOR BOLTS AND
- 11. RELOCATE EXISTING FIRE EXTINGUISHER.
- 12. REMOVE EXISTING DEHUMIDIFIER, SUPPORT SHELF, AND BRACKETS.
- 13. RELOCATE EXISTING LADDER. REMOVE EXISTING ANCHOR BOLTS AND GROUT. PATCH AND FINISH SURFACE TO MATCH EXISTING.
- 14. REMOVE PART OF CONCRETE WALL AND ALL ASSOCIATED COMPONENTS TO INSTALL NEW LOUVER, LOCATED ABOVE CHEMICAL ROOM. PATCH AND PREPARE SURFACES TO ACCEPT NEW WORK.
- 15. REMOVE PART OF CONCRETE CEILING AND ALL ASSOCIATED COMPONENTS TO INSTALL NEW DUCT OPENING. PATCH AND PREPARE SURFACES TO ACCEPT NEW WORK.
- 16. REMOVE EXISTING BORROWED LIGHT.
- 17. REMOVE EXISTING EPOXY FLOORING.

KEYNOTES

- 1. EXISTING CONCRETE SLAB TO REMAIN.
- 2. EXISTING CMU WALL TO REMAIN.
- 3. EXISTING MEZZANINE TO REMAIN.
- 4. EXISTING CONCRETE EQUIPMENT PAD TO REMAIN.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: KLW/TOC
DRAWN BY: KLW/JRF
CHECKED BY: TOC

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

OW LIFT PUMP STATION ARCHITECTURAL DEMOLITION PLAN

PROJECT No


LΟW

O0130014

SHEET 013 OF 088 SHEETS

A-20-101

ARCHITECTURAL DEMOLITION PLAN (ELEV. 12.0)



NOTES

- 1. SEE DRAWING A-00-101 FOR ARCHITECTURAL GENERAL NOTES.
- 2. ALL WALLS, FLOORS, AND CEILINGS IN GENERATOR ROOM, CHEMICAL ROOM, POTASSIUM PERMANGANATE MIXING SYSTEM AREA AND MODIFIED WALLS (TO EXTERIOR BUILDING WALLS) SHALL BE PATCHED AND PAINTED TO MATCH EXISTING SURFACE COLORS. ALL SUPPORT BRACKETS NOT BEING USED SHALL BE REMOVED AND ALL HOLES IN WALLS, FLOORS, AND CEILING TO BE PATCHED.
- 3. PROVIDE 2-HOUR FIRE RATED SEAL AROUND ALL EXISTING AND NEW PENETRATIONS IN GENERATOR ROOM WALLS OR CEILING.
- PROVIDE LAMINATE SIGNS (TYPE TO MATCH NEW SIGNS AT WTP) ON GENERATOR ROOM AND CHEMICAL ROOM INTERIOR DOORS.

(#) KEYNOTES

- 1. EXISTING CMU WALL
- 2. EXISTING CONCRETE EQUIPMENT PAD.
- 3. PROVIDE CONCRETE EQUIPMENT PAD (COORDINATE EXACT SIZE WITH SELECTED EQUIPMENT). SEE DETAIL 2/A-30-103.
- 4. PROVIDE CMU WALL.
- 5. PROVIDE $3'-0" \times 7'-0" \times 1 3/4"$ DOOR AND FRAME, DOOR D.
- 6. PROVIDE REMOVABLE LOUVERS.
- 7. EXISTING CONCRETE SLAB.
- 8. EXISTING MEZZANINE.
- 9. RELOCATED STAIR STRINGERS, ALUMINUM GRATING STAIR TREADS, AND ALUMINUM PIPE RAILS.
- 10. PROVIDE MEZZANINE EXTENSION.
- 11. RELOCATED FIRE EXTINGUISHER.
- 12. PROVIDE 16" HIGH CONCRETE CONTAINMENT CURB. SEE STRUCTURAL SECTION E/A-20-402.
- 13. PROVIDE 12" THICK CONCRETE TO FILL IN OPENING IN CONCRETE CEILING TO MATCH EXISTING SURFACE. DOWEL REBAR INTO EXISTING CONCRETE CEILING TO TIE CONCRETE TOGETHER. SEE DETAIL C/A-20-402.
- 14. PROVIDE CONCRETE WALL. SEE STRUCTURAL SECTION F/A-20-402.
- 15. CONCRETE ENCASE EXISTING WET WELL VENT PIPE 16" HIGH. POUR CONTINGUOUS WITH CONTAINMENT CURB.
- 16. 52"H x 8'-0"W DARK BRONZE ANODIZED LOUVER, LOCATED ABOVE GENERATOR ROOM.
- 17. EXISTING WET WELL VENT PIPE.
- 18. RELOCATED LADDER. PROVIDE ANCHOR BOLTS AND GROUT AS REQUIRED.
- 19. PROVIDE ANCHOR BOLTS AND GROUT FOR STAIR STRINGERS AS REQUIRED.
- 20. MODIFY SUPPORT POST FOR PLATFORM AND ANCHOR TO CONTAINMENT CURB.
- 21. PROVIDE STEEL LADDER. SEE DETAIL 6 ON SHEET A-30-103.
- 22. REMOVABLE ALUMINUM GUARDRAIL WITH TOE PLATE (LOCATED ON CONCRETE CEILING). SEE DETAIL 5 ON SHEET A 30-103.
- 23. BLOCK IN OPENING FOR WINDOW WITH CMU.
- 24. PROVIDE PAIR 1 1/2" HOUR FIRE RATED DOORS AND FRAME, DOOR E.
- 25. PAINT FLOOR PER SPECIFICATIONS.
- 26. PATCH EPOXY FLOORING TO MATCH EXISTING AT REMOVALS AND NEW FLOORING.
- 27. PROVIDE PROTECTIVE STEEL COVER OVER PIPE CROSSING FLOOR. COVER SHALL BE CONSTRUCTED OF $\frac{1}{2}$ 6" MIN, THICK A36 STEEL PLATE WITH A MINIMUM WIDTH OF 2'-6" IN THE LINE OF PASSAGE. COVER SHALL BE "U" SHAPED AND COMPLETELY FIT OVER PIPE AND INSULATION. PROVIDE FLANGES WITH (2) $\frac{1}{4}$ " CONCRETE SCREWS ON EACH SIDE OF COVER.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: KLW/TOC
DRAWN BY: KLW/JRF
CHECKED BY: TOC


NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

LOW LIFT PUMP STATION FIRST FLOOR ARCHITECTURAL PLAN

PROJECT No. 00130014

DRAWING No.

A-20-201



1. SEE DRAWING A-00-101 FOR ARCHITECTURAL GENERAL NOTES.

KEYNOTES

- REMOVE EXISTING VENT PIPE AND PATCH SURFACE TO MATCH EXISTING.
- 2. USE AND MODIFY EXISTING EXTERIOR WALL PENETRATION. SEAL OPENING WATER TIGHT.
- 3. REMOVE EXISTING EXHAUST PIPE AND PATCH SURFACE TO MATCH



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION


LOW LIFT PUMP STATION ARCHITECTURAL EXTERIOR ELEVATIONS

PROJECT No. O0130014

A-20-301 SHEET 015 OF 088 SHEETS

EXISTING NORTHWEST ELEVATION NO SCALE

01/22/2010



DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER


DESIGNED BY: SMM DRAWN BY: SMM

SCALING ANY PORTION OF

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

PROJECT No.

A-20-401



Clark D'etz

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SMM
DRAWN BY: SMM
CHECKED BY: PS
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION


LOW LIFT PUMP STATION STRUCTURAL PLANS AND SECTIONS


PROJECT No. 00130014

0010001

A-20-402
SHEET 017 OF 088 SHEETS

CONTRACTOR SHALL VERIFY DIMENSIONS OF EXISTING SLAB OVER PROPOSED GENERATOR ROOM.





CONSTRUCTION PROCEDURE


- 1. IF PRESENT, REMOVE EXISTING WATERPROOFING AND PAINT. CLEAN EXISTING CONCRETE SURFACE THOROUGHLY OF ALL MUD, SCUM, DEBRIS AND LOOSE
- 2. BUSH HAMMER TO ACHIEVE ROUGH SURFACE.

NO SCALE

- 3. APPLY BONDING AGENT TO EXISTING CONCRETE SURFACE; SEE SPECIFICATIONS.
- 4. PLACE NEW CONCRETE AFTER ERECTION OF REINFORCEMENT AND FORMWORK.

NEW TO EXISTING CONCRETE


CONSTRUCTION DETAILS



*PAD SIZE TO BE DETERMINED FROM EQUIPMENT MANUFACTURER'S APPROVED SHOP DRAWINGS. SEE DRAWINGS FOR APPROXIMATE DIMENSIONS.

NO SCALE

EQUIPMENT PAD REINFORCEMENT



NOTE: KEYWAY IS OPTIONAL. DO NOT PROVIDE IN SLAB LESS THAN 6" THICK OR IN COMBINATION WITH DOWEL

1/4" MAX. SAWED JOINT 4" COMPACTED GRANULAR BEDDING, TYP. BARRIER, TYP.

NOTE: AT THE CONTRACTOR'S OPTION "STRESS LOCK"

CONSTRUCTION JOINT NO SCALE

SLAB THICKNESS

5"-6"


DOWEL DIA. AND LENGTH	DOWEL SPACING
3/4"ø x 16"	12"
1"ø x 18"	12"
/	

7"-8" 1"ø x 9"-11" 1 1/4"ø x18' 12" 3/8"ø x 18" 12" 12"

SLAB ON GRADE JOINT DETAILS FOR BUILDING SLAB ONLY.

NOTES


1. SEE SHEET A-00-102 FOR STRUCTURAL GENERAL NOTES.



PLASTIC CONTROL JOINT OR APPROVED EQUAL MAY BE USED INSTEAD OF SAWED JOINT.

CONTRACTION JOINT NO SCALE

SECTION



RAILS-

1/4

*1 1/2" DIA. SCH. 40 POST @ 5'-0" CTRS. (MAX.)

-SEE POST MOUNTING DETAIL

1½" DIA. POST. (1.90" O.D.)

ALUMINUM PIPE FLANGE

WITH (3) ¼" S.S. FASTENERS AND SET SCREW

2" I.D. CORED HOLE IN NEW OR EXIST. CONCRETE

ELEVATION

-TOP OF CONCRETE WALKING SURFACE

-1/4"x4" TOE PLATE

1. LADDER ATTACHED TO MASONRY WALLS SHALL ALSO BE BOLTED TO THE FLOOR.

2. ALL EXPANSION BOLTS SHALL BE STAINLESS STEEL. WHEN CONNECTING TO CMU, CELLS SHALL BE GROUTED PRIOR TO INSTALLATION OF BOLTS.

<u>STEEL LADDER DETAIL</u>



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SMM DRAWN BY:

CHECKED BY: NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF HIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

DETAILS STRUCTURAL


PROJECT No. O0130014

A-30-103

SHEET 020 OF 088 SHEETS

PROVIDE PREFAB CORNER AND TEES SEE PLAN AND NOTES FOR LOCATION OF VERTICAL REINF.-8" MIN. LAP SEE SPECIFICATIONS TYP FOR SIZE OF REINF. PROVIDE PREFAB CORNER AND TEES -SEE DETAIL FOR

TYP JOINT REINFORCEMENT DETAIL



APPLIES TO (1) ALL OPENINGS IN NON-STRUCTURAL PARTITIONS OVER 100 IN. SQ. AND (2) ANY OPENING 2' OR LESS BOTH WAYS BUT OVER

100 IN. SQ. IN STRUCTURAL

PARTITION OR EXTERIOR WALL.


APPLIES TO STRUCTURAL PARTITION AND EXTERIOR WALLS WHEN OPENING EXCEEDS 2' BUT NOT MORE THAN 4' IN EITHER DIRECTION.

APPLIES TO STRUCTURAL PARTITION AND EXTERIOR WALLS WHEN OPENING EXCEEDS 4' IN EITHER DIRECTION.

NOTES:

- 1. FOR VERTICAL REINFORCEMENT OF BARS, EA. BAR SHALL BE PLACED IN A SEPARATE CELL.
- 2. VERTICAL BARS SHALL BE BARS OF THE SAME SIZE, EXTENT, AND ANCHORAGE AS THE TYPICAL REINFORCEMENT IN THAT WALL UNLESS OTHERWISE NOTED.
- 3. VERTICAL REINFORCEMENT BARS CAN BE PART OF THE NORMAL VERTICAL REINFORCEMENT.

REINFORCEMENT AROUND WALL OPENINGS IN C.M.U.



WALL TO WALL ANCHORAGE AT INTERSECTION OF BEARING WALLS

BOND BEAM AT SECOND FLOOR OR ROOF 2'-0" OR 48 BAR DIAMETERS WHICH-EVER IS LARGER CONTINUE AROUND CORNER AS REQ'D (TYP.) 2'-0" OR 48 BAR DIAMETERS WHICH-EVER IS LARGER TOP OF FOUNDATION WALL OR SLAB

NOTES

- 1. SEE SHEET A-00-102 FOR STRUCTURAL GENERAL NOTES.
- 2. BOND PATTERNS SHALL MATCH EXISTING CONDITIONS.
- 3. CMU WALL VERTICAL REINFORCEMENT:
- 3.1. UNLESS NOTED OTHERWISE, PROVIDE #4 AT 32" ON-CENTER.
- PROVIDE (1) #4 AT EACH CORNER AND AT EACH INTERSECTION OF WALLS
- PROVIDE (1) #4 AT EACH SIDE OF OPENINGS 4'-0" WIDE OR
- 3.4. PROVIDE (2) #4 AT EACH SIDE OF OPENINGS GREATER THAN 4'-0" WIDE
- 3.5. PROVIDE #4 DOWELS INTO SLAB OR FOUNDATION WALL FOR EACH VERTICAL BAR IN CMU WALLS. PROVIDE MIN. EMBEDMENT OF 6".
- 4. CMU HORIZONTAL REINFORCEMENT: WHERE BOND BEAMS TERMINATE INTO EXISTING WALL, PROVIDE #4 DOWEL EXISTING BOND BEAM WITH 6" MIN. EMBEDMENT. PROVIDE 2'-0" MIN. LAP BETWEEN DOWEL AND NEW BOND BEAM REINFORCEMENT.
- 5. FOR LINTELS SEE DETAILS AND SECTIONS FOR EACH LOCATION



DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SMM DRAWN BY:

CHECKED BY: NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF HIS DRAWING


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

DETAILS

STRUCTURAL

PROJECT No. O0130014

A-30-104 SHEET 021 OF 088 SHEETS



NOTE: SEE SHEET E-10-401 FOR TRANSFORMER LOCATION

TRANSFORMER PAD

REINFORCEMENT AROUND DOOR OPENING IN C.M.U. NO SCALE

PROCESS GENERAL NOTES

- 1. NOT ALL OF THE CAS, POWER, OR TELEPHONE LINES, WHETHER ABOVE OR BELOW GROUND, HAVE BEEN SHOWN ON THE DRAWINGS. THE CONTRACTOR MUST REALIZE THAT THE ACTUAL LOCATIONS OF THE UTILITIES SHOWN ON THE DRAWINGS MAY BE DIFFERENT FROM THE LOCATIONS INDICATED.
- 2. THE LOCATIONS OF THE EXISTING YARD PIPING, SUCH AS RAW SEWAGE LINES, DRAIN LINES, NON-POTABLE WATER LINES, ETC., AS SHOWN ON THE DRAWINGS, HAS BEEN DETERMINED FROM PLANS FOR THE EXISTING FACILITIES AND ARE GIVEN FOR THE CONVENIENCE OF THE CONTRACTOR. THE CONTRACTOR MUST ASSUME RESPONSIBILITY FOR ALL PIPING AND MUST REALIZE THAT THE ACTUAL LOCATIONS MAY BE DIFFERENT FROM THOSE INDICATED ON THE DRAWINGS.
- 3. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAINTAIN IN SERVICE THE WATER TREATMENT FACILITY, ALL EXISTING PROCESS PIPING, AND ALL EXISTING UTILITIES ENCOUNTERED DURING CONSTRUCTION UNLESS OTHERWISE INDICATED IN THE DRAWINGS. ANY PIPING WHICH CAN BE REMOVED DURING CONSTRUCTION WITHOUT UNDUE INTERRUPTION OF SERVICE MAY BE REMOVED AND REPLACED BY THE CONTRACTOR WITH THE PERMISSION OF THE OWNER.
- 4. BEFORE WORKING WITH OR AROUND EXISTING UTILITIES, THE APPLICABLE UTILITY COMPANY SHALL BE CONTACTED BY THE CONTRACTOR.
- 5. THE CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE AREA AND NO EXTRA COMPENSATION CONNECTED WITH OVERHEAD UTILITIES WILL BE ALLOWED.
- 6. THE CONTRACTOR IS SOLELY AND COMPLETELY RESPONSIBLE FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THIS PROJECT, INCLUDING EROSION CONTROL AND THE SAFETY OF ALL PERSONS AND PROPERTY; THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS, AND THE CONTRACTOR SHALL DEFEND, INDEMNIFY AND HOLD THE OWNER AND THE ENGINEER HARMLESS FROM ALL LIABILITY, REAL, OR ALLEGED, IN CONNECTION WITH THE PERFORMANCE OR WORK ON THE PROJECT EXCEPTING FOR LIABILITY ARISING FROM THE SOLE NEGLIGENCE OF THE OWNER OF THE ENGINEER.
- 7. INFORMATION ON DETAIL DRAWINGS TAKES PRIORITY OVER ALL GENERAL DRAWINGS AND SCHEDULES. CONFLICTS SHALL BE RESOLVED ACCORDINGLY.
- 8. WHEN CONNECTIONS ARE TO BE MADE TO EXISTING PIPING AND STRUCTURES, THE LOCATION AND ELEVATION OF THE EXISTING PIPING SHALL BE FIELD VERIFIED AND NOTIFICATION GIVEN TO THE OWNER IF THE EXISTING PIPING IS FOUND TO BE DIFFERENT THAN THAT SHOWN ON THE DRAWINGS.
- THE COST OF ABIDING BY THE PROVISIONS OF PERMITS ISSUED BY VARIOUS AGENCIES SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. ALL ASSOCIATED BONDING REQUIREMENTS AND COSTS ARE INCIDENTAL TO THE CONTRACT

PROCESS LEGEND POTASSIUM PERMANGANATE PIPING CARBON FEED PIPING WATER PIPING POTABLE WATER PIPING -NPW-NON-POTABLE WATER PIPING EXISTING PIPING ——(NAME)— ELBOW DOWN OR AWAY ELBOW UP OR TOWARDS \bowtie VALVE \oslash **GAUGE** TO BE REMOVED

NEW CONNECTION TO EXISTING

<u>PROCESS</u>	AND	INSTRUMENTATION	DIAGRAM	LEGEND
	PROCE	ESS PIPING		
	ELECT	RICAL SIGNAL		
\bowtie	VALVE			
	PROCE	ESS FLOW DIRECTION		
	VIEWIN	IG GLASS		
D D	DISCR	ETE SIGNAL		
⊳ A	ANALO	G SIGNAL		
	— UNIT I	PROCESS NUMBER		
(xx xxxx)	FIELD	MOUNTED DEVICE		
	— UNIT I	NUMBER		

	PROCESS	AND INSTRUM	ENTATION DIAGRA	M ABBREVIATION	S
	FIRST LETTER			SUCCEEDING LETTERS	
	MEASURED OR INITIATING VARIBLE	MODIFIER	READOUT OR PASSIVE FUNCTION	OUTPUT FUNCTION	MODIFIER
Α	ANALYSIS		ALARM		
В	BURNER, COMBUSTION		USER'S CHOICE	USER'S CHOICE	USER'S CHOICE
С	USER'S CHOICE			CONTROL	
D	USER'S CHOICE	DIFFERENTIAL			
Ε	VOLTAGE		SENSOR (PRIMARY ELEMENT)		
F	FLOW RATE	RATIO (FRACTION)			
G	USER'S CHOICE		GLASS, VIEWING DEVICE		
Н	HAND				HIGH, OPEN
1	CURRENT (ELECTRICAL)		INDICATE		
J	POWER	SCAN			
K	TIME, TIME SCHEDULE	TIME RATE OF CHANGE			
L	LEVEL		LIGHT		LOW, CLOSED
М	USER'S CHOICE	MOMENTARY			MIDDLE, INTERMEDIATE
N	USER'S CHOICE		USER'S CHOICE	USER'S CHOICE	USER'S CHOICE
0	USER'S CHOICE		ORIFICE, RESTRICTION		
Р	PRESSURE, VACUUM		TEST POINT CONNECTION		
Q	QUANTITY	INTEGRATE, TOTALIZE			
R	RADIATION		RECORD		
S	SPEED, FREQUENCY	SAFETY		SWITCH	
Т	TEMPERATURE			TRANSMIT	
U	MULTIVARIABLE		MULTIFUNCTION	MULTIFUNCTION	MULTIFUNCTION
٧	VIBRATION, MECHANICAL ANALYSIS			VALVE, DAMPER, LOUVER	
W	WEIGHT, FORCE		WELL		
Х	UNCLASSIFIED	X AXIS	UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED
Υ	EVENT, STATE OR PRESENCE	Y AXIS		RELAY, COMPUTE, CONVERT	
Z	POSITION, DIMENSION	Z AXIS		DRIVER, ACTUATOR	



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: JLE
DRAWN BY: CWL
CHECKED BY: TKB
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

> PROCESS GENERAL NOTES, LEGEND, AND ABBREVIATIONS

PROJECT No.
00130014

DRAWING No.

PR-00-101



DEMOLITION KEYNOTES

- 1. RELOCATE EXISTING SCALE INDICATOR PANEL.
- 2. REMOVE EXISTING CHLORINE DETECTOR PANEL AND ASSOCIATED DETECTOR IN CHEMICAL ROOM.
- 3. REMOVE EXISTING PORTABLE EYEWASH STATION.
- 4. REMOVE EXISTING POTASSIUM PERMANGANATE FEED PIPING.
- REMOVE EXISTING HYDROPNEUMATIC TANK AND TURN OVER TO OWNER. REMOVE ASSOCIATED PIPING.
- REMOVE EXISTING TURBINE WATER PUMP AND TURN OVER TO OWNER. REMOVE ASSOCIATED PIPING.
- 7. REMOVE EXISTING CHEMICAL FEED PIPING. EXISTING PIPE SLEEVE FEEDING INTO SHORE WELL TO REMAIN.
- 8. REMOVE EXISTING RAW WATER PIPING FEEDING THRU CONCRETE WALL TO AMMONIA ROOM. PATCH HOLE IN WALL TO MATCH EXISTING SURFACE
- 9. REMOVE EXISTING WATER HOSE AND REEL.
- 10. REMOVE EXISTING 1,300 GALLON FIBERGLASS SODIUM HYPOCHLORITE TANK.
- 11. REMOVE EXISTING SODIUM HYPOCHLORITE CHEMICAL METERING PUMP, AND CONTROLLER AND TURN OVER TO OWNER. REMOVE ASSOCIATED PIPING.
- 12. REMOVE EXISTING POTASSIUM PERMANGANATE CHEMICAL METERING PUMP AND CONTROLLER AND TURN OVER TO OWNER.
- 13. REMOVE EXISTING 480 GALLON FIBERGLASS POTASSIUM PERMANGANATE MIXING TANK AND MIXER.
- 14. RELOCATE EXISTING 50 GALLON PLASTIC TUB FOR POTASSIUM PERMANGANATE WASTE.
- 15. RELOCATE EXISTING EDUCTOR PUMP.
- 16. RELOCATE EXISTING RAW WATER SUPPLY BOOSTER PUMP AND FILTER CANISTER.
- 17. RELOCATE EXISTING POTASSIUM PERMANGANATE SCALE.

KEYNOTES

- 1. EXISTING RAW WATER DISCHARGE PIPING TO REMAIN.
- 2. EXISTING VALVE ON RAW WATER PIPING TO REMAIN. PROVIDE BLIND FLANGE TO CAP OFF VALVE.
- 3. EXISTING PIPE SLEEVES FEEDING INTO SHORE WELL TO REMAIN AND BE REUSED.
- 4. EXISTING POTASSIUM PERMANGANATE FEED PIPING TO REMAIN AND BE REUSED.



DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: JLE
DRAWN BY: JRF
CHECKED BY: TKB

DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


LOW LIFT PUMP STATION FIRST FLOOR PROCESS DEMOLITION PLAN

PROJECT No. 00130014

..........

PR-20-101

SHEET 023 OF 088 SHEETS



NOTES

 SEE DRAWING PR-00-101 FOR PROCESS GENERAL NOTES, LEGEND, AND ABBREVIATIONS.

KEYNOTES

- PROVIDE 200' OF 2" FLEXIBLE PLASTIC PIPE (SIMILAR TO EXISTING CARBON FEEDER PIPE) FOR OWNER'S USE FOR CONNECTION TO CARBON FEEDER AND TO FEED INTO SHORE WELL.
- 2. CORE HOLE IN CONCRETE WALL AND INSTALL 2" PIPE THROUGH OPENING STUBBING PIPE 2" FROM WALL ON EACH SIDE (LOCATE PIPE 6" ABOVE INTERIOR CONCRETE SLAB AND COORDINATE FINAL LOCATION IN THE FIELD WITH THE ENGINEER). PROPERLY ANCHOR PIPE TO WALL AND SEAL AROUND PIPE WATERTIGHT. PROVIDE QUICK CONNECT COUPLING (SIMILAR TO EXISTING COUPLING ON CARBON FEEDER) ON END OF PIPE AND FOR CONNECTION TO EACH END OF THE PIPE. ALSO PROVIDE QUICK CONNECT BLANK CAP FOR EACH SIDE OF PIPE TO BE USED DURING WINTER TIME TO COVER OPENING IN PIPE.
- 3. CUT OFF EXISTING 4" STEEL PIPING FEEDING INTO SHOREWELL FLUSH WITH FLOOR AND PROVIDE SMOOTH FINISH ON CUT. PROVIDE EXTREME CARE TO NOT GET STEEL SHAVING IN THE SHOREWELL. OWNER WILL INSTALL 2" FLEXIBLE PLASTIC PIPE INTO OPENING TO FEED CARBON INTO SHOREWELL.
- 4. EXISTING HATCH OPENING INTO SHOREWELL.
- 5. EXISTING LOW LIFT PUMP.
- PROVIDE POTASSIUM PERMANGANATE CHEMICAL METERING PUMPS P-4010, P-4011 AND CONTROLLERS SIC-4010, SIC-4011. PROVIDE STAINLESS STEEL SUPPORT FRAME AND FIBERGLASS GRATING SIMILAR TO EXISTING.
- 7. PROVIDE 625 GALLON FIBERGLASS POTASSIUM PERMANGANATE MIXING TANK $\underline{\mathsf{T-4007}}$.
- 8. RELOCATED 50 GALLON PLASTIC TUB FOR POTASSIUM PERMANGANATE WASTF
- 9. RELOCATED POTASSIUM PERMANGANATE SCALE WE-4006.
- 10. RELOCATED SCALE INDICATOR PANEL WIT-4006.
- 11. SPACE FOR 25 KG BUCKETS OF POTASSIUM PERMANGANATE.
- 12. RELOCATED EDUCTOR PUMP P-4003.
- 13. RELOCATED RAW WATER SUPPLY BOOSTER PUMP $\underline{P-4004}$ AND FILTER CANISTER $\underline{FT-4004}$.
- 14. EXISTING RAW WATER DISCHARGE PIPING.
- 15. CONCRETE WALL.
- 16. EXISTING PIPE SLEEVE AND POTASSIUM PERMANGANATE FEED PIPING FEEDING INTO SHORE WELL.
- 17. PROVIDE POTASSIUM PERMANGANATE FEED PIPING FROM POTASSIUM PERMANGANATE SYSTEM. ROUTE PIPING ALONG WALL WITH EXISTING POTABLE WATER PIPING AND MOUNT ON EXISTING PIPE SUPPORTS.
- 18. PROVIDE 16" HIGH CONCRETE CONTAINMENT CURB.
- 19. EXISTING WET WELL VENT.
- 20. 4" CONCRETE EQUIPMENT PAD.
- 21. EXISTING POTASSIUM PERMANGANATE FEED PIPING.
- 22. CONNECT NEW POTASSIUM PERMANGANATE FEED PIPING TO EXISTING PIPING AS REQUIRED.
- 23. PROVIDE MIX TANK AGITATOR M-4007.
- 24. PROVIDE TANK LEVEL TRANSDUCER LE-4007.
- 25. PROVIDE TANK LEVEL TRANSMITTER LIT-4007.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: JLE

DRAWN BY: JRF
CHECKED BY: TKB
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF

THIS DRAWING.

//21/11 ISSUED FOR CONS

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION


LOW LIFT PUMP STATION FIRST FLOOR PROCESS PLAN

PROJECT No. 00130014

.....


PR-20-201

SHEET 024 OF 088 SHEETS









PLUMBING GENERAL DEMOLITION NOTES

- VERIFY EXACT SIZE AND LOCATION OF EXISTING UTILITIES PRIOR TO START OF DEMOLITION.
- DISCONNECT ALL PLUMBING CONNECTIONS TO EQUIPMENT/FIXTURES BEING REMOVED BY OTHERS.
- UNLESS OTHERWISE NOTED, REMOVAL OF PIPING SHALL INCLUDE ALL INSULATION, VALVES, HANGERS, SUPPORTS, EQUIPMENT PADS, FLASHING, CONTROLS, AND ASSOCIATED ACCESSORIES.
- UNLESS OTHERWISE NOTED, REMOVAL OF PIPING SHALL BE BACK TO THE MAIN OR LAST ACTIVE SERVICE AND CAPPED.
- ALL OPENINGS OR HOLES LEFT IN EXISTING WALLS, FLOORS, AND CEILINGS INCLUDING CHASES, SHALL BE PATCHED TO MATCH EXISTING CONDITIONS BY THE CONTRACTOR WHOSE WORK HAS CREATED THE OPENING OR HOLE. PATCHING SHALL BE IN ACCORDANCE WITH THE APPROPRIATE DIVISION OF THE SPECIFICATIONS.

PLUMBING GENERAL NOTES

- PIPING IS SHOWN IN SCHEMATIC FORM ONLY, CHANGES IN ELEVATIONS ARE NOT NECESSARILY SHOWN. ROUTE PIPING IN AN ORDERLY MANNER AS REQUIRED FOR CLEARANCE WITH STRUCTURAL CONDITIONS. COORDINATE LOCATION OF PIPING WITH OTHER TRADES PRIOR TO INSTALLATION. WHERE POSSIBLE, RACK PIPING HORIZONTALLY OR VERTICALLY.
- 2. COORDINATE LOCATIONS AND SIZES OF CONNECTIONS TO EQUIPMENT.
- 3. ALL CONNECTIONS TO, OR SHUTDOWNS OF, EXISTING SYSTEMS SHALL BE COORDINATED WITH THE OWNER TO PROVIDE MINIMUM INTERFERENCE WITH THEIR OPERATION AND DOWNTIME OF THE SYSTEM. PROVIDE PROPOSED PHASING PLAN FOR CONNECTIONS TO EXISTING SERVICES TO OWNER FOR APPROVAL PRIOR TO
- 4. PROVIDE AND INSTALL ISOLATION VALVES IN ALL BRANCH PIPING, EXCLUDING SANITARY SEWER, VENT, AND STORM WATER SYSTEMS.
- 5. PROVIDE AND INSTALL ISOLATION VALVES FOR BATTERIES OF FIXTURES AND AT INDIVIDUAL BATHROOM GROUPS
- 6. CONNECTIONS TO EQUIPMENT SHALL BE PROVIDED WITH ISOLATION VALVES AND UNIONS TO FACILITATE EQUIPMENT REMOVAL.
- 7. LOCATE ALL ISOLATION VALVES IN AN ACCESSIBLE LOCATION. WHERE VALVES ARE NOT ACCESSIBLE PROVIDE 12X12 ACCESS DOOR.
- 8. UNLESS OTHERWISE NOTED. CONCEAL ALL PLUMBING PIPING ABOVE CEILINGS. IN WALLS, OR INSIDE CHASES.
- CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ADEQUATE SUPPORTING SYSTEMS AND DEVICES FOR ALL PLUMBING PIPING, EQUIPMENT, AND
- 10. COORDINATE THE LOCATIONS AND HEIGHTS OF ALL FIXTURES WITH ARCHITECTURAL PLANS AND CODE REQUIREMENTS PRIOR TO INSTALLATION.
- 11. PROVIDE AND INSTALL SLEEVES FOR ALL PIPING PASSING THROUGH WALLS, AND
- 12. PROVIDE FIRE STOPPING OR FIRE CAULK AT <u>ALL</u> PENETRATIONS OF FIRE AND/OR SMOKE RATED WALLS, CEILINGS, AND FLOORS. SEE ARCHITECTURAL PLANS FOR LOCATIONS OF FIRE AND/OR SMOKE RATED WALLS, CEILINGS, AND FLOORS.
- 13. LOCATE ALL PLUMBING EQUIPMENT TO PROVIDE MANUFACTURER'S MINIMUM SERVICE CLEARANCES
- 14. VENTS SERVING FLOOR DRAINS LOCATED BELOW GRADE SHALL NOT BE COMBINED BELOW THE LEVEL OF THE FINISHED FLOOR.
- 15. ALL EXISTING INSULATION ON WATER LINES SHALL BE REPLACED WITH NEW IN THE BUILDING AND GROUNDS ROOM AT THE WATER TREATMENT PLANT AND PIPING THAT IS BEING MODIFIED AT LOW LIFT PUMP STATION. INSULATION SHALL BE PAINTED AND LABELED TO MATCH EXISTING.

PLUMBING ABBREVIATIONS

COLD WATER CW HOT WATER HW HWR HOT WATER RETURN SANITARY VENT SAN SANITARY SEWER TW TEMPERED WATER <u>CO</u> LCO CLEANOUT IN FLOOR LINE CLEANOUT WATER HEATER <u>WH-#</u> <u>HB-#</u> HOSE BIB/HYDRANT

PLUMBING LEGEND

SYMBOL	DESCRIPTION	<u>SYMBOL</u>	DESCRIPTION
PW	POTABLE COLD WATER		ELBOW DOWN
HW	DOMESTIC HOT WATER		ELBOW UP
Tw	TEMPERED WATER		RISE OR DROP
NPW	NON-POTABLE COLD WATER		TEE DOWN
D	DRAIN		TEE UP
SAN	SANITARY DRAIN, ABOVE GRADE		CAP OR BLIND FLANGE
— — — SAN— — —	SANITARY DRAIN, BELOW GRADE		UNION
V	SANITARY VENT, ABOVE GRADE	——————	BALL VALVE
	SANITARY VENT, BELOW GRADE		GATE VALVE
ST	STORM DRAIN PIPING		CHECK VALVE
G	NATURAL GAS	o ^{CO}	CLEANOUT
CA	COMPRESSED AIR		LINE TYPE CLEANOUT
(NAME)	EXISTING PIPING	F	HOSE BIBB
		<i>'////////////////////////////////////</i>	TO BE REMOVED
		•	NEW CONNECTION TO EXISTING

PLUMBING FIXTURE ROUGH-IN SCHEDULE								
FIXTURE	WASTE	VENT	TRAP	COLD WATER	HOT WATER	TEMPERED WATER		
EMERGENCY SHOWER	DISCHARGE TO FLOOR					1-1/4"		
FLOOR DRAIN	4" MIN.	2" MIN.	NOTE 3					
CLEANOUT	3" MIN.							

NOTES:


- ALL DRAIN, WASTE, OR VENT LINES LOCATED BELOW A SLAB SHALL BE A MINIMUM OF 2" IN DIAMETER.
- 2. THE ABOVE SCHEDULE DENOTES THE MINIMUM REQUIREMENTS FOR THE ROUGH-IN OF EACH PLUMBING FIXTURE
- 3. TRAP SHALL BE SAME SIZE AS WASTE.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

ATER TREATMENT PLANT D LOW LIFT PUMP STATION STANDBY POWER WATE AND L

DESIGNED BY: NTP DRAWN BY: NTP CHECKED BY: DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS REVISION

PLUMBING GENERAL NOTES, LEGEND AND ABBREVIATIONS

PROJECT No O0130014

굡

P-00-101 SHEET 027 OF 088 SHEETS



1. SEE DRAWING P-00-101 FOR GENERAL NOTES, LEGEND AND ABBREVIATIONS.

DEMOLITION KEYNOTES

- 1. EXISTING NATURAL GAS SERVICE METER TO BE REMOVED BY WE ENERGIES.
- 2. EXISTING UNDERGROUND NATURAL GAS SERVICE TO BE ABANDONED IN

KEYNOTES

- 1. NATURAL GAS SERVICE METER BY WE ENERGIES.
- 2. HIGH PRESSURE NATURAL GAS PIPE PROVIDED BY WE ENERGIES.
- 3. EXISTING WE ENERGIES UNDERGROUND HIGH PRESSURE NATURAL GAS



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

WATER TREATMENT PLANT PLUMBING SITE PLAN

PROJECT No. O0130014

P-10-001

SHEET 028 OF 088 SHEETS



DEMOLITION KEYNOTES

- 1. EXISTING NATURAL GAS METER TO BE REMOVED AND REPLACED AT THE NEW LOCATION BY WE ENERGIES. SEE DRAWING P-10-201 FOR NEW LOCATION. CONTRACTOR SHALL COORDINATE THE REPLACEMENT REQUIREMENTS WITH WE ENERGIES.
- 2. REMOVE EXISTING 4" GAS PIPING INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES TO ALLOW FOR CONNECTIONS TO NEW GAS PIPING. TEMPORARILY CAP PIPING. SEE DRAWING P-10-201 FOR NEW WORK.
- REMOVE EXISTING GAS REGULATOR. ASSOCIATED PIPING SHALL BE REMOVED TO ALLOW FOR CONNECTIONS TO NEW GAS PIPING. PATCH OPENING IN ROOF WATER TIGHT. SEE DRAWING P-10-201 FOR NEW
- 4. REMOVE EXISTING GAS PIPING TO HEATING HOT WATER BOILER INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES.
- 5. REMOVE EXISTING POTABLE WATER PIPING TO HEATING HOT WATER BOILER INCLUDING ALL INSULATION, SUPPORTS, HANGERS AND
- 6. EXISTING HEATING HOT WATER BOILER TO BE REMOVED.
- 7. RELOCATE EXISTING DOMESTIC HOT WATER HEATER. DISCONNECT AND REMOVE ALL POTABLE WATER, HOT WATER AND GAS PIPING COMPLETE INCLUDING INSULATION, SUPPORTS AND HANGERS. SEE DRAWING P-10-201 FOR NEW LOCATION.
- 8. RELOCATE EXISTING AIR COMPRESSOR. CONTRACTOR SHALL REMOVE AND RECONNECT COMPRESSED AIR PIPING, DRYER, FILTER, DRAINS, VALVES, SUPPORTS, HANGERS, AND ALL ASSOCIATED ACCESSORIES AT NEW LOCATION. VERIFY LOCATION OF ALL EXISTING PIPING PRIOR TO DEMOLITION. SEE DRAWING P-10-202 FOR NEW LOCATION.
- REMOVE EXISTING WALL MOUNTED HOSE BIBB. REMOVE 3/4" POTABLE WATER PIPING BACK TO MAIN INCLUDING ALL SUPPORTS, HANGERS, AND ACCESSORIES TO ALLOW FOR CONNECTION TO NEW POTABLE WATER PIPING. TEMPORARILY CAP PIPING FOR LATER EXTENSION. SEE DRAWING P-10-201 FOR NEW WORK.
- 10. REMOVE EXISTING 3/4" HOT WATER PIPING INCLUDING ALL SUPPORTS, HANGERS, AND ACCESSORIES TO ALLOW FOR CONNECTION TO NEW HOT WATER PIPING. TEMPORARILY CAP PIPING. SEE DRAWING P-10-201 FOR NEW WORK.
- 11. REMOVE EXISTING 2" GAS PIPING INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES TO ALLOW FOR CONNECTION TO NEW GAS PIPING. TEMPORARILY CAP PIPING. SEE DRAWING P-10-201 FOR NEW WORK.
- 12. EXISTING NATURAL GAS GENERATOR TO BE REMOVED. DISCONNECT AND REMOVE 2" GAS PIPING TO GENERATOR AND REMOVE PIPING DOWN TO LOWER LEVEL.
- 13. REMOVE EXISTING FLOOR DRAIN IN SLAB.
- 14. REMOVE EXISTING FLOOR CLEANOUT IN SLAB.
- 15. REMOVE EXISTING POTABLE WATER PIPING AND DRAIN PIPING FROM HEAT EXCHANGER DOWN THRU FLOOR. PATCH OPENING IN FLOOR TO MATCH EXISTING SURFACE.
- 16. REMOVE EXISTING 3/4" GAS VENT PIPING EXPOSED ALONG WALL INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES. PATCH OPENING IN EXTERIOR WALL WATER TIGHT.
- 17. REMOVE EXISTING 1 1/2" GAS PIPING FROM GENERATOR DOWN THROUGH FLOOR. PATCH OPENING IN FLOOR TO MATCH EXISTING SURFACE.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

DATE CHECKED: 01/11 NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.


3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

DEMOUNT TITLE
ADMINISTRATION AND
FILTRATION FACILITY
FIRST FLOOR
PLUMBING
DEMOLITION PLAN

O0130014

P-10-101 SHEET 029 OF 088 SHEETS

KEY PLAN



1. SEE DRAWING P-00-101 FOR GENERAL NOTES, LEGEND, AND

DEMOLITION KEYNOTES

- 1. REMOVE EXISTING 4" SANITARY PIPING BELOW SLAB AND UP TO
- 2. REMOVE EXISTING 4" SANITARY PIPING BELOW SLAB.
- 3. REMOVE EXISTING 4" SANITARY PIPING BACK TO MAIN AND CAP.
- 4. REMOVE EXISITING 4" SANITARY PIPING UP TO FLOOR CLEANOUT.
- 5. REMOVE EXISTING 1 1/2" GAS PIPING UP THRU FLOOR TO EXISTING NATURAL GAS GENERATOR. PROVIDE SHUT-OFF VALVE AND CAP AT
- 6. REMOVE EXISTING DRAIN PIPING FROM GENERATOR HEAT EXCHANGER. REMOVE SANITARY PIPING BACK TO MAIN AND CAP. PATCH OPENING IN SLAB TO MATCH EXISTING.
- 7. REMOVE EXISTING POTABLE WATER PIPING UP THROUGH SLAB FROM GENERATOR HEAT EXCHANGER. PROVIDE SHUT—OFF VALVE AND CAP
- 1. EXISTING 4" GAS PIPING FROM FLOOR ABOVE TO REMAIN.
- 2. EXISTING 4" SANITARY PIPING DOWN TO 4" SANITARY MAIN TO REMAIN.
- 3. EXISTING 2" GAS PIPING UP THRU SLAB TO EXISTING HORIZONTAL
- 4. EXISTING SANITARY PIPING UP TO SLAB DRAIN TO REMAIN.
- 5. EXISTING 4" SANITARY PIPING TO REMAIN.
- 6. EXISTING GAS PIPING TO REMAIN.
- 7. EXISTING 6" SANITARY PIPING FROM BUILDING.
- 8. EXISTING 6" SEAL WATER DRAIN PIPING TO REMAIN.
- 9. EXISTING SEAL WATER DRAIN PIPING UP THRU SLAB TO REMAIN.
- 10. EXISTING SEAL WATER DRAIN PIPING FROM PUMPS TO REMAIN.
- 11. EXISTING POTABLE WATER PIPING TO REMAIN.
- 12. EXISTING POTABLE WATER PIPING UP THRU SLAB TO HORIZONTAL
- 13. EXISTING HORIZONTAL SHAFT PUMP HEAT EXCHANGER DRAIN PIPING



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE: 217.373.8900 FAX: 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ADMINISTRATION AND
FILTRATION FACILITY
LOWER LEVEL
PLUMBING DEMOLITION PLA

O0130014

P-10-102 SHEET 030 OF 088 SHEETS


KEY PLAN

NOTES

- SEE DRAWING P-00-101 FOR GENERAL NOTES, LEGENDS, AND ABBREVIATIONS.
- 2. ALL PIPING IN ELECTRICAL ROOM AND IN MECHANICAL ROOM ARE EXPOSED AT CEILING, UNLESS OTHERWISE INDICATED.
- GENERATOR SHALL BE MOVED TO THE EAST IN THE ELECTRICAL ROOM TO PROVIDE 36" CLEARANCE BETWEEN GENERATOR CONTROL PANEL AND OPENED DAMPER BLADES AND ACTUATOR. FINAL LOCATION SHALL BE DETERMINED IN THE FIELD.


KEYNOTES

- 1. GAS SERVICE FROM WE ENERGIES. CONTRACTOR SHALL COORDINATE LOCATION AND SERVICE WITH WE ENERGIES.
- 2. GAS METER PROVIDED BY WE ENERGIES. THE METER SHALL BE RATED FOR 30,000 CFH AT 5 PSI. THE METER SHALL BE INSTALLED ON THE WALL. CONTRACTOR SHALL PROVIDE CONCRETE PAD BELOW METER. SEE DRAWING A-10-201 FOR ADDITIONAL INFORMATION. SEE DETAIL 1/P-30-101 FOR ADDITIONAL INFORMATION.
- 3. PROVIDE 4" GAS PIPING FROM METER INTO BUILDING. PROVIDE SLEEVE THROUGH WALL AND SEAL OPENING WATER TIGHT. SEE DETAIL 1/P-30-201.
- 4. PROVIDE 3" GAS PIPING FOR NATURAL GAS GENERATOR GEN-101. SEE DETAIL 1/P-30-201.
- 5. EXISTING HOSE BIBB.



KEYNOTES (CONT.)

- 6. PROVIDE 1 1/2" GAS PIPING INTO MECHANICAL ROOM. PROVIDE GAS REGULATOR TO ADJUST PRESSURE DOWN TO 14" WC FOR BOILER. TRANSITION PIPING TO 2 1/2" GAS.
- 7. PROVIDE 3/4" GAS PIPING DOWN TO RELOCATED WATER HEATER. SEE DETAIL 3/P-30-201.
- 8. PROVIDE 2 1/2" GAS PIPING DOWN TO HEATING HOT WATER BOILER <u>B-101</u>. SEE DETAIL 3/P-30-201.
- 9. RELOCATED WATER HEATER. PROVIDE 3/4" POTABLE WATER AND HOT WATER PIPING TO WATER HEATER. INSTALL WATER HEATER ON 4" THICK CONCRETE PAD.
- 10. PROVIDE 1" GAS PIPING. PROVIDE GAS REGULATOR TO ADJUST PRESSURE DOWN TO 1 PSI. TRANSITION PIPING TO 1 1/2" GAS.
- 11. PROVIDE 3/4" POTABLE WATER PIPING TO HEATING HOT WATER BOILER <u>B-101</u>
- 12. PROVIDE 1/2" POTABLE WATER PIPING DOWN TO WALL MOUNTED HOSE BIBB $\underline{\sf HB}-1$. CONNECT TO EXISTING PIPING.
- 13. PROVIDE 1" GAS PIPING TO REFEED EXISTING 1" GAS PIPING FOR BUILDING SERVICES.
- 14. PROVIDE 4" GAS PIPING TO REFEED EXISTING 4" GAS PIPING FOR HORIZONTAL SHAFT PUMP
- 15. PROVIDE 3/4" POTABLE WATER AND HOT WATER PIPING TO/FROM RELOCATED HOT WATER HEATER, CONNECT TO EXISTING PIPING.
- 16. PROVIDE 4" POTABLE WATER PIPING TO HEAT EXCHANGERS FOR GENERATOR COOLING.
- 17. JACKET WATER HEAT EXCHANGER <u>HX-101A</u>. PROVIDE 4" POTABLE WATER AND 4" DRAIN PIPING TO HEAT EXCHANGER. SEE DETAIL 10/P-30-201.
- 18. AFTER COOLER HEAT EXCHANGER <u>HX-101B</u>. PROVIDE 2" POTABLE WATER AND 2" DRAIN PIPING TO HEAT EXCHANGER. SEE DETAIL 10/P-30-201.
- 19. PROVIDE DRAIN PIPING FROM HEAT EXCHANGERS. ROUTE PIPING DOWN TO SUMP PIT.
- 20. SUMP PIT. PROVIDE 6" SANITARY PIPING DOWN THRU SLAB.
- 21. PROVIDE 3/4" GAS PIPING DOWN TO GAS FIRED UNIT HEATER. SEE DETAIL 3/P-30-201.
- 22. EXISTING 4" GAS PIPING DOWN TO LOWER LEVEL.
- 23. EXISTING GAS PIPING TO BUILDING SERVICES.
- 24. EXISTING POTABLE WATER AND HOT WATER PIPING.
- 25. NATURAL GAS STANDBY GENERATOR GEN-101
- 26. PROVIDE 2" GAS PIPING DOWN TO GENERATOR GEN-101. SEE DETAIL 3/P-30-201.
- 7. --NOT USED--
- 28. PROVIDE 3" GAS PIPING FOR FUTURE GENERATOR. PROVIDE CAP AND ISOLATION VALVE.
- 29. COMPRESSED AIR PIPING FROM LOWER LEVEL. EXTEND AND CONNECT TO EXISTING EXISTING PIPING CONTRACTOR SHALL VERIFY SIZES OF ALL PIPING PRIOR TO INSTALLATION.
- 30. GAS UNIT HEATER GUH-1.
- 31. PROVIDE 2" GAS PIPING TO REFEED EXISTING 2" GAS PIPING FOR BUILDING SERVICES.
- 32. PROVIDE 4" POTABLE WATER PIPING CONNECTION WITH ISOLATION VALVE TO EXISTING 6" THREADED STEEL POTABLE WATER RISER FROM LOWER LEVEL.
- 33. PROVIDE 4" POTABLE WATER PIPING TO GENERATOR COOLING HEAT EXCHANGERS. PROVIDE RPZ TYPE BACKFLOW PREVENTER, APPROXIMATELY 4' ABOVE FINISHED FLOOR. ROUTE DRAIN PIPING TO FLOOR DRAIN. MAINTAIN TUBE REMOVAL CLEARANCE FOR GAS FIRED BOILER. SEE DETAIL 9/P-30-201.
- 34. PROVIDE LINE SIZE SOLENOID WATER FLOW CONTROL VALVE INTERCONNECTED WITH GENERATOR CONTROL PANEL. PROVIDE 120V CONTROL VALVE ACTUATOR. VERIFY VOTLAGE WITH GENERATOR MANUFACTURER.
- 35. --NOT USED--
- 36. PROVIDE 2" VENT PIPING UP THRU SLAB. EXTEND PIPING UP TO BELOW CEILING. CONNECT TO 3" VENT PIPING AT CEILING.
- 37. PROVIDE 2" VENT PIPING UP THRU SLAB. CONNECT TO 3" VENT PIPING AND EXTEND THRU ROOF. SEE DETAIL 4/P-30-201.
- 38. EXISTING WATER ISOLATION VALVE IN WALL FOR EXTERIOR HOSE BIBB.
- 39. GAS FIRED BOILER B-101.
- 40. SAWCUT AND REMOVE ASPHALT SURFACE FOR INSTALLATION OF SANITARY PIPING. PATCH ASPHALT SURFACE TO MATCH EXISTING.
- 41. EXISTING POTABLE WATER PIPING.
- 42. PIPE TRENCH FOR COOLANT PIPING.
- 43. PIPE TRENCH FOR COOLANT PIPING AND HEAT EXCHANGER DRAIN PIPING.
- 44. CORE EXISTING WALL FOR POTABLE WATER PIPING. SEE DETAIL 2/P-30-201.





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

DATE CHECKED: 01/11


NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

ADMINISTRATION AND FILTRATION FACILITY ENLARGED FIRST FLOOR PLUMBING PLAN

PROJECT No. 00130014

DRAWING

P-10-201



- 3. PROVIDE 4" SANITARY PIPING UP THRU SLAB TO FLOOR DRAIN FD-1.

- 7. PROVIDE 6" SANITARY PIPING THRU FOUNDATION (& ELEV. 92.0). COORDINATE FINAL ELEVATION IN FIELD. PROVIDE PIPE SLEEVE IN PENETRATION. EXTEND PIPING 3' PAST FOUNDATION WALL AND CAP
- 10. PROVIDE 6" SANITARY PIPING, CONNECT TO EXISTING 6" SANITARY
- 12. PROVIDE 4" SANITARY PIPING UP THRU SLAB TO FLOOR CLEANOUT.
- 13. RELOCATE EXISTING AIR COMPRESSOR AND DRYER FROM MECHANICAL ROOM. INSTALL AIR COMPRESSOR ON 4" CONCRETE PAD. PROVIDE NEW PIDING, FILTER, DRAIN, VALVES, SEPARATORS, AND QUICK



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY LOWER LEVEL PLUMBING PLAN

PROJECT No O0130014

P-10-202 SHEET 032 OF 088 SHEETS

DEMOLITION KEYNOTES

- EXISTING GAS FIRED UNIT HEATER TO BE RELOCATED. CONTRACTOR SHALL DISCONNECT AND REMOVE GAS PIPING TO THE UNIT HEATER. TEMPORARILY CAP PIPING AND ALLOW FOR RECONNECTION. SEE DRAWING P-20-201 FOR NEW WORK.
- EXISTING GAS FIRED UNIT HEATER TO BE REMOVED. CONTRACTOR SHALL DISCONNECT AND REMOVE ALL GAS PIPING INCLUDING SUPPORTS, HANGERS AND ACCESSORIES BACK TO MAIN AND CAP.
- RELOCATE EXISTING AIR COMPRESSOR TO NEW LOCATION.
 CONTRACTOR SHALL REMOVE AND RECONNECT COMPRESSED AIR
 PIPING, DRYER, FILTER, DRAINS, SUPPORTS, HANGERS, AND ALL
 ASSOCIATED ACCESSORIES TO NEW LOCATION. SEE DRAWING
 P-20-201 FOR NEW WORK.
- 4. REMOVE EXISTING COMPRESSED AIR PIPING INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES.
- 5. EXISTING NATURAL GAS FIRED GENERATOR TO BE REMOVED.
 DISCONNECT AND REMOVE NATURAL GAS PIPING INCLUDING ALL
 SUPPORTS, HANGERS AND ACCESSORIES BACK TO MAIN AND CAP.
- 6. EXISTING HEAT EXCHANGER TO BE REMOVED. DISCONNECT AND REMOVE NON-POTABLE WATER PIPING INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES BACK TO MAIN AND CAP.
- REMOVE EXISTING POTABLE WATER PIPING ALONG WALL INCLUDING ALL INSULATION, SUPPORTS, HANGERS AND ACCESSORIES.
- 8. REMOVE EXISTING NON-POTABLE WATER PIPING ALONG WALL INCLUDING ALL INSULATION, SUPPORTS, HANGERS AND ACCESSORIES.
- 9. REMOVE AND RELOCATE EXISTING 2" DRAIN VENT PIPING. SEE SHEET P-20-201 FOR NEW WORK.
- 10. PLUG AND REMOVE EXISTING FLOOR DRAIN, AND SEAL DRAIN PIPING PENETRATING CONCRETE SLAB WATERTIGHT. SEAL OPENING FLUSH WITH EXISTING SURFACE.
- 11. PLUG EXISTING DRAIN CONNECTION FOR DISCHARGE WATER FROM HEAT EXCHANGER. SEAL DRAIN PIPING AT CONCRETE SLAB WATERTIGHT. SEAL OPENING FLUSH WITH EXISTING SURFACE.
- 12. REMOVE EXISTING PIPING PENETRATING WALL AND SEAL OPENING TO MATCH EXISTING SURFACE.
- 13. REMOVE ALL EXISTING WATER PIPING, VALVES, ETC FEEDING EQUIPMENT IN CHEMICAL ROOM.

KEYNOTES

- 1. EXISTING DRAIN PIPING BELOW SLAB TO REMAIN.
- 2. EXISTING DRAIN PIPING BELOW SLAB INTO SUMP PIT TO REMAIN.
- 3. EXISTING FLOOR DRAIN TO REMAIN.
- 4. EXISTING DRAIN CONNECTION FOR DISCHARGE WATER FROM SEAL WATER PIPING TO REMAIN.
- 5. EXISTING SUMP PIT AND 14" DISCHARGE FROM SUMP PIT TO REMAIN.
- 6. EXISTING 4" STORM DRAIN PIPING DOWN FROM ROOF DRAIN INTO SUMP PIT TO REMAIN.
- 7. EXISTING NON-POTABLE WATER PIPING DOWN TO HOSE BIBB TO REMAIN.
- 8. EXISTING NON-POTABLE WATER PIPING FROM ABOVE TO REMAIN. PROVIDE VALVE AND CAP PIPING IN VERTICAL FOR PIPING BEING REMOVED.
- 9. EXISTING POTABLE WATER PIPING TO REMAIN.
- 10. EXISTING 4" POTABLE WATER RISER TO REMAIN.
- 11. EXISTING POTABLE WATER BACKFLOW PREVENTER ASSEMBLY TO REMAIN.
- 12. EXISTING GAS PIPING TO GAS FIRED UNIT HEATER TO REMAIN.

Clark Dietz

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION


LOW LIFT PUMP STATION FIRST FLOOR UMBING DEMOLITION PLAN


PROJECT No.

O0130014

P-20-101

SHEET 033 OF 088 SHEETS





MEZZANINE PLUMBING DEMOLITION PLAN

DEMOLITION KEYNOTES

- EXISTING GAS METER AND REGULATOR ASSEMBLY TO BE REMOVED AND REPLACED BY WE ENERGIES. CONTRACTOR SHALL COORDINATE THE REPLACEMENT REQUIREMENTS WITH WE ENERGIES.
- REMOVE EXISTING 3/4" GAS PIPING DOWN TO THE EXISTING GAS FIRED UNIT HEATER AS REQUIRED TO ALLOW FOR RELOCATION OF EXISTING UNIT HEATER.
- 3. REMOVE EXISTING 3/4" GAS PIPING DOWN TO EXISTING GAS FIRED UNIT HEATER. PROVIDE SHUTOFF VALVE AT MAIN. CAP PIPE AT MAIN.
- 4. REMOVE EXISTING 1" COMPRESSED AIR PIPING TO AIR COMPRESSOR.
- 5. REMOVE EXISTING 1" GAS PIPING DOWN TO EXISTING GAS FIRED GENERATOR. CAP PIPE AT MAIN AND PROVIDE SHUTOFF VALVE.
- 6. REMOVE EXISTING 3/4" NON-POTABLE WATER PIPING DOWN TO EXISTING HEAT EXCHANGER. CAP PIPE AT MAIN.
- 7. REMOVE AND RELOCATE EXISTING 2" DRAIN VENT PIPING. SEE DRAWING P-20-202 FOR NEW WORK.
- 8. REMOVE AND RELOCATE EXISTING 4" STORM DRAIN PIPING TO AVOID NEW EXHAUST LOUVER PLENUM. PROVIDE STRUCTURAL SUPPORTS AS REQUIRED.

KEYNOTES

- 1. EXISTING 3" GAS SERVICE UP TO GAS METER TO REMAIN AND BE REUSED.
- 2. EXISTING GAS PIPING TO REMAIN.
- 3. EXISTING GAS PIPING TO GAS FIRED UNIT HEATER TO REMAIN.
- 4. EXISTING NON-POTABLE WATER DOWN TO BELOW MEZZANINE LEVEL TO REMAIN.
- 5. EXISTING NON-POTABLE WATER DOWN TO HOSE BIBB TO REMAIN.
- 6. EXISTING NON-POTABLE WATER PIPING ALONG CEILING TO REMAIN.
- 7. EXISTING NON-POTABLE WATER PIPING CONNECTION TO RAW WATER PIPING TO REMAIN.
- 8. EXISTING NON-POTABLE WATER PIPING DOWN TO SEAL WATER VALVE ON LOW LIFT PUMP TO REMAIN.
- 9. EXISTING 4" INCOMING POTABLE WATER SERVICE INTO BUILDING TO REMAIN
- 10. EXISTING 4" POTABLE WATER RISER TO REMAIN.
- 11. EXISTING 4" STORM DRAIN PIPING FROM ROOF DRAIN TO REMAIN.
- 12. EXISTING 4" STORM DRAIN PIPING DOWN INTO SUMP PIT TO REMAIN.
- 13. EXISTING GAS VENT PIPING TO EXHAUST PIPE TO REMAIN.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: NTP
CHECKED BY: NTP
CHECKED BY: NTP
CHECKED BY: NTP

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

> LOW LIFT PUMP STATION MEZZANINE LUMBING DEMOLITION PLAN

> > O0130014

.

P-20-102
SHEET 034 OF 088 SHEETS

(ELEV. 22.0)

NOTES

(#) KEYNOTES

- 1. EXISTING 1/2" GAS PIPING TO GAS FIRED UNIT HEATER TO REMAIN.
- 2. PROVIDE 3" GAS PIPING DOWN TO NATURAL GAS GENERATOR GEN-102, FROM ABOVE. SEE DETAIL 3/P-30-201.
- 3. PROVIDE 3/4" GAS PIPING DOWN TO GAS FIRED UNIT HEATER GUH-102, FROM ABOVE. SEE DETAIL 3/P-30-201.
- 4. RELOCATED EXISTING AIR COMPRESSOR AND DRYER. INSTALL COMPRESSOR ON 4" CONCRETE PAD. PROVIDE 1" COMPRESSED AIR PIPING, AIR VALVE. PRESSURE REGULATOR, FITTINGS, DRAINS, SEPARATORS, AND ACCESSORIES.
- 5. PROVIDE 3/4" COMPRESSED AIR PIPING TO CARBON FEEDER CONNECTION. ROUTE PIPING ALONG WALL WITH EXISTING POTABLE WATER PIPING AND USE EXISTING PIPE SUPPORTS.
- 6. PROVIDE 3/4" COMPRESSED AIR PIPING THRU EXTERIOR WALL. ROUTE PIPING ALONG EXTERIOR WALL. PROVIDE SLEEVE THRU WALL. SEE DETAIL 1/P-30-201. PROVIDE STAINLESS STEEL UNISTRUT SUPPORTS.
- 7. PROVIDE COMPRESSED AIR QUICK CONNECT FITTING FOR CONNECTION TO CARBON FEEDER CF-101. MOUNT 24" ABOVE GRADE. SLOPE PIPING TO NORTH AT 1/8"/FOOT TO ALLOW FOR DRAINING.
- 8. EXISTING 1 1/2" POTABLE WATER PIPING. INSULATE ALL EXISTING PIPING PER SPECIFICATIONS.
- 9. EXISTING 4" POTABLE WATER RISER.
- 10. EXISTING POTABLE WATER BACKFLOW PREVENTER ASSEMBLY.
- 11. PROVIDE 1 1/2" POTABLE WATER PIPING TO CARBON FEEDER $\underline{\text{CF}-101}$ CONNECTION. CONNECT TO EXISTING PIPING. ROUTE PIPING THRU EXTERIOR WALL AND ROUTE ALONG EXTERIOR WALL. PROVIDE ISOLATION VALVE ON PIPING PRIOR TO WALL PENETRATION. SLOPE EXTERIOR PIPING TO NORTH AT 1/8"/FOOT TO ALLOW FOR DRAINING. SEE DETAIL 5/P-30-201. PROVIDE STAINLESS STEEL UNISTRUT SUPPORTS.
- 12. PROVIDE 1 1/2" POTABLE WATER PIPING FOR CONNECTION TO CARBON FEEDER (PROVIDE COUPLING AS REQUIRED TO CONNECT TO CARBON FFFDFR PIPING).
- 13. PROVIDE 1 1/2" POTABLE WATER PIPING TO HOT WATER HEATER. CONNECT TO EXISTING PIPING.
- 14. PROVIDE 2" POTABLE WATER PIPING DOWN FROM MEZZANINE LEVEL TO POTASSIUM PERMANGANATE SYSTEM.
- 15. PROVIDE 1 1/2" POTABLE WATER PIPING UP TO MEZZANINE LEVEL.
- 16. PROVIDE FLOOR MOUNTED EMERGENCY SHOWER/EYEWASH ASSEMBLY ESEW-1. PROVIDE 1 1/4" TEMPERED WATER PIPING FROM THERMOSTATIC MIXING VALVE ASSEMBLY TO EMERGENCY SHOWER. CONNECT PIPING TO SHOWER AS REQUIRED. PROVIDE FLOW SWITCH IN PIPING. CONNECT SWITCH TO PLC. SEE ELECTRICAL DRAWINGS FOR DETAILS
- 17. PROVIDE 6" DRAIN PIPING DOWN FROM MEZZANINE LEVEL INTO SUMP PIT. CORE HOLE THRU CONCRETE FLOOR INTO SUMP PIT. SEAL OPENING
- 18. EXISTING NON-POTABLE WATER PIPING DOWN FROM MEZZANINE LEVEL TO
- 19. EXISTING NON-POTABLE WATER PIPING FROM MEZZANINE LEVEL.
- 20. RELOCATED GAS UNIT HEATER. EXTEND 3/4" GAS PIPING DOWN FROM MEZZANINE LEVEL TO UNIT HEATER. REPLACE CONDENSATE DRAIN PIPING FROM UNIT HEATER TO EXISTING FLOOR DRAIN.
- 21. EXISTING DRAIN PIPING BELOW SLAB.
- 22. EXISTING DRAIN PIPING BELOW SLAB INTO SUMP PIT.
- 23. EXISTING FLOOR DRAIN.
- 24. EXISTING DRAIN CONNECTION FOR DISCHARGE WATER FROM SEAL WATER
- 25. EXISTING SUMP PIT AND 14" DISCHARGE FROM SUMP PIT.
- 26. EXISTING 4" STORM DRAIN PIPING DOWN FROM MEZZANINE LEVEL INTO
- 27. EXISTING 2" DRAIN VENT PIPING FROM BELOW SLAB. ROUTE PIPING OVER TO WALL ALONG FLOOR.
- 28. PROVIDE 2" VENT PIPING UP TO ABOVE. ROUTE PIPING ALONG WALL.
- 29. PROVIDE WATER HEATER WH-102. INSTALL WATER HEATER ON UNISTRUT SUPPORT RACK. PROVIDE 1 1/4" POTABLE WATER, 1 1/4" HOT WATER, AND 1 1/2" GAS PIPING TO HOT WATER HEATER. SEE DETAIL 8/P-30-201.
- 30. PROVIDE THERMOSTATIC MIXING VALVE ASSEMBLY TMV-1. INSTALL MIXING VALVE ASSEMBLY ON UNISTRUT SUPPORT RACK. PROVIDE 1 1/4" POTABLE WATER, 1 1/4" HOT WATER, AND 1 1/4" TEMPERED WATER PIPING TO MIXING VALVE. SEE DETAIL 7/P-30-201.
- 31. 2" NON-POTABLE WATER DOWN TO LOWER LEVEL.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX: 217.373.8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER AND

DESIGNED BY: NTP
DRAWN BY: NTP CHECKED BY:

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF HIS DRAWING


3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

STATION FIRST FLOOR PLUMBING PLAN PUMP H 9

> PROJECT No O0130014

SHEET 035 OF 088 SHEETS

P-20-201



FIRST FLOOR PLUMBING PLAN

(ELEV. 12.0)

4

(19)-

⟨#⟩ KEYNOTES

- GAS SERVICE AND METER PROVIDED BY WE ENERGIES. THE METER SHALL BE RATED FOR 13,000 CFH AT 5PSI. CONTRACTOR SHALL COORDINATE LOCATION AND SERVICE WITH WE ENERGIES AS REQUIRED. SEE DETAIL 2/P-30-101 FOR ADDITIONAL INFORMATION.
- 2. EXISTING 3" GAS SERVICE UP TO GAS METER TO REMAIN AND BE REUSED.
- PROVIDE 4" GAS PIPING FROM GAS METER/MANIFOLD ASSEMBLY TO EXISTING BUILDING SERVICES. PROVIDE REGULATOR RATED FOR SAME SETTINGS AS EXISTING SERVICE. CONNECT TO EXISTING PIPING.
- 4. PROVIDE 3" GAS PIPING TO NATURAL GAS GENERATOR. ROUTE GAS PIPING ALONG WALL.
- 5. PROVIDE 3" GAS PIPING DOWN TO NATURAL GAS GENERATOR GEN-102, (LOCATED IN GENERATOR ROOM).
- PROVIDE 3/4" GAS PIPING DOWN TO GAS FIRED UNIT HEATER (LOCATED IN GENERATOR ROOM). CONNECT TO EXISTING GAS PIPING.
- 7. PROVIDE 2" GAS PIPING FOR WATER HEATER.
- 8. PROVIDE 2" GAS PIPING DOWN TO WATER HEATER (LOCATED BELOW).
- PROVIDE 1 1/2" POTABLE WATER PIPING DOWN TO WATER HEATER AND THERMOSTATIC MIXING VALVE ASSEMBLY (LOCATED BELOW).
- 10. EXISTING GAS PIPING TO GAS FIRED UNIT HEATER BELOW.
- 11. EXISTING GAS PIPING.
- 12. EXTEND 3/4" GAS PIPING DOWN TO RELOCATED GAS FIRED UNIT HEATER (LOCATED BELOW).
- 13. EXISTING 4" INCOMING POTABLE WATER SERVICE INTO BUILDING.
- 14. EXISTING 4" POTABLE WATER RISER.
- 15. PROVIDE 4" POTABLE WATER PIPING TO GENERATOR HEAT EXCHANGERS AND POTASSIUM PERMANGANATE SYSTEM. CONNECT TO EXISTING PIPING USING EXISTING VALVE. PROVIDE RPZ TYPE BACKFLOW PREVENTER (MOUNT ABOVE EXISTING BACKFLOW PREVENTER). SEE DETAILS 3/P-30-101 AND 9/P-30-201.
- 16. JACKET WATER HEAT EXCHANGER <u>HX-102A</u>. PROVIDE 4" POTABLE WATER AND 4" DRAIN PIPING TO HEAT EXCHANGER. SEE DETAIL 10/P-30-201.
- 17. AFTER COOLER HEAT EXCHANGER $\underline{\text{HX}-102B}$. PROVIDE 2" POTABLE WATER AND 2" DRAIN PIPING TO HEAT EXCHANGER. SEE DETAIL 10/P-30-201.
- 18. PROVIDE 1 1/2" POTABLE WATER PIPING UP FROM BELOW.
- 19. ROUTE PIPING ALONG WALL. AVOID CONFLICT WITH EXISTING PROCESS PIPING.
- 20. EXISTING NON-POTABLE WATER PIPING DOWN TO BELOW MEZZANINE LEVEL.
- 21. EXISTING NON-POTABLE WATER PIPING DOWN TO HOSE BIBB.
- 22. EXISTING 4" NON-POTABLE WATER PIPING CONNECTION TO RAW WATER PIPING.
- 23. EXISTING NON-POTABLE WATER PIPING ALONG CEILING.
- 24. EXISTING NON-POTABLE WATER PIPING DOWN TO SEAL WATER VALVE ON LOW LIFT PUMP.
- 25. PROVIDE 2" NON-POTABLE WATER PIPING DOWN TO POTASSIUM PERMANGANATE SYSTEM (LOCATED BELOW).
- 26. PROVIDE 6" DRAIN PIPING FROM HEAT EXCHANGERS. ROUTE PIPING ALONG GENERATOR ROOM CEILING DOWN TO BELOW. CONNECT CONDENSATE DRAIN PIPING FROM SILENCER. SEE DRAWING HV-20-202 FOR LOCATION.
- 27. RELOCATE EXISTING 4" STORM DRAIN PIPING ALONG CEILING TO AVOID NEW EXHAUST LOUVER PLENUM.
- 28. RECONNECT EXISTING 4" STORM DRAIN PIPING DOWN FROM ROOF DRAIN AND DOWN INTO SUMP PIT (LOCATED BELOW) TO RELOCATED 4" STORM DRAIN.
- 29. PROVIDE 2" VENT PIPING FROM BELOW. ROUTE PIPING ALONG GENERATOR ROOM CEILING TO EXISTING SANITARY VENT THRU ROOF.
- 30. PROVIDE 2" SANITARY VENT PIPING UP TO EXISTING VENT THRU ROOF. TRANSITION TO EXISTING 4" VENT.
- 31. PROVIDE 2" POTABLE WATER PIPING DOWN TO POTASSIUM PERMANGANATE SYSTEM. PROVIDE ISOLATION VALVE.
- 32. RECONNECT EXISTING 4" PIPING DOWN FROM ROOF DRAIN TO RELOCATED 4" STORM DRAIN.
- 33. PROVIDE 2" NON-POTABLE WATER PIPING CONNECTED TO EXISTING NON-POTABLE WATER PIPING. PROVIDE SUPPORT BRACKET TO MOUNT OFF SIDE OF OVERHEAD MONORAIL.
- 34. CORE WALL FOR GAS PIPING. SEE DETAIL 1/P-30-201.
- 35. PROVIDE LINE SIZE SOLENOID WATER FLOW CONTROL VALVE INTERCONNECTED WITH GENERATOR CONTROL PANEL. PROVIDE 120V CONTROL VALVE ACTUATOR. VERIFY VOLTAGE WITH GENERATOR MANUFACTURER.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

LOW LIFT PUMP STATION MEZZANINE PLUMBING PLAN

PROJECT No. 00130014

.

SHEET 036 OF 088 SHEETS

P-20-202

MEZZANINE PLUMBING PLAN

(ELEV. 22.0)

15

(13)-

 $\langle 14 \rangle$

	WATER HEATER S	SCHE	DULE	<u> </u>	INST	TANT/	ANEC	US GAS	FIRED								
	SERVICE		WATE	:R			NATUR/	AL GAS	THERMAL	ELEC	TRIC DA	TΑ	INITAIZE	EXHAUST		DESIGN	BASIS
TAG		FLOW	EWT	LWT	W.P.D.	MIN.	MAX.	GAS PRESSURE	EFFICIENCY						REMARKS		
	LOCATION	(GPM)	(°F)	(*F)	(PSI)	(MBH)	(MBH)	(IN WC)	(%)	V	PH	HZ	AIR	AIR		MANUFACTURER	MODEL NUMBER
WH-102	EMERGENCY SHOWER	8.0	45.0	120.0	7.5	15.0	380.0	5-14	90.0	120	1	60	E"4	- " a	NOTE 1 2 7	TAKACI	T MEONOME
WH-102	LLPS-PUMP ROOM	7 0.0	45.0	120.0	/.5	15.0	300.0	3-14	80.0	120	'	60	5"ø	5 %	NOTE 1, 2, 3	TAKAGI	T-M50ASME


- . PROVIDE MANUFACTURER'S WALL MOUNTED SUPPORT KIT.
- 2. PROVIDE MANUFACTURER'S CONDENSATE NEUTRALIZER KIT IF REQUIRED.
- 3. PROVIDE MANUFACTURER'S INTAKE AND EXHAUST AIR TERMINATION KITS.


	THERMOSTATIC	MIXING	VALVE	E S	CHE	DULE					
	SERVICE			V	ALVE DAT					DESIGN	BASIS
TAG	LOCATION	TYPE	FLOW CAP	ACITY MAX.	INLET	OUTLET F	CONDITION ENT. HW	$\overline{}$	REMARKS	MANUFACTURER	MODEL NUMBER
TMV-1	WH-102 LLPS-PUMP ROOM	THERMOSTATIC		24.0	1-1/4"	1-1/4"	120.0		NOTE 1	LAWLER	SERIES 911E

NOTES:

1. PROVIDE WITH LOCKING TEMPERATURE REGULATOR AND WALL SUPPORT BRACKET.

EQUIP	MENT (CONNEC	TION S	CHEDUL	.E
TAG	HW	PW	TW	G	D
HX-101A		4"			4"
HX-101B		2"			2"
HX-102A		4"			4"
HX-102B		2"			2"
TMV-1	1-1/4"	1-1/4"	1-1/4"		
ESEW-1			1-1/4"		
WH-101	3/4"	3/4"			
WH-102	1"	1"			
B-101		3/4"		2"	






ADMINISTRATION AND FILTRATION FACILITY GAS PIPING DETAIL

2 LOW LIFT PUMP STATION GAS PIPING DETAIL
NO SCALE

∅ KEYNOTES

- 1. GAS SERVICE FROM WE ENERGIES.
- 2. 3" GAS PIPING FOR FUTURE GENERATOR.
- 3. 3/4" GAS PIPING FOR GAS FIRED UNIT HEATER GUH-1.
- 4. 3" GAS PIPING FOR GAS GENERATOR GEN-101.
- 5. 4" GAS PIPING TO REFEED EXISTING 4" GAS PIPING.
- 6. 1" GAS PIPING TO REFEED EXISTING 1" GAS PIPING.
- 7. 3/4" GAS PIPING FOR RELOCATED WATER HEATER.
- 8. 2 1/2" GAS PIPING FOR HEATING HOT WATER BOILER <u>B-101</u>.
- 9. GAS REGULATOR TO ADJUST PRESSURE DOWN TO 14" WC. CFH PROVIDED IS BASED ON AVAILABLE INFORMATION. CONTRACTOR SHALL VERIFY IN FIELD PRIOR TO SIZING REGULATORS.
- 10. GAS REGULATOR TO ADJUST PRESSURE DOWN TO 1 PSI. CFH PROVIDED IS BASED ON AVAILABLE INFORMATION. CONTRACTOR SHALL VERIFY IN FIELD PRIOR TO SIZING REGULATORS.
- 11. 3" GAS PIPING TO GAS GENERATOR GEN-102.
- 12. 4" GAS PIPING TO REFEED EXISTING 4" GAS PIPING.
- 13. 2" GAS PIPING FOR WATER HEATER WH-102.
- 14. GAS REGULATOR TO ADJUST PRESSURE TO EXISTING SERVICE SETTING.
 CFH PROVIDED IS BASED ON AVAILABLE INFORMATION. CONTRACTOR
 SHALL VERIFY IN FIELD PRIOR TO SIZING REGULATORS.
- 15. EXISTING 4" INCOMING POTABLE WATER SERVICE INTO BUILDING.
- 16. PROVIDE 4" POTABLE WATER PIPING. CONNECT TO EXISTING PIPING USING EXISTING VALVE.
- 17. PROVIDE RPZ TYPE BACKFLOW PREVENTER. MOUNT AT HEIGHT ABOVE EXISTING BACKFLOW PREVENTER TO ALLOW MAINTENANCE FROM FXISTING PLATFORM
- 18. PROVIDE 2" POTABLE WATER PIPING TO POTASSIUM PERMANGANATE SYSTEM. PROVIDE ISOLATION VALVE.
- 19. PROVIDE 4" POTABLE WATER PIPING TO GENERATOR HEAT EXCHANGERS.
- PROVIDE 1 1/2" POTABLE WATER PIPING TO HOT WATER HEATER. CONNECT TO EXISTING PIPING.
- 21. EXISTING POTABLE WATER BACKFLOW PREVENTER ASSEMBLY.
- 22. EXISTING 1 1/2" POTABLE WATER PIPING.



LLPS POTABLE WATER SERVICE DETAIL

NO SCALE

Clank D'etz

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: NTP
CHECKED BY: NTP
DATE CHECKED: 01/1

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

PLUMBING QUIPMENT SCHEDULES AND DETAILS


PROJECT No.

O0130014

DRAWING No.

P-30-101

SHEET 037 OF 088 SHEETS



HEATING/\	VENTILATION LEGEND		
SYMBOL	DESCRIPTION	<u>SYMBOL</u>	DESCRIPTION
	SUPPLY DUCT UP OR TOWARD	HWS	HOT WATER HEATING SUPPLY HOT WATER HEATING RETURN
×	SUPPLY DUCT DOWN OR AWAY	——————————————————————————————————————	JACKET WATER COOLANT SUPPLY JACKET WATER COOLANT RETURN AFTER COOLER COOLANT SUPPLY
7	RETURN DUCT UP OR TOWARD		AFTER COOLER COOLANT RETURN RELIEF VENT
	RETURN DUCT DOWN OR AWAY	——(3MAN)———	EXISTING PIPING ELBOW DOWN OR AWAY
	EXHAUST DUCT UP OR TOWARD		ELBOW UP OR TOWARD TEE DOWN OR AWAY TEE UP OR TOWARD
	EXHAUST DUCT DOWN OR AWAY	——+c+	RISE OR DROP 90° ELBOW
24/24	RECTANGULAR DUCT (FIRST FIGURE IS SIDE SHOWN) ALL DUCT DIMENSIONS ARE INSIDE CLEAR DIMENSIONS		PIPE TEE PIPE TAKEOFF (FROM BOTTOM OF MAIN) PIPE TAKEOFF (FROM TOP OF MAIN)
z Xø z	ROUND DUCTWORK		45° ELBOW
The state of the s	90' ELBOW WITH TURNING VANES		45° BRANCH PITCH PIPING IN DIRECTION OF ARROW
Ž AD	ACCESS DOOR (HORIZONTAL/VERTICAL)	——- ∂⊦——	BALANCING VALVE BALL VALVE BUTTERFLY VALVE
<u>M</u>	MOTORIZED DAMPER	—————————————————————————————————————	CHECK VALVE GATE VALVE GLOBE VALVE — TWO WAY
	FLEXIBLE DUCT CONNECTION		GLOBE VALVE - THREE WAY CONTROL VALVE - TWO WAY
	TRANSITION FROM RECTANGULAR TO ROUND DUCT		CONTROL VALVE — THREE WAY 3-WAY VALVE REDUCER
XX-X	THERMOSTAT W/EQUIPMENT NUMBER	——————————————————————————————————————	CONCENTRIC REDUCER ECCENTRIC REDUCER
XX-X H	HUMIDISTAT W/EQUIPMENT NUMBER	——————————————————————————————————————	EMPTY WELL END CAP
<u>EF-X</u> ([Z])	EXHAUST FAN W/ EQUIPMENT NUMBER		PRESSURE / TEST POINT GAUGE – PRESSURE
	DIRECTION OF AIRFLOW		THERMOMETER UNION — SCREWED TO BE REMOVED CONNECTION TO EXISTING GAUGE — TEMPERATURE
		*	THERMOSTATIC WELL

GENERAL HEATING/VENTILATION DEMOLITION NOTES GENERAL HEATING/VENTILATION NOTES

- VERIFY EXACT SIZE AND LOCATION OF EXISTING UTILITIES PRIOR TO START OF DEMOLITION. SEE GENERAL CONDITIONS OF THE CONTRACT FOR ADDITIONAL
- DISCONNECT ALL HEATING PIPING AND DUCTWORK CONNECTIONS TO EQUIPMENT BEING REMOVED.
- UNLESS OTHERWISE NOTED, REMOVAL OF DUCTWORK, PIPING AND/OR EQUIPMENT SHALL INCLUDE ALL INSULATION, DAMPERS, VALVES, HANGERS, SUPPORTS, EQUIPMENT PADS, FLASHING, ROOF CURB, CONTROLS, AND ASSOCIATED
- UNLESS OTHERWISE NOTED, REMOVAL OF PIPING SHALL BE BACK TO THE MAIN OR LAST ACTIVE SERVICE.
- ALL OPENINGS OR HOLES LEFT IN EXISTING WALLS, FLOORS, AND CEILINGS TO REMAIN, INCLUDING CHASES, SHALL BE PATCHED TO MATCH EXISTING CONDITIONS BY THE CONTRACTOR WHOSE WORK HAS CREATED THE OPENING OR HOLE. PATCHING SHALL BE IN ACCORDANCE WITH THE APPROPRIATE DIVISION OF THE SPECIFICATIONS.
- CONTRACTOR SHALL VERIFY SEQUENCE OF OPERATION OF EXISTING BOILER AND PUMPS PRIOR TO DEMOLITION. BOILER AND PUMPS PROVIDED BY THIS CONTRACT SHALL OPERATE ON THE SAME SEQUENCE OF OPERATION.

HEATING/VENTILATION ABBREVIATIONS

SUPPLY AIR EΑ EXHAUST AIR OΑ OUTDOOR AIR CFM CUBIC FEET PER MINUTE INTAKE LOUVER EXHAUST LOUVER GUH ELECTRIC BASE HEATER BOIL FR ΕX EXPANSION TANK

- DUCTWORK AND PIPING IS SHOWN IN SCHEMATIC FORM ONLY, OFFSETS AND CHANGES IN ELEVATIONS ARE NOT NECESSARILY SHOWN. ROUTE DUCTWORK AND PIPING AN ORDERLY MANNER AS REQUIRED FOR CLEARANCE WITH STRUCTURAL CONDITIONS. COORDINATE LOCATION OF DUCTWORK AND PIPING WITH OTHER TRADES PRIOR TO INSTALLATION. WHERE POSSIBLE RACK PIPING HORIZONTALLY AND VERTICALLY.
- COORDINATE LOCATIONS AND SIZES OF DUCT CONNECTIONS AND PIPING CONNECTIONS TO EQUIPMENT BEING PROVIDED.
- PROVIDE AND INSTALL MANUAL BALANCING DAMPERS IN ALL BRANCH DUCTWORK AND AT EACH AIR INLET AND OUTLET.
- LOCATE ALL MANUAL BALANCING DAMPERS IN AN ACCESSIBLE LOCATION. WHERE DAMPERS ARE NOT ACCESSIBLE PROVIDE MINIMUM 18x18 ACCESS
- UNLESS OTHERWISE NOTED, CONCEAL ALL DUCTWORK AND PIPING ABOVE CEILINGS, IN WALLS, OR INSIDE CHASES.
- CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ADEQUATE SUPPORTING SYSTEMS AND DEVICES FOR ALL DUCTWORK, EQUIPMENT, PIPING AND ACCESSORIES.
- PROVIDE AND INSTALL SLEEVES FOR ALL DUCTWORK AND PIPING PASSING THROUGH WALLS AND FLOORS.
- PROVIDE FIRE AND/OR SMOKE DAMPERS AT ALL PENETRATIONS OF FIRE AND/OR SMOKE RATED WALLS, CEILINGS, AND FLOORS. SEE ARCHITECTURAL PLANS FOR LOCATIONS OF FIRE AND/OR SMOKE RATED WALLS, CEILINGS, AND FLOORS. PROVIDE ACCESS DOOR(S) TO FACILITATE RESETTING OF DAMPERS.
- PROVIDE RIGID METAL DUCT, WITH NO EXCEPTION, WHERE FIRE AND/OR SMOKE RATED WALLS, CEILINGS, AND FLOORS ARE PENETRATED.
- FOR DUCT CONNECTIONS TO TERMINAL DEVICES, FANS, AND OTHER EQUIPMENT SEE MECHANICAL DETAILS.
- COORDINATE LOCATIONS OF ALL DIFFUSERS, GRILLES, AND REGISTERS WITH ARCHITECTURAL REFLECTED CEILING PLANS.
- LOCATE AND INSTALL ALL MECHANICAL EQUIPMENT TO PROVIDE MANUFACTURER'S MINIMUM SERVICE CLEARANCES
- 13. PROVIDE AND INSTALL ISOLATION VALVES IN ALL BRANCH PIPING.
- CONNECTIONS TO EQUIPMENT SHALL BE PROVIDED WITH ISOLATION VALVES AND UNIONS TO FACILITATE EQUIPMENT REMOVAL.
- 15. LOCATE ALL ISOLATION VALVES IN AN ACCESSIBLE LOCATION. WHERE VALVES ARE NOT ACCESSIBLE PROVIDE 12X12 ACCESS DOOR.
- SEE MECHANICAL DETAILS FOR EXACT PIPING CONNECTIONS TO TERMINAL UNITS, PUMPS, AND OTHER EQUIPMENT, INCLUDING VALVES, TRAPS, AND SYSTEM ACCESSORIES.
- 17. ALL EXISTING INSULATION ON WATER LINES SHALL BE REPLACED WITH NEW IN THE BUILDING AND GROUNDS ROOM AT THE WATER TREATMENT PLANT AND PIPING THAT IS BEING MODIFIED AT LOW LIFT PUMP STATION INSULATION SHALL BE PAINTED AND LABELED TO MATCH EXISTING



DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

MENT PLANT DUMP STATION POWER ATER TREATME LOW LIFT PUN STANDBY PC AND

DESIGNED BY: NTP DRAWN BY: NTP CHECKED BY:

DATE CHECKED: 01/11 NOTE: DIMENSIONAL DATA SCALING ANY PORTION OF HIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS REVISION

HEATING/VENTILATION ENERAL NOTES, LEGEND, AND ABBREVIATIONS


വ

PROJECT No.

O0130014

HV-00-101

SHEET 039 OF 088 SHEETS




DEMOLITION KEYNOTES

- 1. EXISTING NATURAL GAS FIRED GENERATOR TO BE REMOVED. THIS CONTRACTOR SHALL DISCONNECT ALL EXHAUST PIPING, AND ALL COOLANT PIPING TO EXISTING HEAT EXCHANGERS
- 2. REMOVE EXISTING GENERATOR SILENCER, INCLUDING ALL INSULATION, HANGERS, SUPPORTS AND ACCESSORIES.
- REMOVE EXISTING (2) 4"Ø EXHAUST PIPE INCLUDING ALL INSULATION, HANGERS, SUPPORTS AND ACCESSORIES. PATCH OPENINGS IN ROOF WATER TIGHT.
- 4. REMOVE EXISTING 20"x7" EXHAUST DUCTWORK INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES.
- 5. REMOVE EXISTING EXHAUST FAN, LOCATED ON ROOF ABOVE, INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES. EXISTING OPENING TO BE MODIFIED FOR NEW FAN. SEE DRAWING HV-10-201 FOR NEW WORK.
- 6. REMOVE EXISTING HOT WATER UNIT HEATER INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES.
- 7. REMOVE EXISTING 3/4" HEATING HOT WATER SUPPLY AND RETURN PIPING TO/FROM HOT WATER UNIT HEATER BACK TO MAIN AND CAP. REMOVE ALL ASSOCIATED SUPPORTS, HANGERS, INSULATION AND ACCESSORIES.
- 8. REMOVE EXISTING 2" HEATING HOT WATER RETURN PIPING AS REQUIRED TO ALLOW FOR CONNECTION TO NEW PIPING. REMOVE ALL ASSOCIATED INSULATION, SUPPORTS, HANGERS AND ACCESSORIES. TEMPORARILY CAP PIPING. SEE DRAWING HV-10-201 FOR NEW WORK.
- 9. REMOVE EXISTING HEATING HOT WATER BOILER. DISCONNECT AND REMOVE ALL ASSOCIATED PIPING AS REQUIRED. REMOVE ALL INSULATION, SUPPORTS, HANGERS, HOUSEKEEPING PAD AND ACCESSORIES.
- 10. REMOVE EXISTING AIR SEPARATOR INCLUDING ALL INSULATION, SUPPORTS, HANGERS, ACCESSORIES.
- REMOVE EXISTING HEATING HOT WATER PUMPS INCLUDING ALL SUPPORTS, HANGERS, CONTROLS AND ACCESSORIES.
- 12. REMOVE EXISTING CHEMICAL FEED SYSTEM INCLUDING ALL PIPING, SUPPORTS, HANGERS AND ACCESSORIES.
- 13. REMOVE EXISTING HEATING WATER EXPANSION TANK INCLUDING ALL PIPING, INSULATION, SUPPORTS, HANGERS, AND ACCESSORIES.
- 14. REMOVE EXISTING 10"0 FLUE INCLUDING ALL INSULATION, HANGERS, SUPPORTS, AND ACCESSORIES. PATCH OPENING IN ROOF WATER TIGHT.
- 15. REMOVE EXISTING 3"0 FLUE FROM HOT WATER HEATER INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES. PATCH OPENING IN ROOF WATER TIGHT.
- 16. REMOVE EXISTING 2" HEATING HOT WATER SUPPLY PIPING AS REQUIRED TO ALLOW FOR CONNECTION TO NEW PIPING. REMOVE ALL ASSOCIATED INSULATION, SUPPORTS, HANGERS AND ACCESSORIES. TEMPORARILY CAP PIPING. SEE DRAWING HV-10-201 FOR NEW WORK.
- 17. REMOVE EXISTING INTAKE DUCTWORK, ROOF MOUNTED INTAKE HOOD, GRILLE, DAMPER, DAMPER ACTUATOR, AND ASSOCIATED CONTROLS.
- 18. EXISTING EAST TEMPERATURE CONTROL PANEL SHALL BE REPLACED WITH NEW PANEL. SEE DRAWING HV-10-201 FOR NEW WORK. EXISTING WEST TEMPERATURE CONTROL PANEL SHALL REMAIN.
- REMOVE EXISTING (2) 3/4" CONDENSATE DRAIN PIPING INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES.

KEYNOTES

- 1. EXISTING EXHAUST PIPING FROM GAS FIRED HORIZONTAL SHAFT PUMP TO REMAIN.
- 2. EXISTING EXHAUST SILENCER FOR GAS FIRED HORIZONTAL SHAFT PUMP TO REMAIN.
- 3. EXISTING HEATING HOT WATER SUPPLY PIPING TO REMAIN.
- 4. EXISTING HEATING HOT WATER RETURN PIPING TO REMAIN.
- 5. EXISTING HEATING HOT WATER SUPPLY AND RETURN PIPING DOWN TO LOWER LEVEL TO REMAIN.
- 6. EXISTING INTAKE AIR LOUVERS WITH MOTORIZED DAMPERS TO REMAIN.
- 7. EXISTING EXHAUST FAN (LOCATED ABOVE MEZZANINE) TO REMAIN.
- 8. EXISTING EXHAUST DUCTWORK (LOCATED ABOVE MEZZANINE) TO REMAIN.
- 9. EXISTING EXHAUST LOUVER (LOCATED ABOVE MEZZANINE) TO REMAIN.
- 10. EXISTING EXHAUST DUCTWORK FROM LOWER LEVEL TO REMAIN.
- 11. EXISTING GAS FIRED HORIZONTAL SHAFT PUMP.





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS

DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY FIRST FLOOR HEATING/VENTILATION DEMOLITION PLAN

PROJECT No. 00130014

DRAWING N

HV-10-101

- 1. SEE DRAWING HV-00-101 FOR GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. ALL EQUIPMENT ASSOCIATED WITH GENERATOR (e.g. HEAT EXCHANGERS, EXPANSION TANKS, SILENCER, COOLANT PIPING, EXHAUST PIPING, ETC.) SHALL BE INSTALLED PER MANUFACTURER INSTALLATION INSTRUCTIONS.
- 3. SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF THE WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.
- F. GENERATOR SHALL BE MOVED TO THE EAST IN THE ELECTRICAL ROOM TO PROVIDE 36" CLEARANCE BETWEEN GENERATOR CONTROL PANEL AND OPENED DAMPER BLADES AND ACTUATOR. FINAL LOCATION SHALL BE DETERMINED IN THE FIELD.

KEYNOTES

- 1. PROVIDE GAS FIRED HEATING HOT WATER BOILER <u>B-101</u>. CONNECT 3" HEATING HOT WATER SUPPLY AND RETURN PIPING. INTERCONNECT BOILER CONTROL PANEL TO RELOCATED TEMPERATURE CONTROL PANEL. INSTALL BOILER ON 4" THICK CONCRETE PAD. SEE DETAIL 3/HV-30-201.
- PROVIDE HEATING HOT WATER EXPANSION TANK <u>EX-101</u>. SUPPORT FROM STRUCTURE/WALL AS REQUIRED PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAIL 3/HV-30-202.
- 3. PROVIDE 3" AIR SEPARATOR AS-101. SUPPORT FROM STRUCTURE AS REQUIRED PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAIL 3/HV-30-202.
- PROVIDE COMBUSTION AIR AND FLUE UP FROM BOILER. PROVIDE MANUFACTURER'S RAIN CAP/TERMINATION KIT. ROUTE DUCTWORK UP THROUGH ROOF. SEAL OPENING WATER TIGHT. SEE DETAIL 8/HV-30-201.
- 5. PROVIDE INLINE HEATING HOT WATER PUMP <u>HWP</u>#. CONNECT TO HEATING HOT WATER SUPPLY PIPING. SUPPORT FROM FLOOR AS REQUIRED PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAIL 1/HV-30-202 AND 2/HV-30-202.
- 6. PROVIDE CHEMICAL FEED SYSTEM. PROVIDE NECESSARY CLEARANCE FOR MAINTENANCE ACCESS. SEE DETAIL 7/HV-30-202.

GUH-10

GUH-101

 $\langle 32 \rangle$

 \Diamond

 $\langle 3 \rangle$

√39)

(2) 2" HEATING HOT WATER RETURN PIPING TO BOILER. CONNECT TO EXISTING HEATING HOT WATER RETURN PIPING.

L-101


L-102

L-103

 $\langle 5 \rangle$ HWP-101

-{21}(TYP.)

- 8. (2) 2" HEATING HOT WATER SUPPLY PIPING FROM BOILER. CONNECT TO EXISTING HEATING HOT WATER SUPPLY PIPING AS REQUIRED.
- 9. EXISTING 14"x12" EXHAUST DUCTWORK FROM LOWER LEVEL.
- 10. PROVIDE 22"x22" INTAKE DUCTWORK 12" BELOW BOTTOM OF DECK. PROVIDE MOTORIZED DAMPER MD-104 IN DUCT SECTION. PROVIDE 1/2" x 1/2" MESH SCREEN OVER OPENING. SEE ELECTRICAL DRAWINGS FOR CONTROL OPERATION.
- 11. PROVIDE ROOF MOUNTED INTAKE VENTILATOR IV—101. TRANSITION INTAKE DUCT WORK TO HOOD AND CONNECT. SEE DETAIL 8/HV—30—202.
- 12. NATURAL GAS GENERATOR GEN-101.
- 13. JACKET WATER HEAT EXCHANGER <u>HX-101A</u>. SEE DRAWING P-10-201 FOR WATER SUPPLY AND DRAIN PIPING. SEE DETAIL 5/HV-30-202.
- 14. AFTER COOLER HEAT EXCHANGER <u>HX-101B</u>. SEE DRAWING P-10-201 FOR WATER SUPPLY AND DRAIN PIPING. SEE DETAIL 5/HV-30-202.
- 15. PROVIDE 6" JACKET WATER COOLANT SUPPLY PIPING FROM HEAT EXCHANGER TO GENERATOR. ROUTE PIPING IN UTILITY TRENCH.
- 16. PROVIDE 6" JACKET WATER COOLANT RETURN PIPING FROM GENERATOR TO HEAT EXCHANGER. ROUTE PIPING IN UTILITY TRENCH.
- 17. PROVIDE 3" AFTER COOLER COOLANT SUPPLY PIPING FROM HEAT EXCHANGER TO GENERATOR. ROUTE PIPING IN UTILITY TRENCH.
- PROVIDE 3" AFTER COOLER COOLANT RETURN PIPING FROM GENERATOR TO HEAT EXCHANGER. ROUTE PIPING IN UTILITY TRENCH.
- 19. PROVIDE 32"x32" EXHAUST DUCTWORK UP THROUGH ROOF. TERMINATE DUCTWORK 12" BELOW BOTTOM OF ROOF DECK. PROVIDE 1/2"X1/2" MESH SCREEN OVER OPENING.
- 20. PROVIDE ROOF MOUNTED EXHAUST FAN EF-#. PROVIDE GRAVITY DAMPER BELOW ROOF DECK. SEE DETAIL 6/HV-30-201. SEE ELECTRICAL DRAWINGS FOR CONTROLS AND OPERATION.
- 21. PROVIDE INTAKE AIR LOUVER <u>IL-#</u>. PROVIDE REMOVABLE LOUVERS. COORDINATE LOCATION AND ELEVATION WITH ARCHITECTURAL DRAWINGS. PROVIDE SECTIONAL MOTORIZED DAMPERS IN WALL OPENING. SEE ELECTRICAL DRAWINGS FOR CONTROLS AND OPERATION.
- 22. PROVIDE 3" FLUE UP FROM RELOCATED WATER HEATER. COORDINATE LOCATION WITH PLUMBING DRAWINGS. ROUTE FLUE UP THROUGH ROOF. SEAL OPENING WATER TIGHT. PROVIDE TALL CONE FLASHING, STORM COLLAR AND RAINCAP.
- 23. PROVIDE 12" GENERATOR EXHAUST PIPING UP FROM NATURAL GAS GENERATOR. ROUTE PIPE UP THROUGH ROOF. SEAL OPENING WATER TIGHT. SEE DETAIL 6/HV-30-202.
- 24. GENERATOR SILENCER ON ROOF ABOVE. TRANSITION EXHAUST PIPE TO/FROM SILENCER AS REQUIRED. MOUNT SILENCER ON 6" SUPPORT STAND ABOVE ROOF. ROUTE CONDENSATE DRAIN PIPING TO NEAREST ROOF DRAIN.
- 25. PROVIDE 12" EXHAUST PIPING FROM SILENCER. CONNECT TO SILENCER. PROVIDE 90" ELBOW AND TERMINATE WITH RAIN CAP.
- 26. PROVIDE GAS FIRED UNIT HEATER <u>GUH-101</u>. PROVIDE MANUFACTURER'S WALL/CEILING MOUNTED SUPPORT KIT. CONNECT COMBUSTION AIR INTAKE AND FLUE TO UNIT HEATER. PROVIDE MANUFACTURER'S CONCENTRIC VENT KIT. ROUTE DUCTWORK UP THROUGH ROOF. SEAL OPENING WATER TIGHT. SEE DETAIL 10/HV-30-201.
- 27. EXISTING HEATING HOT WATER SUPPLY AND RETURN PIPING DOWN TO LOWER LEVEL.
- 28. EXISTING HEATING HOT WATER SUPPLY PIPING.
- 29. EXISTING HEATING HOT WATER RETURN PIPING.
- 30. EXISTING TEMPERATURE CONTROL PANEL.
- 31. INSTALL THERMOSTAT ON INSULATED BASE
- 32. EXPANSION TANK FOR JACKET WATER LOOP.33. EXPANSION TANK FOR AFTER COOLER LOOP.
- 34. PIPE TRENCH FOR COOLANT PIPING.
- 35. PIPE TRENCH FOR COOLANT PIPING AND HEAT EXCHANGER DRAIN PIPING.
- 36. PROVIDE 2" PIPING FOR CRANKCASE FUME DISPOSAL AND DRIP COLLECTOR UP THROUGH ROOF.
- 37. PROVIDE AUTOMATIC BREATHER VALVE FOR AIR BLEED.
- 38. PROVIDE 12"x12" EXHAUST DUCTWORK UP THROUGH ROOF. TERMINATE DUCTWORK 12" BELOW BOTTOM OF ROOF DECK. PROVIDE 1/2" x 1/2" MESH SCREEN OVER OPENING.
- 39. PROVIDE TEMPERATURE CONTROL PANEL. RELOCATE EXISTING PNEUMATIC TUBING TO THIS PANEL. RELOCATE EXISTING SIEMENS CONTROL MODULE. SEE ELECTRICAL DRAWINGS FOR DETAILS





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT ND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
NTP
CHECKED BY: KBP

DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


ADMINISTRATION AND FILTRATION FACILITY ENLARGED FIRST FLOOR HEATING/VENTILATION PLAI

PROJECT No. 00130014

DRAWING N

HV-10-201

SHEET 041 OF 088 SHEETS



ELECTRICAL ROOM

-(17)

(22)-

HWP-102 5 HWP-103

(20)(38)

20×19>

⟨34⟩-

——2"(HWR)-

—2"(HWR)-

FF-10

2"(HWS)-

CORRIDOR

FIRST FLOOR HEATING/VENTILATION DEMOLITION PLAN

NOTES

1. SEE DRAWING HV-00-101 FOR GENERAL NOTES, LEGEND AND ABBREVIATIONS.

DEMOLITION KEYNOTES

- 1. EXISTING NATURAL GAS FIRED GENERATOR TO BE REMOVED. THIS CONTRACTOR SHALL DISCONNECT AND REMOVE ALL 3" EXHAUST PIPES AND ALL COOLANT PIPING TO EXISTING HEAT EXCHANGER INCLUDING SUPPORTS, HANGERS AND ACCESSORIES.
- 2. REMOVE EXISTING GAS FIRED UNIT HEATER COMPLETE, INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES.
- REMOVE EXISTING 4" COMBUSTION AIR AND 4" FLUE VENT DUCTWORK COMPLETE INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES. PATCH EXISTING OPENING IN EXTERIOR WALL TO MATCH EXISTING.
- 4. REMOVE EXISTING 17"x24" EXHAUST DUCTWORK UP TO ABOVE CEILING COMPLETE, INCLUDING ALL SUPPORTS, HANGERS AND ACCESSORIES. PATCH EXISTING OPENING IN SLAB TO MATCH EXISTING. SEE ARCHITECTURAL DRAWINGS FOR DETAILS.
- 5. RELOCATE EXISTING GAS FIRED UNIT HEATER. MODIFY EXISTING SUPPORTS TO FACILITATE RELOCATION OF UNIT HEATER. SEE DRAWING HV-20-201 FOR NEW WORK.
- 6. MODIFY 3" COMBUSTION AIR AND 3" FLUE VENT PIPE FROM EXISTING GAS FIRED UNIT HEATER AS REQUIRED TO ALLOW FOR RELOCATION OF EXISTING UNIT HEATER, INCLUDING SUPPORTS, HANGERS AND ACCESSORIES.
- 7. REMOVE EXISTING 24"x36" WALL MOUNTED GRILLE AND ASSOCIATED MOTORIZED DAMPER ASSEMBLY COMPLETE INCLUDING SLEEVE, SUPPORTS AND ACCESSORIES. PATCH EXISTING WALL OPENING TO
- 8. REMOVE EXISTING THERMOSTAT FOR EAST UNIT HEATER AND EXISTING VANE AXIAL FAN. EXISTING CONTROL WIRING TO BE REMOVED AND REPLACED. SEE DRAWING HV-20-201 FOR NEW WORK.
- 9. REMOVE EXISTING THERMOSTAT AND EXISTING ASSOCIATED CONTROLS FOR UNIT HEATER.

KEYNOTES

- 1. EXISTING 6" EXHAUST PIPE FROM GAS FIRED HORIZONTAL SHAFT PUMP UP TO HIGH LEVEL TO REMAIN.
- 2. EXISTING 10"x12" EXHAUST DUCTWORK IN AMMONIA ROOM UP TO ABOVE CEILING TO REMAIN.
- 3. EXISTING 12"x24" WALL MOUNTED GRILLE AND MOTORIZED DAMPER ASSEMBLY TO REMAIN.
- 4. EXISTING 16" VENT PIPING FROM WET WELL UP THROUGH EXTERIOR WALL TO REMAIN.
- 5. EXISTING 54"x60" INTAKE AIR LOUVER AND MOTORIZED DAMPER ASSEMBLY TO REMAIN.
- 6. EXISTING GAS FIRED UNIT HEATER TO REMAIN.
- 7. EXISTING 3" COMBUSTION AIR AND 3" FLUE PIPE FROM GAS FIRED UNIT HEATER UP TO ABOVE TO REMAIN.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

DATE CHECKED: 01/11 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

LOW LIFT PUMP STATION FIRST FLOOR HEATING/VENTILATION DEMOLITION PLAN


PROJECT No

O0130014

LOW

HV-20-101

SHEET 042 OF 088 SHEETS



 SEE DRAWING HV-00-101 FOR GENERAL NOTES, LEGEND AND ABBREVIATIONS.

DEMOLITION KEYNOTES

- REMOVE EXISTING 3" EXHAUST PIPE FROM EXISTING NATURAL GAS FIRED GENERATOR (LOCATED BELOW) COMPLETE, INCLUDING ALL INSULATION, HANGERS, SUPPORTS, AND ACCESSORIES. PATCH OPENING IN WALL TO MATCH EXISTING.
- 2. REMOVE EXISTING GENERATOR SILENCER, INCLUDING ALL INSULATION, HANGERS, SUPPORTS AND ACCESSORIES.
- 3. REMOVE EXISTING 17"x24" EXHAUST DUCTWORK COMPLETE, INCLUDING ALL SUPPORTS, HANGERS, PADS AND ACCESSORIES. PATCH OPENING IN CEILING WATER TIGHT. SEE STRUCTURAL DRAWINGS FOR DETAILS.
- 4. REMOVE EXISTING INLINE EXHAUST FAN COMPLETE INCLUDING ALL SUPPORTS, HANGERS, CONTROLS, AND ACCESSORIES. REMOVE ALL DUCTWORK CONNECTED TO FAN.
- REMOVE EXISTING EXHAUST LOUVER IN EXTERIOR WALL. TEMPORARILY SEAL OPENING TO ALLOW MODIFICATIONS FOR NEW WORK. SEE DRAWING HV-20-202 FOR NEW WORK.
- 6. REMOVE 3" COMBUSTION AIR AND 3" FLUE FROM EXISTING GAS FIRED UNIT HEATER (LOCATED BELOW) AS REQUIRED TO ALLOW FOR RELOCATION OF EXISTING UNIT HEATER, INCLUDING SUPPORTS, HANGERS AND ACCESSORIES.
- 7. MODIFY AND RELOCATE EXISTING 3/4" DRAIN PIPING FROM EXHAUST PIPE AS REQUIRED TO ALLOW CONSTRUCTION OF NEW WALL.

⟨#⟩ KEYNOTES

- EXISTING 6" EXHAUST FROM GAS FIRED HORIZONTAL SHAFT PUMP (LOCATED BELOW) TO REMAIN.
- 2. EXISTING EXHAUST SILENCER FOR GAS FIRED HORIZONTAL SHAFT PUMP TO REMAIN.
- 3. EXISTING 10"x12" EXHAUST DUCTWORK FROM AMMONIA ROOM TO REMAIN.
- 4. EXISTING 16" VENT PIPING FROM WET WELL UP THROUGH EXTERIOR WALL TO REMAIN.
- 5. EXISTING 3" COMBUSTION AIR AND 3" FLUE VENT PIPE FROM GAS FIRED UNIT HEATER (LOCATED BELOW) TO REMAIN.
- 6. EXISTING EXHAUST FAN ON PLATFORM TO REMAIN.
- 7. EXISTING 72"x72" EXHAUST LOUVER TO REMAIN.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST.
2/3/11 ISSUED FOR BIDS
DATE REVISION

LOW LIFT PUMP STATION MEZZANINE HEATING/VENTILATION DEMOLITION PLAN

PROJECT No.

O0130014

HV-20-102

SHEET 043 OF 088 SHEETS

- SEE DRAWING HV-00-101 FOR GENERAL NOTES, LEGEND AND ABBREVIATIONS.
- ALL EQUIPMENT ASSOCIATED WITH GENERATOR (e.g. HEAT EXCHANGERS, EXPANSION TANKS, SILENCER, COOLANT PIPING, EXHAUST PIPING, ETC.) SHALL BE INSTALLED PER MANUFACTURER INSTALLATION INSTRUCTIONS.
- SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF THE WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.

KEYNOTES

- 1. EXISTING 6" EXHAUST PIPE FROM GAS FIRED HORIZONTAL SHAFT PUMP UP TO HIGH LEVEL.
- EXISTING 10"x12" EXHAUST DUCTWORK IN CHEMICAL ROOM UP TO ABOVE CEILING.
- EXISTING 12"x24" WALL MOUNTED GRILLE AND MOTORIZED DAMPER ASSEMBLY.
- 4. EXISTING 16" VENT PIPING FROM WET WELL UP THROUGH EXTERIOR WALL.
- 5. EXISTING 54"X60" INTAKE AIR LOUVER AND MOTORIZED DAMPER ASSEMBLY.
- 6. EXISTING GAS FIRED UNIT HEATER.
- 7. EXISTING COMBUSTION AIR AND FLUE PIPING FROM GAS FIRED UNIT HEATER UP HIGH LEVEL.
- 8. PROVIDE GAS FIRED UNIT HEATER <u>GUH-102</u>. PROVIDE MANUFACTURER'S WALL/CEILING MOUNTED SUPPORT KIT. CONNECT COMBUSTION AIR INTAKE AND FLUE VENT TO UNIT HEATER.
- 9. PROVIDE INTAKE AIR LOUVER <u>IL—#</u>. PROVIDE REMOVABLE LOUVERS. COORDINATE LOCATION AND ELEVATION WITH ARCHITECTURAL DRAWINGS. PROVIDE SECTIONAL MOTORIZED DAMPERS IN WALL OPENING. SEE ELECTRICAL DRAWINGS FOR CONTROLS AND OPERATION.
- 10. NATURAL GAS GENERATOR GEN-102.
- 11. 48"x48" EXHAUST DUCTWORK UP THROUGH GENERATOR ROOM CONCRETE CEILING. TERMINATE DUCTWORK BELOW BOTTOM OF CEILING. PROVIDE EXHAUST GRILLE ON OPENING AS INDICATED. SEE DETAIL 1/HV-30-201.
- PROVIDE 12" GENERATOR EXHAUST PIPING UP FROM NATURAL GAS GENERATOR THROUGH GENERATOR ROOM CONCRETE CEILING. SEAL OPENING WATER TIGHT.
- 13. GAS FIRED UNIT HEATER. CONNECT COMBUSTION AIR AND FLUE TO UNIT HEATER. SUPPORT UNIT FROM STRUCTURE ABOVE.
- 14. EXTEND EXISTING 3" COMBUSTION AIR AND 3" FLUE PIPE. CONNECT TO EXISTING COMBUSTION AIR AND FLUE PIPE.
- 15. PROVIDE 6" JACKET WATER COOLANT SUPPLY PIPING FROM HEAT EXCHANGER (LOCATED ABOVE) TO GENERATOR.
- 16. PROVIDE 6" JACKET WATER COOLANT RETURN PIPING FROM GENERATOR TO HEAT EXCHANGER (LOCATED ABOVE).
- 17. PROVIDE 3" AFTER COOLER COOLANT SUPPLY PIPING FROM HEAT EXCHANGER (LOCATED ABOVE) TO GENERATOR.
- 18. PROVIDE 3" AFTER COOLER COOLANT RETURN PIPING FROM GENERATOR TO HEAT EXCHANGER (LOCATED ABOVE).
- 19. PROVIDE 4" COMBUSTION AIR INTAKE AND 4" FLUE FROM GAS FIRED UNIT HEATER. ROUTE PIPING AS CLOSE TO CEILING AS POSSIBLE.
- 20. PROVIDE GAS FIRED UNIT HEATER MANUFACTURER'S CONCENTRIC VENT KIT. USE AND MODIFY EXISTING EXTERIOR WALL PENETRATION FOR KIT INSTALLATION AS REQUIRED. SEE DETAIL 5/HV-30-201.
- 21. PROVIDE 2" PIPING FOR CRANKCASE FUME DISPOSAL AND DRIP COLLECTOR. USE AND MODIFY EXISTING EXTERIOR WALL PENETRATION FOR FUME DISPOSAL PIPING. SEAL OPENING WATER TIGHT.
- 22. PROVIDE THERMOSTATS FOR EXISTING UNIT HEATERS AND EXHAUST FAN. CONNECT/EXTEND EXISTING WIRING TO NEW THERMOSTAT AS REQUIRED. SEE ELECTRICAL DRAWINGS FOR CONTROLS AND OPERATION.
- 23. PROVIDE 5" FLUE AND 5" COMBUSTION AIR UP FROM WATER HEATER $\underline{\text{WH}-102}$.
- 24. INSTALL THERMOSTAT ON INSULATED BASE.



DESIGN FIRM REGISTRATION No. 184-000450

> 125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


LOW LIFT PUMP STATION FIRST FLOOR HEATING/VENTILATION PLAN

PROJECT No. 00130014

.....

HV-20-201

SHEET 044 OF 088 SHEETS



- 1. SEE DRAWING HV-00-101 FOR GENERAL NOTES, LEGEND AND ABBREVIATIONS.
- 2. ALL EQUIPMENT ASSOCIATED WITH GENERATOR (e.g. HEAT EXCHANGERS, EXPANSION TANKS, SILENCER, COOLANT PIPING, EXHAUST PIPING, ETC.) SHALL BE INSTALLED PER MANUFACTURER INSTALLATION INSTRUCTIONS.
- 3. SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF THE WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.

KEYNOTES

- EXISTING 6" EXHAUST PIPE FROM GAS FIRED HORIZONTAL SHAFT PUMP (LOCATED BELOW).
- 2. EXISTING EXHAUST SILENCER FOR GAS FIRED HORIZONTAL SHAFT PUMP.
- 3. EXISTING 10"x12" EXHAUST DUCTWORK FROM CHEMICAL ROOM.
- 4. EXISTING 16" Ø VENT PIPING FROM WET WELL UP THROUGH EXTERIOR WALL.
- 5. EXISTING COMBUSTION AIR AND FLUE VENT PIPING FROM GAS FIRED UNIT HEATER (LOCATED BELOW).
- 6. EXISTING 72"x72" EXHAUST LOUVER.
- PROVIDE 48"x48" EXHAUST DUCTWORK UP FROM GENERATOR ROOM BELOW. BUILD DUCTWORK TO USE AS A PLENUM. CONNECT DUCTWORK FROM FAN TO PLENUM. SEE DETAIL 1/HV-30-201.
- 8. PROVIDE EXHAUST FAN $\underline{\text{EF}-105}$. CONNECT DUCTWORK TO/FROM FAN. SEE DETAIL 9/HV-30-201.
- 9. PROVIDE EXHAUST LOUVER <u>EL-101</u>. SEE DRAWING A-20-201. COORDINATE LOCATION AND ELEVATION WITH ARCHITECTURAL DRAWINGS. PROVIDE 18" DEEP PLENUM OF SAME SIZE BEHIND LOUVER. CONNECT DUCTWORK FROM <u>EF-105</u>.
- 10. PROVIDE 12"Ø EXHAUST PIPE UP FROM NATURAL GAS GENERATOR (LOCATED BELOW IN GENERATOR ROOM).
- 11. GENERATOR SILENCER. TRANSITION EXHAUST PIPE TO/FROM SILENCER AS REQUIRED.

 MOUNT SILENCER ON 6" SUPPORT STAND ON CEILING. ROUTE CONDENSATE PIPING TO DRAIN PIPING. SEE PLUMBING DRAWINGS FOR LOCATION.
- 12. PROVIDE 12"Ø EXHAUST PIPE FROM SILENCER. CONNECT TO SILENCER. TERMINATE PIPING WITH MANUFACTURERS TERMINATION KIT. SEAL OPENING IN WALL WATER TIGHT. SEE DETAIL 6/HV-30-202.
- 13. PROVIDE 3" COMBUSTION AIR AND 3" FLUE VENT PIPE FROM RELOCATED GAS FIRED UNIT HEATER. CONNECT TO EXISTING COMBUSTION AIR AND FLUE PIPE AS REQUIRED.
- 14. PROVIDE 5" FLUE AND 5" COMBUSTION AIR UP FROM LOWER LEVEL. ROUTE DUCTWORK UP THROUGH EXTERIOR WALL. PROVIDE MANUFACTURER'S TERMINATION KIT. SEAL OPENING WATER TIGHT.
- 15. JACKET WATER HEAT EXCHANGER <u>HX-102A</u>. INSTALL HEAT EXCHANGER ON GENERATOR ROOM CEILING. SEE DRAWING P-20-202 FOR WATER SUPPLY AND DRAIN PIPING. SEE DETAIL 5/HV-30-202.
- 16. AFTER COOLER HEAT EXCHANGER <u>HX-102B</u>. INSTALL HEAT EXCHANGER ON GENERATOR ROOM CEILING. SEE DRAWING P-20-202 FOR WATER SUPPLY AND DRAIN PIPING. SEE DETAIL 5/HV-30-202.
- 17. PROVIDE INSULATED 6" JACKET WATER COOLANT SUPPLY PIPING DOWN FROM HEAT EXCHANGER TO GENERATOR (LOCATED BELOW IN GENERATOR ROOM). SEAL OPENING IN GENERATOR ROOM CONCRETE CEILING WATER TIGHT. SEE DETAIL 4/HV-30-201.
- 18. PROVIDE INSULATED 6" JACKET WATER COOLANT RETURN PIPING UP FROM GENERATOR (LOCATED BELOW IN GENERATOR ROOM) TO HEAT EXCHANGER. SEAL OPENING IN GENERATOR ROOM CONCRETE CEILING WATER TIGHT. SEE DETAIL 4/HV-30-201.
- 19. PROVIDE INSULATED 3" AFTER COOLER COOLANT SUPPLY PIPING DOWN FROM HEAT EXCHANGER TO GENERATOR (LOCATED BELOW IN GENERATOR ROOM). SEAL OPENING IN GENERATOR ROOM CONCRETE CEILING WATER TIGHT. SEE DETAIL 4/HV-30-201.
- 20. PROVIDE INSULATED 3" AFTER COOLER COOLANT RETURN PIPING UP FROM GENERATOR (LOCATED BELOW IN GENERATOR ROOM) TO HEAT EXCHANGER. SEAL OPENING IN GENERATOR ROOM CONCRETE CEILING WATER TIGHT. SEE DETAIL 4/HV-30-201.
- 21. EXISTING EXHAUST FAN ON PLATFORM.
- 22. EXPANSION TANK FOR JACKET WATER LOOP. SUPPORT FROM ROOF STRUCTURE ABOVE.
- 23. EXPANSION TANK FOR AFTER COOLER LOOP. SUPPORT FROM ROOF STRUCTURE ABOVE.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED E SCALING ANY PORTION OF THIS DRAWING.

> LOW LIFT PUMP STATION MEZZANINE EATING/VENTILATION PLAN

PROJECT No. 00130014

DRAWING No.

HV-20-202

SHEET 045 OF 088 SHEETS

		BOILER SCH	EDULE	- GAS	FIRF)									
		SERVICE		DATA	1 \	<u> </u>			5WT 4 WT	ELI	EC. CH.	AR.		DESIGN	BASIS
TA	4G	LOCATION	INPUT (CFH)	MIN PRESS (IN WC)	(MBH)	OUTPUT (MBH)	MEDIA	FLOW RATE (GPM)	EWI/LWI (°F)	٧	PH	HZ	REMARKS	MANUFACTURER	MODEL NUMBER
В-	101	HEATING SYSTEM MECHANICAL ROOM	1800	7 - 11	1800	1440	WATER	88.0	200/240	120	1	60	NOTE 1	BRYAN BOILERS	CLM-180-W

1. PROVIDE PRESSURE & TEMPERATURE RELIEF VALVE, MANUFACTURER'S CONTROLS, BURNER/BLOWER ASSEMBLY, AND MANUFACTURER'S GAS TRAIN.
2. PROVIDE MANUFACTURER'S CONCENTRIC VENT KIT.

	EXPANSION	TANK SC	HEDULE								
TAG	SERVICE	TVDE	ASME	PRESSURE	TANK	TANK SIZE (IN.)	OPER. TEMP.	AIR PRE-CHARGE	REMARKS	DESIGN	BASIS
TAG	LOCATION	TYPE	CONSTR.	RATING (PSIG)	CAPACITY (GAL)	LGTH. x DIAM.	(*F)	PRESSURE (PSIG)	REMARKS	MANUFACTURER	MODEL NUMBER
ET-101	HEATING SYSTEM MECHANICAL ROOM	COMPRESSION TYPE	YES	60	100.0	78x20	240	30.0		BELL & GOSSETT	100

	PUMP SCHEDULE												
	SERVICE			PUMP	DATA			ELE	EC. CH	AR.		DESIG	N BASIS
TAG	LOCATION	TYPE	OPER. TEMP. (*F)	FLOW (GPM)	T.D.H. (FT. OF H20)	RPM	MOTOR HP	٧	PH	HZ	REMARKS	MANUFACTURER	MODEL NUMBER
HWP-101	DEHUMIDIFICATION UNIT MECHANICAL ROOM	IN-LINE	240	44	75	1750	5	480	3	60	NOTE 1, 2	BELL & GOSSETT	80-2x2x9-1/2
HWP-102	HEATING SYSTEM BACK-UP MECHANICAL ROOM	IN-LINE	240	44	75	1750	5	480	3	60	NOTE 1, 2	BELL & GOSSETT	80-2x2x9-1/2
HWP-103	HEATING SYSTEM MECHANICAL ROOM	IN-LINE	240	44	75	1750	5	480	3	60	NOTE 1, 2	BELL & GOSSETT	80-2x2x9-1/2

NOTES:

1. PROVIDE LINE SIZE TRIPLE DUTY VALVE.
2. INTERCONNECT PUMPS TO RELOCATED TEMPERATURE CONTROL PANEL. SEE ELECTRICAL DRAWINGS FOR DETAILS.

l	UNIT HEATER	SCHE	DULE	— G	AS F	TRED											
		AIRFLOW	F	AN DATA		TEMP RISE	INPUT	ОИТРИТ	GAS PRESS	NO OF	ELEC	CTRIC D	ATA	MOUNTING		DESIGN	BASIS
TAG	LOCATION	PATTERN	AIR VOL.	THROW (FT.)	MOTOR HP	(*F DB)	(MBH)	(MBH)		STAGES	٧	PH	HZ	HEIGHT	REMARKS	MANUFACTURER	MODEL NUMBER
GUH-101	WTP-ELECTRICAL ROOM	HORIZ.	1345	30	1/6	60	105	87.15	10	1	120	1	60	9'-0"	NOTES 1, 2, 3	REZNOR	UDAS 100
GUH-102	LLPS-GENERATOR ROOM	HORIZ.	1345	30	1/6	60	105	87.15	10	1	120	1	60	9'-0"	NOTES 1, 2, 3	REZNOR	UDAS 100

NOTES:

PROVIDE WITH MANUFACTURER'S WALL MOUNTED ADJUSTABLE THERMOSTAT, WALL SUPPORT KIT AND CONCENTRIC VENT KIT. PROVIDE STAINLESS STEEL HEAT EXCHANGERS AND TOTALLY ENCLOSED MOTOR.

PROVIDE STAINLESS STEEL HEAT EXCHANGERS AND TOTAL
 ADJUST INTEGRAL LOUVER TO ACHIEVE REQUIRED THROW.

	FAN SCHEDULE												
	SERVICE	AIR VOL.	EXT. S.P.	FAN SPEED	MOTOR			ELE	CTRIC [DATA		DESIGN	BASIS
TAG	LOCATION		(IN. W.C.)		(HP)	DRIVE	FAN TYPE	٧	PH	HZ	REMARKS	MANUFACTURER	MODEL NUMBER
EF-101	GENERATOR COMBUSTION AIR WTP-ROOF	8335	0.2	551	1-1/2	BELT	CENT.	480	3	60	NOTE 1	GREENHECK	CUBE-300-15
EF-102	GENERATOR/SPACE HEAT RELIEF WTP-ROOF	8335	0.2	551	1-1/2	BELT	CENT.	480	3	60	NOTE 1	GREENHECK	CUBE-300-15
EF-103	GENERATOR/SPACE HEAT RELIEF WTP-ROOF	8335	0.2	551	1-1/2	BELT	CENT.	480	3	60	NOTE 1	GREENHECK	CUBE-300-15
EF-104	MECHANICAL ROOM WTP-ROOF	300	0.25	979	1/4	BELT	CENT.	480	3	60	NOTE 1	GREENHECK	CUBE-098-4
EF-105	GENERATOR ROOM LLPS-MEZZANINE	25000	0.5	1,410	10	BELT	VANE AXIAL	480	3	60	NOTE 2	GREENHECK	VAB-36F17-I-10

1. PROVIDE WITH MANUFACTURER'S 12" ROOF CURB.
2. PROVIDE WITH INVERTERDUTY MOTOR FOR VFD APPLICATION. SEE ELECTRICAL DRAWINGS FOR DETAILS.

	GRILLES &	DIFFU	SER S	CHED	ULE						
TAG	TYPE	FACE SIZE	AIR PATTERN	THROW (FEET)	MOUNTING	MATERIAL	FINISH	MAX N.C. LEVEL	REMARKS	DESIGN MANUFACTURER	BASIS MODEL NUMBER
EG-1	3/4" SPACING 0" DEFLECTION	VARIES			SURFACE	STEEL	NOTE 1	30		TITUS	350ZFL

1. FINISH/COLOR TO BE SELECTED BY THE OWNER/ARCHITECT.



125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

HEATING EQUIPMENT SCHEDULES

PROJECT No. O0130014

HV-30-101

SHEET 046 OF 088 SHEETS

	LOUVER SCHEDULE	Ξ											
	SERVICE			AIR VOL.	5	SIZE (IN	1)	MAX. VEL.	FREE AREA			DESIGN	BASIS
TAG	LOCATION	MATERIAL	TYPE	(CFM)	w	н	D	(FPM)	(SQ. FT.)	FINISH	REMARKS	MANUFACTURER	MODEL NUMBER
IL-101	GEN-101 COMBUSTION AIR	AT LINAINILINA	FLANGED	8335	36	100	6	525	15.47	NOTE 2	NOTE 1	AWV	LE31
IL-101	WTP-ELECTRICAL ROOM	ALUMINUM	PLANGED	6333	36	100	0	525	15.47	NOTE 2	NOTE 1	AWV	LEJI
IL-102	GEN-101/ROOM HEAT RELIEF	AT LINAINILINA	FLANGED	8335	36	100	6	525	15.47	NOTE 2	NOTE 1	AWV	LE31
11-102	WTP-ELECTRICAL ROOM	ALUMINUM	FLANGED	8333	30	100	0	323	13.47	NOTE 2	NOTE 1	AWV	LLJI
IL-103	GEN-101/ROOM HEAT RELIEF	AL LIMINILIM	FLANGED	8335	36	100	6	525	15.47	NOTE 2	NOTE 1	AWV	LE31
IL-103	WTP-ELECTRICAL ROOM	ALOWINOW	TLANGLD	0333	30	100		323	13.47	NOIL Z	NOTE 1	All V	LLST
IL-105A	GEN-101 COMBUSTION AIR	ALUMINUM	FI ANCED	8335	36	104	6	525	15.47	NOTE 2	NOTE 1	AWV	LE31
IL TOOK	LLPS-GENERATOR ROOM	ALOWINGIN	TEANOLD	0555	30	107	Ů	323	13.47	NOIL Z	NOTE 1	7,111	LLOT
IL-105B	GEN-101/ROOM HEAT RELIEF	ALLIMINI IA	FLANGED	8335	36	104	6	525	15.47	NOTE 2	NOTE 1	AWV	LE31
IL-103B	LLPS-GENERATOR ROOM	ALOWINOW	TLANGLD	0333	30	10+		323	13.47	NOIL Z	NOTE 1	All V	LLST
IL-105C	GEN-101/ROOM HEAT RELIEF	AL LIMINILIM	FLANGED	8335	36	104	6	525	15.47	NOTE 2	NOTE 1	AWV	LE31
IL-103C	LLPS-GENERATOR ROOM	ALOWINOW	ILANGED	0333	30	104	"	323	13.47	NOIL 2	NOTE	AWV.	LLST
EL-101	EF-105	AL LIMINILIM	FLANGED	25000	96	52	6	1200	20.84	NOTE 2	NOTE 1	AWV	LE31
LL-101	LLPS-MEZZANINE	ALOMINOM	LANGED	25000	30	32	"	1200	20.04	I NOTE Z	INOTE I		LLS

EQUIP	MENT (CONNEC	TION S	CHEDUL	.E	
TAG	HWS	HWR	JWCS	JWCR	ACCS	ACCR
HX-101A			6"	6"		
HX-101B					2"	2"
HX-102A			6"	6"		
HX-102B					2"	2"
HWP-101	2" (2)					
HWP-102	2" (2)					
HWP-103	2" (2)					
B-101	3"	3"				
AS-101	3"	3"				
ET-101	1"					
CHEMICAL FEEDER		3/4"				

- 1. PROVIDE WITH FRAMED BIRD SCREEN, REMOVABLE FROM OUTSIDE, TO MATCH LOUVER FINISH.
- 2. FINISH/COLOR TO BE SELECTED BY THE OWNER/ARCHITECT

	DAMPER SCHEDUL	Ε					
TAG	SERVICE LOCATION	DAMPER SIZE (IN WIDTH HEIGHT		BLADE CONFIGURATION	MOUNTING	TYPE	REMARKS
MD-101	INTAKE LOUVER, IL-101 WTP-ELECTRICAL ROOM	- 36	100	PARALLEL	NOTE 1	TWO-POSITION	
MD-102	INTAKE LOUVER, IL-102 WTP-ELECTRICAL ROOM	- 36	100	PARALLEL	NOTE 1	TWO-POSITION	
MD-103	INTAKE LOUVER, IL-103 WTP-ELECTRICAL ROOM	- 36	100	PARALLEL	NOTE 1	TWO-POSITION	
MD-104	INTAKE LOUVER, IL-104 WTP-MECHANICAL ROOM	22	22	PARALLEL		TWO-POSITION	
MD-105A	INTAKE LOUVER, IL-105A LLPS-GENERATOR ROOM	- 36	104	PARALLEL	NOTE 1	TWO-POSITION	
MD-105B	INTAKE LOUVER, IL-105B LLPS-GENERATOR ROOM	- 36	104	PARALLEL	NOTE 1	TWO-POSITION	
MD-105C	INTAKE LOUVER, IL-105C	- 36	104	PARALLEL	NOTE 1	TWO-POSITION	

DAMPERS SHALL BE MOUNTED BEHIND LOUVERS, AND WITHIN THE WALL OPENING. PROVIDE DUCT COLLAR FOR DAMPER MOUNTING.

AIR INLET/OUTLET CONNECTION SCHEDULE										
SYMBOL	TAG	NECK SIZE	DUCT SIZE	REMARKS						
(1)	EG-1		48"x48"	NOTE 1						

NOTES:

1. PROVIDE WITH INTEGRAL, GANG OPERATED, OPPOSED BLADE DAMPER.

INTAKE/EXHAUST VENTILATOR SCHEDULE								
TAG	SERVICE	AIR VOL.	S.P.	THROAT	MAX, VELOCITY	851118118	DESIGN	BASIS
	LOCATION	(CFM)	(IN W.C.)	AREA (FT²)	(FPM)	REMARKS	MANUFACTURER	MODEL NUMBER
IV-101	B-1, EF-104	1680	0.03	3.36	500	NOTE 1	GREENHECK	FGI SERIES
1, 101	ROOF	1 1000	0.00	0.50	300	14012 1	OKLENITECK	1 Of SERVES

NOTES:

1. PROVIDE 14" HIGH MANUFACTURER'S ROOF CURB.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP
DATE CHECKED: 01/11


NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

HEATING EQUIPMENT SCHEDULES

PROJECT No. O0130014

HV-30-102 SHEET 047 OF 088 SHEETS



Clark Lietz

DESIGN FIRM REGISTRATION No. 184-000450

> 125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER


DESIGNED BY: NTP
DRAWN BY: NTP
CHECKED BY: KRP

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

HV-30-201

SHEET 048 OF 088 SHEETS



ELECTRICAL GENERAL NOTES

- 1. ALL WORK SHALL CONFORM TO THE 2008 NATIONAL ELECTRICAL CODE AND ALL
- 2. CONTRACTOR SHALL FURNISH ALL MATERIALS FOR A COMPLETE AND WORKABLE SYSTEM. ALL MATERIALS FURNISHED BY THE CONTRACTOR ARE TO BE NEW.
- ALL CONDUIT SHALL BE RIGID GALVANIZED STEEL CONNECTED TO THREADED HUB FITTINGS, UNLESS OTHERWISE NOTED. ALL UNDERGROUND CONDUIT SHALL BE PVC. EXCEPT FOR ELBOWS TURNING UP FROM DUCTBANKS AND CONDUITS EXTÉNDING ABOVE GRADE SHALL BE RGS. UNDERGROUND PVC CONDUITS SHALL HAVE CONCRETE ENCASED DUCTBANKS DOWELED INTO BUILDING OR STRUCTURE WALLS TO AVOID SHEARING OF THE PVC CONDUITS. ALL CONDUITS SHALL BE EXPOSED IN SPACE UNLESS OTHERWISE NOTED BELOW:
- CONDUIT IN SPACES WITH DROP CEILINGS SHALL BE EMT AND INSTALLED ABOVE DROP CEILING.
- CONDUITS INDICATED ON PLANS SHALL BE INSTALLED AS NOTED.
- PAINT ALL RACEWAYS (E.G. CONDUITS, BOXES, WIRE TROUGHS, ETC.) EXPOSED IN ROOMS LIGHT GRAY TO MATCH EXISTING PAINT COLOR OF EXISTING CONDUITS AT THE PLANT. PROVIDE LABELS ON ALL RACEWAYS AND BOXES TO MATCH EXISTING AT PLANT.
- 5. ALL BRANCH CIRCUIT WIRING AND MOTOR LEADS SHALL BE #12 AWG IN 3/4" CONDUIT, UNLESS OTHERWISE NOTED.
- REMOVE ALL UNUSED CONDUIT AND WIRE FROM EQUIPMENT BEING REMOVED OR RELOCATED BACK TO SOURCE. CONCEALED CONDUIT BELOW SLAB OR UNDERGROUND MAY REMAIN IN PLACE (CUT OFF CONDUITS FLUSH AT WALL OR FLOOR AND FILL IN CONDUIT OPENING). PATCH AND PAINT OPENING IN WALL OR FLOOR TO MATCH EXISTING SURFACE.
- CONTRACTOR IS RESPONSIBLE FOR DISPOSAL OF ALL MATERIALS REMOVED AS PART OF THIS PROJECT, INCLUDING BUT NOT LIMITED TO MCC, FIXTURES, LAMPS, BALLASTS (WITH AND WITHOUT PCB), CONDUIT, WIRE AND OTHER BUILDING MATERIALS. DISPOSAL SHALL BE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. ALL DISPOSAL SHALL BE AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL INCLUDE \$1,000.00 IN HIS BID AS ALLOWANCE FOR TESTING/DISPOSAL.
- THE LOCATION OF UTILITIES AND STRUCTURES, BOTH SURFACE AND SUBSURFACE, ARE SHOWN ON THE PLANS FROM DATA AVAILABLE AT THE TIME OF THE SURVEY AND ARE NOT NECESSARILY COMPLETE OR CORRECT. THE EXACT LOCATION AND PROTECTION OF UTILITIES AND STRUCTURES IS THE RESPONSIBILITY OF THE CONTRACTOR. DURING CONSTRUCTION THE CONTRACTOR SHALL USE DILIGENCE TO PROTECT ALL EXISTING UTILITIES AND STRUCTURES WHETHER SHOWN ON THE DRAWINGS OR NOT. IF DAMAGE IS CAUSED, THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPAIR AND RESTORATION OF SAME IN ACCORDANCE WITH THE DIRECTIONS OF THE OWNER AND FOR ANY RESULTING CONTINGENT
- 9. ALL ACCESS CONTROL/VIDEO MONITORING WIRING SHALL BE INSTALLED IN
- 10. ALL WIRING DEVICES SHALL BE BROWN IN COLOR. ALL COVER PLATES SHALL BE STAINLESS STEEL, UNLESS OTHERWISE NOTED.
- 11. EACH HOMERUN TO PANELBOARDS SHALL CONSIST OF A MAXIMUM OF THREE CIRCUITS WITH THE FOLLOWING WIRES: 3 HOTS, 3 NEUTRALS AND ONE GROUND. EACH SINGLE PHASE CIRCUIT SHALL HAVE ITS OWN NEUTRAL (I.E. NO SHARING OF NEUTRALS). WHEN COMBINING POWER AND CONTROL WIRING IN RACEWAYS FOR PROCESS AND INSTRUMENTATION EQUIPMENT, DERATE WIRE AND PROVIDE WIRE FILL IN RACEWAY PER THE NEC.
- 12. ALL CONDUCTORS SHALL BE CONTINUOUS FROM POINT OF ORIGIN TO THE END USE LOAD. NO CONDUCTORS SHALL BE SPLICED EXCEPT AS SHOWN ON THE DRAWINGS OR ON EXPLICIT INSTRUCTIONS FROM THE ENGINEER.

ELECTRICAL LEGEND

GAS RAW WATER

SEWER

STORM DRAIN

SANITARY SEWER

TELEPHONE

WATER

SPENT WASH WATER

RECLAIMED WASH WATER

SUMP PUMP DISCHARGE

TO BE REMOVED OR ABANDONED

____RWW____

—SD—

----ss----

----sww----

____т___

**}}*

NOTE: SYMBOLS SHOWN LIGHT ARE EXISTING, BOLD ARE NEW. 図 WALL MOUNTED HID LIGHT FIXTURE PANEL, MCC OR SWITCHGEAR FLUORESCENT LIGHT FIXTURE FEEDER CIRCUIT FLUORESCENT LIGHT FIXTURE WITH EMERGENCY BATTERY PACK SWITCH ___ \otimes WALL MOUNTED EXIT SIGN CIRCUIT BREAKER \square DUAL HEAD EMERGENCY LIGHT +□+ FUSE +~+ SOFT START CONTROLLER OR VFD ഗ# SINGLE POLE LIGHT SWITCH (# INDICATES SWITCH LEG) -}[-ഗ^{3,#} TRANSFORMER THREE WAY LIGHT SWITCH (# INDICATES SWITCH LEG) 0 **GENERATOR** 2₩ DUPLEX RECEPTACLE (NUMBER INDICATES CIRCUIT IN PANEL) 2

GFI GROUND FAULT CIRCUIT INTERRUPTER DUPLEX RECEPTACLE (NUMBER TRANSFER SWITCH INDICATES CIRCUIT IN PANEL) WEATHERPROOF GROUND FAULT CIRCUIT INTERRUPTER DUPLEX 2 - WP,GFI ∄ CT'S/PT'S RECEPTACLE (NUMBER INDICATES CIRCUIT IN PANEL) **≪**□≫ \circ^{M} DRAWOUT BREAKER MANUAL MOTOR STARTER LLPS LOW LIFT PUMP STATION \Box COMBINATION STARTER/DISCONNECT SWITCH WTP WATER TREATMENT PLANT 42 FUSIBLE DISCONNECT SWITCH $\dashv\vdash$ NORMALLY OPEN CONTACT \Box NON-FUSED DISCONNECT SWITCH NORMALLY CLOSED CONTACT 10 MOTOR (SEE EQUIPMENT CONNECTION SCHEDULE FOR HORSEPOWER) —a.l.a— PUSHBUTTON J JUNCTION OR PULLBOX SELECTOR SWITCH HS HAND SWITCH MD MOTORIZED DAMPER PUSH TO TEST INDICATING LIGHT (A)— ELECTRICALLY INTERLOCKED BREAKER DISCONNECT SWITCH (K)— KIRK-KEY INTERLOCKED BREAKER GROUND PROTECTIVE RELAYING LIGHT FIXTURE DESIGNATIONS: (M)---WE ENERGY METER M ---OWNER METERING INDICATES FIXTURE TYPE S WALL MOUNTED INTERCOM SPEAKER INDICATES SWITCH LEG (IF APPLICABLE) Р WALL MOUNTED HANDSET INDICATES CIRCUIT IN LIGHTING PANEL (IF APPLICABLE) INTERCOM VIDEO CAMERA **ELECTRICAL ABBREVIATIONS** CR CARD READER ES ELECTRIC DOOR STRIKE DC DOOR CONTACT RX REQUEST-TO-EXIT DEVICE BS BREAK GLASS SWITCH DISCHARGE TRANSMISSION MAIN **ELECTRICAL**

Α	AMPERES	MCP	
AF	AMPERES FRAME	MET	
AFF	ABOVE FINISHED FLOOR	MFR	MANUFACTURER
ALUM	ALUMINUM	MLO	MAIN LUG ONLY
ΑT	AMPERES TRIP	MMS	MANUAL MOTOR STARTER
ATS	AUTOMATIC TRANSFER SWITCH	N/A	NON APPLICABLE
CKT	CIRCUIT	NĹ	
CLG	CEILING	OL	OVERLOADS
CONC	CONCRETE	ос	OVERCURRENT
CONT	CONTINUED	P	POLE
D	DEEP	PH	PHASE
DN	DOWN	PLC	PROGRAMMABLE LOGIC CONTROLLER
Ε	ELECTRIC	PNL	
EM	EMERGENCY	PRI	
FDR	FEEDER	PTZ	PAN/TILT/ZOOM
FLA	FULL LOAD AMPERES	PVC	
FLUOR	FLUORESCENT	REX	
FVNR	FULL VOLTAGE NON REVERSING	RGS	
G,GND	GROUND	SEC	
GEN	GENERATOR	TP	
GFI	GROUND FAULT INTERRUPTER	TSP	
Н	HIGH	TYP	
HID	HIGH INTENSITY DISCHARGE	UPS	UNINTERRUPTIBLE POWER SUPPLY
HP	HORSEPOWER	V	VOLTS
KV	KILO-VOLT	VΑ	VOLT AMPERES
KVA	KILO-VOLT AMPERES	VFD	
KW	KILOWATTS	w	WIDE
LED	LIGHT EMITTING DIODE	WP	WEATHER PROOF
		**!	TE TILL TROOT

WTP

XFMR

LOW LIFT PUMP STATION

MOTOR CONTROL CENTER

LIGHTING PANEL

MOTOR

LLPS

MCC

TRANSFORMER

WATER TREATMENT PLANT



DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

MENT PLANT PUMP STATION POWER

TREATME
'LIFT PUI
ANDBY PO ER 1 OW STAI AND

DESIGNED BY: SEM DRAWN BY: CHECKED BY: DATE CHECKED: NOTE: DIMENSIONAL DATA


SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS REVISION

> ELECTRICAL ERAL NOTES, LEGEND, ND ABBREVIATIONS NERA AND $\overline{\Omega}$

PROJECT No O0130014

E-00-101 SHEET 050 OF 088 SHEETS



- 1. SEE DRAWING E-00-101 FOR ELECTRICAL GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.

KEYNOTES

- 1. EXISTING OUTDOOR 24.9 KV SWITCHGEAR.
- 2. TRANSFORMER XFMR-3A WEST.
- 3. EXISTING TRANSFORMER XFMR-3B EAST.
- 4. EXISTING WE ENERGIES 25 KV FEED #1 WEST SOURCE (PENNSYLVANIA AVE. SUBSTATION).
- 5. EXISTING WE ENERGIES 25 KV FEED #2 EAST SOURCE (PENNSYLVANIA AVE. SUBSTATION).
- 6. EXISTING LOW LIFT PUMP STATION 25 KV FEED #1.
- 7. EXISTING LOW LIFT PUMP STATION 25 KV FEED #2.
- 8. EXISTING NORTH GATE OPENER.
- 9. EXISTING NORTH GATE CARD READER.
- 10. PROVIDE THE FOLLOWING DIRECT BURIED CONDUITS (LOCATE CONDUITS 48" WEST OF EXISTING CHAIN LINK FENCE). SEE DRAWING E-10-301 AND E-10-402 FOR CONTINUATION.
 - 1" CONDUIT WITH 3#12, 1#12 GROUND FOR POWER FROM PANEL B-RIGHT TO NORTH GATE OPENER.
- 1" CONDUIT WITH CONTROL WIRES TO NORTH GATE CONTROLLER.
- 1" CONDUIT WITH CONTROL WIRES FOR NORTH GATE CARD READERS AND INTERCOM.
- 1" SPARE CONDUIT.
- 11. REMOVE EXISTING SHRUBS FOR INSTALLATION OF DIRECT BURIED
- 12. REPLACE 480 VOLT FEEDER CONDUCTORS IN EXISTING UNDERGROUND CONDUITS FROM USS NO. 1 AND USS NO. 2 TO MCC-10 (SEE DRAWINGS E-10-403 AND E-10-501 FOR CONTINUATION).
- 13. PROVIDE (2) 1" DIRECT BURIED CONDUITS WITH WIRING TO CARD READER. SAWCUT ASPHALT SURFACE TO REMOVE AS REQUIRED FOR INSTALLATION OF CONDUITS (PATCH TO MATCH EXISTING SURFACE).
- 14. EXISTING METER PIT. REPLACE CONTROL WIRING FROM METER TO RELOCATED AUTOCON METER PIT PANEL (EXTEND CONDUIT IN BUILDING
- 15. REMOVE ABANDONED (2) 2#18 TSP CABLES FROM METER TO EXISTING AUTOCON PANEL LOCATED IN ELECTRICAL ROOM (ABANDON UNDERGROUND CONDUIT IN PLACE).



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY:

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

r PLANT PLAN WATER TREATMENT ELECTRICAL SITE I

PROJECT No O0130014

E-10-101

SHEET 051 OF 088 SHEETS




DEMOLITION KEYNOTES

- 1. REMOVE EXISTING 5 KV SERVICE LATERAL CABLES FROM XFMR-3A WEST TO 2.4 KV SWITCHGEAR (ABANDON UNDERGROUND DUCTBANK IN PLACE). SEE DRAWING E-10-203 FOR CONTINUATION.
- 2. REMOVE EXISTING 250 KW NATURAL GAS STANDBY GENERATOR. REMOVE EXISTING CONCRETE EQUIPMENT PAD. PATCH AND FINISH
- 3. REMOVE EXISTING SWITCHBOARD SB NO. 1. REMOVE EXISTING CONCRETE EQUIPMENT PAD. PATCH AND FINISH SURFACE TO MATCH
- 4. RETROFIT EXISTING AUTOMATIC TRANSFER SWITCH ATS-1. SEE NOTE
- 5. RETROFIT EXISTING AUTOMATIC TRANSFER SWITCH ATS-3 (LOCATED ABOVE ON PUMP ROOM MEZZANINE). SEE NOTE 3.
- 6. RETROFIT EXISTING AUTOMATIC TRANSFER SWITCH ATS-4 (LOCATED ABOVE ON PUMP ROOM MEZZANINE). SEE NOTE 3.
- 7. REMOVE EXISTING WE ENERGIES METERING SOCKET, CABINET, AND ASSOCIATED CONDUIT/WIRE.
- 8. RETROFIT <u>2.4 KV SWITCHGEAR</u> (SEE DRAWING E-10-701 FOR REQUIRED MODIFICATIONS).
- 9. REMOVE EXISTING CONDUITS AND FEEDER CONDUCTORS FROM SB NO. 1 TO ATS-1, ATS-3, AND ATS-4.
- 10. REPLACE EXISTING TRANSFORMER $\underline{\mathsf{XFMR}} = 3\mathsf{A} \underline{\mathsf{WEST}}$ AND CONCRETE PAD.
- 11. REPLACE EXISTING 25KV CABLES FEEDING <u>XFMR—3A WEST</u> (EXISTING UNDERGROUND CONDUITS SHALL REMAIN AND BE EXTENDED AS REQUIRED).

KEYNOTES

- 1. EXISTING OUTDOOR 24.9 KV SWITCHGEAR TO REMAIN.
- 2. EXISTING UNDERGROUND 25KV FEED TO XFMR-3A EAST TO REMAIN.
- 3. EXISTING TRANSFORMER XFMR-3B EAST TO REMAIN.
- 4. EXISTING UNDERGROUND DUCTBANK WITH 5 KV SERVICE LATERAL CABLES FROM XFMR-3B EAST TO 2.4 KV SWITCHGEAR TO REMAIN. SEE DRAWING E-10-203 FOR CONTINUATION.
- 5. EXISTING WE ENERGIES METERING CABINET TO REMAIN.
- 6. EXISTING UNIT SUBSTATION USS NO. 1 AND 2 TO REMAIN (LOCATED ABOVE ON PUMP ROOM MEZZANINE).
- 7. EXISTING TRANSFORMER XFMR-1 (NORTH) TO REMAIN (LOCATED ABOVE ON PUMP ROOM MEZZANINE).
- 8. EXISTING TRANSFORMER XFMR-2 (SOUTH) TO REMAIN (LOCATED ABOVE ON PUMP ROOM MEZZANINE).
- 9. EXISTING MOTOR CONTROL CENTER MCC-2 TO REMAIN.
- 10. EXISTING MOTOR CONTROL CENTER $\underline{\mathsf{MCC-1}}$ TO REMAIN.
- 11. EXISTING HIGH LIFT PUMP TO REMAIN.
- 12. FUTURE HIGH LIFT PUMP.
- 13. EXISTING BACKWASH PUMP TO REMAIN.
- 14. EXISTING CHAIN LINK FENCE TO REMAIN.
- 15. EXISTING BARE COPPER GROUND GRID WITH GROUND RODS.





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY: NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY

SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

DEMOUNT TITLE
ADMINISTRATION AND
FILTRATION FACILITY
FIRST FLOOR
ELECTRICAL
DEMOLITION PLAN

O0130014

E-10-201 SHEET 052 OF 088 SHEETS


- SEE DRAWING E-00-101 FOR ELECTRICAL GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. ALL EQUIPMENT SHOWN ON THIS SHEET IS EXISTING AND TO REMAIN AS CURRENTLY INSTALLED, UNLESS OTHERWISE NOTED.
- 3. SEE DRAWING E-10-401 FOR WORK REQUIRED TO REPLACE 208 VOLT FEEDER CONDUCTORS FROM PANEL PA TO D-LEFT, C, AND H.
- SEE DRAWING E-10-402 FOR WORK ASSOCIATED WITH RELOCATED OR REPLACED EQUIPMENT.

KEYNOTES

- 1. EXISTING MOTOR CONTROL CENTER MCC-4 TO REMAIN.
- 2. EXISTING 208Y/120V PANEL E TO REMAIN.
- 3. EXISTING TRANSFORMER XFMR-T4A TO REMAIN.
- 4. EXISTING 208Y/120V PANEL $\underline{\mathsf{B-LEFT}}$ TO REMAIN AND BE REFED.
- 5. EXISTING 208Y/120V PANEL B-RIGHT TO REMAIN
- 6. EXISTING 240/120V PANEL \underline{Z} AND TRANSFORMER $\underline{XFMR-T4B}$ TO
- 7. EXISTING 480V FEEDER FROM USS NO. 1 AND PULLBOX TO REMAIN.
- 8. EXISTING TEMPERATURE CONTROL PANEL TO REMAIN.
- 9. EXISTING 480Y/277V PANEL AA TO REMAIN.
- 10. EXISTING 480Y/277V PANEL EE TO REMAIN.

DEMOLITION KEYNOTES

- 1. RELOCATE EXISTING AUTOCON METER PIT PANEL. SEE DRAWING E-30-205 FOR DETAILS.
- 2. REPLACE EXISTING 208Y/120V PANEL PA.
- 3. RELOCATE EXISTING BYPASS ISOLATION SWITCH.
- 4. RELOCATE EXISTING TRANSFORMER XFMR-T4.
- 5. RELOCATE EXISTING READER MODULE FOR NORTH GATE CARD READER. REMOVE EXISTING WALL BOX.
- 6. RELOCATE EXISTING AIR COMPRESSOR AND COMBINATION STARTERS.
- 7. REMOVE ELECTRICAL CONNECTED TO EXISTING BOILER AND CONTROL
- REPLACE EXISTING JUNCTION BOX, CONDUIT, AND CONTROL WIRING FOR NORTH GATE CONTROLLER.
- 9. REMOVE EXISTING 4' FLUORESCENT LIGHT FIXTURE.
- 10. REMOVE EXISTING DUPLEX RECEPTACLE.
- 11. RELOCATE EXISTING PAGING SYSTEM HANDSET.
- 12. REMOVE EXISTING WELDER DISCONNECT SWITCH AND RECEPTACLE AND TURN OVER TO OWNER.
- 13. REMOVE ELECTRICAL CONNECTED TO EXISTING HEATING WATER PUMP.
- 14. REMOVE EXISTING INCANDESCENT LIGHT FIXTURE.
- 15. EXISTING TEMPERATURE CONTROL PANEL TO BE REPLACED. SEE DRAWING E-30-204 FOR DETAILS.
- 16. REPLACE EXISTING JUNCTION BOX, CONDUIT, AND POWER WIRING FOR NORTH GATE CONTROLLER.
- 17. REMOVE ELECTRICAL CONNECTED TO EXISTING GAS UNIT HEATER.
- 18. REPLACE EXISTING DOOR CONTACTS. RELOCATE EXISTING REQUEST-TO-EXIT DEVICE.
- 19. REMOVE EXISTING BREAK GLASS SWITCH.
- 20. REMOVE ELECTRICAL CONNECTED TO EXISTING MOTORIZED DAMPER.
- 21. REMOVE EXISTING HEAT DETECTOR.
- 22. REPLACE EXISTING 480 VOLT FEEDER FROM XFMR-T4 TO MCC-4.
- 23. REPLACE EXISTING 208 VOLT FEEDERS FROM XFMR-T4 AND XFMR-T4A TO BYPASS ISOLATION SWITCH.
- 24. REMOVE EXISTING CONDUIT AND 208 VOLT FEEDER FROM BYPASS ISOLATION SWITCH TO PANEL PA (ABANDON UNDERGROUND CONDUIT IN
- 25. REPLACE WALL MOUNTED INTERCOM SPEAKER.
- 26. REMOVE EXISTING MANUAL MOTOR STARTER FOR GAS UNIT HEATER.
- 27. REPLACE 1 1/2" AND 3/4" UNDERGROUND CONDUIT AND WIRE GOING TO NORTH GATE CONTRÓLLER.
- 28. REPLACE EXISTING UNDERGROUND CONDUITS AND CONTROL WIRES TO
- 29. REPLACE EXISTING CONDUIT WITH 9 LOW VOLTAGE CABLES FOR ACCESS CONTROL SYSTEM FROM DOWN LOW TO UP HIGH BY CEILING.
- 30. RELOCATE EXISTING AIR DRYER FOR AIR COMPRESSOR.
- 31. REMOVE EXISTING CONDUIT AND 208 VOLT FEEDER FROM PANEL PA TO C (ABANDON UNDERGROUND CONDUIT IN PLACE).





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER


DESIGNED BY: SEM DRAWN BY:

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF HIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY ENLARGED FIRST FLOOR ELECTRICAL DEMOLITION PLAN

O0130014



SEE DRAWING E-00-101 FOR ELECTRICAL GENERAL NOTES, LEGEND, AND ABBREVIATIONS.

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY LOWER LEVEL ELECTRICAL DEMOLITION PLAN

PROJECT No. O0130014

E-10-203


SHEET 054 OF 088 SHEETS

DEMOLITION KEYNOTES

- REMOVE 5 KV SERVICE LATERAL CABLES FROM XFMR-3A WEST TO 2.4 KV SWITCHGEAR. REMOVE EXISTING CONDUITS FROM POINT SHOWN TO EXTERIOR WALL (CAP CONDUITS AT WALL WITH WATERPROOF PLUG). SEE DRAWING E-10-201 FOR CONTINUATION.
- 2. REMOVE EXISTING 5 KV SERVICE LATERAL CABLES FROM XFMR-3A ${\underline{\sf WEST}}$ TO ${\underline{\sf 2.4}}$ KV ${\underline{\sf SWITCHGEAR}}$ (CONDUITS TO REMAIN AND BE REUSED).

∄ KEYNOTES

- 1. EXISTING CONDUITS WITH 5 KV SERVICE LATERAL CABLES FROM XFMR—3B EAST TO 2.4 KV SWITCHGEAR TO REMAIN. SEE DRAWING E-10-201 FOR CONTINUATION.
- 2. EXISTING PULLBOX TO REMAIN.
- 3. EXISTING CONDUITS WITH 5 KV SERVICE LATERAL CABLES FROM XFMR-3B EAST THRU FLOOR UP TO 2.4 KV SWITCHGEAR TO REMAIN.
- 4. EXISTING CONDUITS FEEDING THRU FLOOR UP TO 2.4 KV SWITCHGEAR
- 5. EXISTING MOTOR CONTROL CENTER $\underline{\mathsf{MCC-8}}$ TO REMAIN AND BE REFED. SEE DRAWING E-10-404 FOR NEW WORK.
- 6. EXISTING 2.4KV SWITCHGEAR (LOCATED ABOVE ON FIRST FLOOR).



- SEE DRAWING E-00-101 FOR ELECTRICAL GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. SEE DRAWING E-30-102 FOR LIGHT FIXTURE SCHEDULE.
- 3. SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF THE WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.
- 4. EMERGENCY LIGHTS BALLASTS SHALL BE WIRED WITH HOT LEG TO TURN LAMPS ON UPON LOSS OF POWER TO ROOM. EXIT SIGNS SHALL BE WIRED HOT AND UNSWITCHED.
- 5. GENERATOR SHALL BE MOVED TO THE EAST IN THE ELECTRICAL ROOM TO PROVIDE 36" CLEARANCE BETWEEN GENERATOR CONTROL PANEL AND OPENED DAMPER BLADES AND ACTUATOR. FINAL LOCATION SHALL BE DETERMINED IN THE FIELD.

KEYNOTES

- 1. EXISTING MOTOR CONTROL CENTER MCC-4.
- EXISTING 480Y/277V PANEL EE. REUSE EXISTING 20 AMP, 1 POLE CIRCUIT BREAKERS TO REFEED LIGHTS IN ELECTRICAL ROOM AND MECHANICAL ROOM. PROVIDE NEW CONDUIT AND WIRE TO FEED NEW LIGHTS.
- 3. NATURAL GAS STANDBY GENERATOR GEN-101.
- 4. AUTOMATIC TRANSFER SWITCH ATS-101.
- 5. RELOCATED REQUEST-TO-EXIT DEVICE.
- RELOCATED PAGING SYSTEM HANDSET. REPLACE EXISTING WIRING BACK TO AUDIO EQUIPMENT IN BCP-1 (EXTEND CONDUIT AS REQUIRED).
- 7. EXISTING 480Y/277V PANEL AA.
- 8. EXISTING 208Y/120V PANEL E.
- PROVIDE SURVEILLANCE CAMERA <u>70-C107A</u>. CAMERA SHALL BE AXIS #P1344 TO MATCH EXISTING CAMERAS. PROVIDE CAT 6 CABLE IN 3/4" CONDUIT FROM CAMERA TO EXISTING NETWORK SWITCH AND COMMUNICATION ENCLOSURE LOCATED IN CONTROL ROOM (SEE DRAWING E-10-402 FOR LOCATION).
- 10. PROVIDE WALL MOUNTED INTERCOM SPEAKER. SPEAKER SHALL BE TESSCO #SPC15T TO MATCH EXISTING SPEAKERS. RECONNECT TO EXISTING AUDIO CABLE.
- 11. PROVIDE TEMPERATURE SENSOR TIED TO PLC-H IN BCP-1 FOR MONITORING ROOM TEMPERATURE AND CONTROL OF EXHAUST FANS.
- 12. PROVIDE 18"x18"x4" HINGED COVER ENCLOSURE FOR RELOCATED READER MODULE FOR NORTH GATE CARD READERS AND DOOR 70-107A DEVICES. REPLACE EXISTING CONDUIT AND CONTROL WIRES LOCATED ON NORTH WALL WITH NEW.
- PROVIDE DIRECT BURIED CONDUITS WITH WIRE TO GATE OPENER, INTERCOM, AND CARD READERS (SEE DRAWINGS E-10-101 FOR CONTINUATION).
- 14. GEN-101 GENERATOR CONTROL PANEL.
- 15. REPLACE 3-WAY LIGHT SWITCH FOR ELECTRICAL ROOM LIGHTS.
- 16. BOILER <u>B-101</u>.





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

PartnersinDesign



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC


NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

ADMINISTRATION AND FILTRATION FACILITY
ENLARGED FIRST FLOOR LIGHTING AND SPECIAL SYSTEMS PLAN

PROJECT No. 00130014

DRAWING No.

E-10-301
SHEET 055 OF 088 SHEETS



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX: 217.373.8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER AND

DESIGNED BY: SEM DRAWN BY:

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS REVISION

> DMINISTRATION AND ILTRATION FACILITY IT FLOOR POWER PLAN ADI FIL⁻

O0130014


E-10-401

SHEET 056 OF 088 SHEETS



KEYNOTES (CONT.)

- 16. GEN-101 POWER TERMINATION BOX.
- 17. 4" CONCRETE EQUIPMENT PAD.
- 18. GEN-101 GENERATOR CONTROL PANEL.
- 19. EXISTING JUNCTION BOX AND CONDUIT FOR POWER TO FOUNTAIN.
- 20. PROVIDE UNDERGROUND CONCRETE ENCASED CONDUITS WITH 5KV CABLES.
- 21. NATURAL GAS STANDBY GENERATOR GEN-101.
- 22. ATS-101 AND WE ENERGIES METERING SECTION.
- 23. PROVIDE 1" PVC CONDUIT WITH 1#4/0 BARE COPPER GROUNDING ELECTRODE TO NEW REBAR IN CONCRETE.
- 24. PROVIDE 4" x 24" x 1/4" COPPER GROUND BAR (WALL MOUNT AT 24" AFF) FOR TERMINATING BUILDING GROUND. PROVIDE 1" UNDERGROUND CONDUIT WITH GROUNDING ELECTRODE CONDUCTOR TO <u>ATS</u>—101, EXISTING GROUND GRID OUTSIDE OF THE BUILDING. AND WATER PIPE.
- 25. PROVIDE METER CABINET AND SOCKET AS REQUIRED FOR WE ENERGIES METER (PROVIDE 1" CONDUIT WITH CONTROL WIRING TO METERING SECTION IN ATS—101 AS REQUIRED PER WE ENERGIES STANDARDS).
- 26. EXISTING 480 VOLT FEEDER FROM USS NO. 1 TO XFMR-T4.
- 27. USE EXISTING 120 VOLT CIRCUIT FEEDING EXISTING RECEPTACLES BEING REMOVED FOR NEW DUPLEX RECEPTACLE.
- 28. EXISTING TEMPERATURE CONTROL PANEL $\underline{\text{TC}-1}$ AND NEW TEMPERATURE CONTROL PANEL $\underline{\text{TC}-2}$. SEE DETAIL HV-10-201 FOR DETAILS.
- 29. EXISTING 30" RAW WATER PIPE.
- 30. CORE THRU LOWER LEVEL WALL AND PROVIDE WATERTIGHT SEAL AROUND CONDUITS.
- 31. REPLACE 480 VOLT FEEDER CONDUCTORS IN EXISTING UNDERGROUND CONDUIT FROM MCC-4 TO USS NO. 1 VIA ATS-1 ENCLOSURE.
- 32. PROVIDE OVERHEAD CONDUIT WITH 480 VOLT FEEDER CONDUCTORS FROM $\underline{\text{MCC-4}}$ TO $\underline{\text{XFMR-T4}}.$
- 33. PROVIDE OVERHEAD CONDUIT WITH 208 VOLT FEEDER CONDUCTORS FROM XFMR-T4 AND XFMR-T4A TO BYPASS ISOLATION SWITCH.
- 34. PROVIDE OVERHEAD CONDUIT WITH 208 VOLT FEEDER CONDUCTORS FROM BYPASS ISOLATION SWITCH TO PA.
- 35. PROVIDE OVERHEAD CONDUIT TO CONNECT TO EXISTING CONDUIT ABOVE DROP CEILING FOR 208 VOLT FEEDER CONDUCTORS FROM PANEL PA TO H.
- 36. PROVIDE OVERHEAD CONDUIT TO CONNECT TO EXISTING CONDUIT ABOVE DROP CEILING FOR 208 VOLT FEEDER CONDUCTORS FROM PANEL PA TO D-LEFT.
- 37. PROVIDE OVERHEAD CONDUIT WITH 208 VOLT FEEDER CONDUCTORS FROM PANEL \underline{PA} TO $\underline{B-LEFT}.$
- 38. PROVIDE OVERHEAD CONDUIT WITH 208 VOLT FEEDER CONDUCTORS FROM PANEL \underline{PA} TO \underline{C} . CORE EXISTING CMU WALL. SEE DRAWING E-10-403 FOR CONTINUATION.
- 39. GENERATOR REMOTE EMERGENCY STOP STATION.
- 40. GENERATOR BATTERY CHARGER
- 41. PROVIDE ELECTRICAL CONNECTION TO POTABLE WATER FLOW CONTROL VALVE.
- 42. PROVIDE ELECTRICAL CONNECTION TO GENERATOR HEAT EXCHANGER LOW COOLANT LEVEL SWITCH.
- 43. PROVIDE ELECTRICAL CONNECTION TO TEMPERATURE SENSOR FOR CONTROL OF EXHAUST FAN.
- 44. THERMOSTAT FOR GUH-101.
- 45. REMOTE GENERATOR ANNUNCIATOR PANEL





DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY: JBF


DATE CHECKED: 01/11


NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

ADMINISTRATION AND FILTRATION FACILITY ENLARGED FIRST FLOOR POWER PLAN

PROJECT No. 00130014

DRAWING No.





- SEE DRAWING E-00-101 FOR ELECTRICAL GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. SEE DRAWING E-10-601 AND E-10-602 FOR POWER ONE-LINE DIAGRAM.
- 3. SEE DRAWING E-30-101 FOR EQUIPMENT CONNECTION SCHEDULE.

KEYNOTES

- EXISTING CONDUITS WITH 5 KV SERVICE LATERAL CABLES FROM <u>XFMR-3B EAST</u> TO <u>2.4 KV SWITCHGEAR</u>. SEE DRAWING E-10-401 FOR CONTINUATION.
- 2. EXISTING PULLBOX.
- 3. EXISTING CONDUITS WITH 5 KV SERVICE LATERAL CABLES THRU FLOOR UP TO $\underline{\text{2.4}}$ KV SWITCHGEAR.
- 4. EXISTING <u>2.4 KV SWITCHGEAR</u> (LOCATED ABOVE ON FIRST FLOOR).
- EXISTING 4" CONDUITS WITH NEW 5 KV CABLES FEEDING THRU FLOOR UP TO 2.4 KV SWITCHGEAR.
- 6. SPLICE NEW 4" CONDUITS TO EXISTING 4" CONDUITS. PROVIDE 5 KV CABLES FROM <u>ATS-101</u> TO <u>2.4 KV SWITCHGEAR</u>.
- 7. PROVIDE (2) 4" CONDUITS WITH 5 KV CABLES FROM <u>2.4 KV SWITCHGEAR</u> TO <u>ATS-101</u>. CONDUITS SHALL BE MOUNTED AS CLOSE TO CEILING AS POSSIBLE AVOIDING EXISTING PROCESS PIPING.
- 8. CORE CONCRETE WALL FOR CONDUITS.
- 9. PROVIDE UNDERGROUND CONDUITS TO $\underline{\text{ATS}-101}$. SEE DRAWING E-10-402 FOR CONTINUATION.
- 10. REFEED EXISTING MOTOR CONTROL CENTER $\underline{\text{MCC}-8}$. SEE DRAWING E-10-703 FOR DETAILS.
- 11. REPLACE 480 VOLT FEEDER CONDUCTORS IN EXISTING CONDUIT FROM USS NO. 1 TO MCC-8. SEE DRAWING E-10-401 FOR CONTINUATION.
- 12. EXISTING HOIST BEAM (NEW CONDUITS SHALL BE LOCATED ABOVE BEAM).
- 13. PROVIDE 48"W x 48"L x 20"D PULLBOX WITH SCREW ON COVER LOCATED ON BOTTOM SIDE (MOUNT PULLBOX TIGHT TO CEILING AND HOLD OFF NORTH WALL 6"). CONDUITS SHALL CONNECT TO PULLBOX TO ALLOW PROPER BENDING RADIUS FOR NEW AND FUTURE 5 KV CARLES
- 14. LAYOUT PULLBOX FOR FUTURE INSTALLATION OF (3) 4" CONDUITS FOR 5 KV CABLES. SEE KENOTE 13.
- 15. PROVIDE 1" PVC CONDUIT WITH GROUNDING ELECTRODE CONDUCTOR TO EXISTING WATER PIPE.
- 16. PROVIDE DUPLEX RECEPTACLE FOR AIR DRYER (MOUNTED AT 48" AFF) AND FED FROM SPARE 20 AMP CIRCUIT BREAKER IN PANEL B-RIGHT ON UPPER LEVEL.
- 17. PROVIDE ELECTRICAL CONNECTION TO (2) RELOCATED COMBINATION STARTERS FOR AIR COMPRESSOR $\underline{\text{AC-}101}$ FROM UPPER LEVEL.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CFC


NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY LOWER LEVEL POWER PLAN

PROJECT No. 00130014

DRAWING



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER


DESIGNED BY: SEM DRAWN BY: CHECKED BY: DATE CHECKED:

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

PRETREATMENT FACILITY FIRST FLOOR POWER PLAN

PROJECT No. O0130014









DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

WATER TREATMENT PLANT POWER AND GROUNDING ONE-LINE DIAGRAMS

PROJECT No O0130014

			1			I	I				1
1A	2A	3A	4A	5A	6A	7A	8A	9A	10A	11A	
1B	2B		4B	1	6B	-	8B		10B	11B	

1 EXISTING 2.4KV SWITCHGEAR ELEVATION NO SCALE

	2.4KV SWITCHG	EAR SCHED	ULE
CUBICLE 1A 1B 2A 2B 3A 4A 4B 5A 6B 7A 8B 9A 10A 10B 11B	DESCRIPTION FEEDER NO. 1 METERING COMPARTMENT UNIT SUBSTATION NO. 1 (NORTH) FEEDER NO. 1 FEEDER NO. 2 METERING COMPARTMENT MCC-1 FEEDER NO. 2 WEPCO METERING COMPARTMENT INCOMING LINE NO. 1 METERING COMPARTMENT INCOMING LINE NO. 1 METERING COMPARTMENT INCOMING LINE NO. 1 AUXILIARY CUBICLE TIE COMPARTMENT TIE CIRCUIT BREAKER AUXILIARY CUBICLE INCOMING LINE NO. 2 METERING COMPARTMENT INCOMING LINE NO. 2 WEPCO METERING COMPARTMENT FEEDER NO. 3 METERING COMPARTMENT UNIT SUBSTATION NO. 2 (SOUTH) FEEDER NO. 4 METERING COMPARTMENT MCC-2 FEEDER NO. 4 MCC-2	MODIFICATIONS SEE NOTE 2 SEE NOTE 3	2.4KV SWITCHGEAR NOTES: 1. EXISTING 2.4 KV SWITCHGEAR IS A GE HORIZONTAL DRAW OUT METAL CLAD SWITCHGEAR, 2400 VOLT, 3 PHASE, 3 WIRE. SEE DRAWING E-10-601 FOR ADDITIONAL INFORMATION. 2. COORDINATE WITH WE ENERGIES ON REMOVAL OF EXISTING WE ENERGIES CTS/PTS. DISCONNECT AND REMOVE CONTROL WIRING FROM CTS/PTS TO REMOVE METER SOCKET (COORDINATE WORK WITH WE ENERGIES). REPLACE NAMEPLATE INDICATING "ABANDONED INCOMING LINE NO. 1 METERING COMPARTMENT". 3. DISCONNECT EXISTING 5 KV CABLES FROM XFMR—3A WEST AND CONNECT NEW 5 KV CABLES FROM ATS—101.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ADMINISTRATION AND FILTRATION FACILITY 2.4 KV SWITCHGEAR SCHEDULE AND ELEVATION

PROJECT No.

O0130014

E-10-701

SHEET 063 OF 088 SHEETS

7A 7В 2A 2B 2C 4B 5B 5C 7C 3B 2D 7D 5D 2E 3C 6C 7E 1D 8R 2F 3D 4C 5E 2G 3E 4D 5F 7G 8D 4" CONCRETE PAD CONCRETE FLOOR

MCC-4 SCHEDULE

MCC-4 ELEVATION

CUBICLE	DESCRIPTION	MODIFICATIONS	CUBICLE	DESCRIPTION	MODIFICATIONS
1A	SPACE	SEE NOTE 9	5A	SPACE	
1B	SPACE	SEE NOTE 10	5B	SPACE	
1C	SPACE	SEE NOTE 11	5C	PANEL EE MAIN CIRCUIT BREAKER	
1D	SPACE		5D	LIGHTING PANEL EE	
1E	NORMAL POWER TRANSFORMER T-4	SEE NOTE 2	5E	SPACE	
2A	CRANE DISCONNECT SWITCH K		5F	INCOMING LINE FROM GENERATOR TRANSFER SWITCH	SEE NOTE 5
2B	FOUNTAIN TRANSFORMER		6A	SPACE	
2C	SPACE		6B	LIGHTING PANEL E	
2D	KATHABAR HEAT CIRCULATING PUMP	SEE NOTE 12	6C	LIGHTING XFMR CIRCUIT BREAKER	
2E	M-92 PUMP NO. 3	SEE NOTE 3	6D	30KVA LIGHTING XFMR	
2F	SPARE STARTER		7A	M-93 AIR COMPRESSOR	SEE NOTE 6
2G	SPARE STARTER		7B	M-94 BOILER MOTOR	SEE NOTE 7
3A	M-70 RECLAIMED WATER PUMP NO. 1		7C	M-46 SUMP PUMP NO. 1	
3B	M-71 RECLAIMED WATER PUMP NO. 2		7D	M-91 PUMP NO. 2	SEE NOTE 8
3C	M-95 AXIVANE FAN NO. 1		7E	M-96 AXIVANE FAN NO. 2	
3D	SPACE		7F	SPACE	
3E	SPACE		7G	SPACE	
4A	PANEL AA MAIN CIRCUIT BREAKER		8A	MCC NO. 6 FEEDER BREAKER	
4B	PANEL AA		8B	SPACE	
4C	WELDER OUTLET	SEE NOTE 4	8C	SPACE	
4D	INCOMING LINE FROM CUBICLE 5F		8D	SPACE	

- MCC-4 NOTES:

 1. EXISTING MCC-4 IS AN ALLIS-CHALMERS MCC, 480 VOLT, 3 PHASE, 4 WIRE. SEE DRAWINGS E-10-601 AND E-10-602 FOR ADDITIONAL INFORMATION.
- 2. REPLACE 480 VOLT FEEDER TO XFMR-T4.
- 3. REUSE M-92 PUMP NO. 3 COMBINATION STARTER TO FEED <u>HWP-103</u>. REPLACE THERMAL OVERLOADS AS REQUIRED. REPLACE NAMEPLATE INDICATING "HEATING WATER
- 4. ABANDON EXISTING BREAKER FEEDING WELDER OUTLET IN PLACE. REPLACE LABEL INDICATING "SPARE".
- 5. REPLACE 480 VOLT FEEDER FROM <u>USS NO. 1</u> TO MAIN LUGS. PROVIDE TEMPORARY 480 VOLT FEED FROM USS NO. 1 DURING REPLACEMENT OF FEEDER. REPLACE NAMEPLATE INDICATING "INCOMING LINE FROM USS NO. 1".
- 6. ABANDON EXISTING BREAKER FEEDING M-93 AIR COMPRESSOR IN PLACE. REPLACE LABEL INDICATING "SPARE".
- 7. ABANDON EXISTING BREAKER FEEDING M-94 BOILER MOTOR IN PLACE. REPLACE LABEL INDICATING "SPARE".
- 8. REUSE M-91 PUMP NO. 2 COMBINATION STARTER TO FEED <u>HWP-102</u>. REPLACE THERMAL OVERLOADS AS REQUIRED. REPLACE NAMEPLATE INDICATING "HEATING WATER PUMP HWP-102".
- 9. PROVIDE SIZE 1 COMBINATION STARTER IN EXISTING SPACE FOR <u>EF-101</u>.
- 10. PROVIDE SIZE 1 COMBINATION STARTER IN EXISTING SPACE FOR EF-102.
- 11. PROVIDE SIZE 1 COMBINATION STARTER IN EXISTING SPACE FOR EF-103.
- 12. REUSE KATHABAR HEAT CIRCULATING PUMP COMBINATION STARTER TO FEED <u>HWP-101</u>. REPLACE THERMAL OVERLOAD AS REQUIRED. REPLACE NAMEPLATE INDICATING "HEATING WATER PUMP HWP-101 (KATHABAR)".



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC

SCALING ANY PORTION OF THIS DRAWING.


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

AND ELEVATION ADMINISTRATION AND FILTRATION FACILITY MCC-4 SCHEDULE

O0130014

E-10-702

SHEET 064 OF 088 SHEETS



FILTER #8 VALVES

FILTER #9 VALVES FILTER #10 VALVES SLUDGE PUMP #1 SOUTH SPARE STARTER SPARE STARTER FILTER TO WASTE #8 EAST FILTER #1 VALVES

FILTER #2 VALVES FILTER #3 VALVES

FILTER #4 VALVES

FILTER #5 VALVES

FILTER #6 VALVES SPARE BLANK


4B

4D 4E 4F 4G

GENERATOR BREAKER

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION ADMINISTRATION AND FILTRATION FACILITY ATS-101 AND MCC-8 SCHEDULE AND ELEVATION PROJECT No. O0130014

E-10-703 SHEET 065 OF 088 SHEETS



DEMOLITION KEYNOTES

- REPLACE EXISTING MCC-2 AND MCC-3. CUT OFF ALL UNDERGROUND CONDUITS AT FLOOR. REMOVE (2) BUCKETS FROM MCC AND TURN OVER TO OWNER.
- 2. REPLACE EXISTING 208Y/120V PANEL A.
- REMOVE EXISTING NATURAL GAS STANDBY GENERATOR.
- 4. REPLACE ELECTRICAL CONNECTED TO EXISTING AIR COMPRESSOR.
- 5. REMOVE EXISTING INCANDESCENT LIGHT FIXTURE.
- 6. REMOVE EXISTING 4' FLUORESCENT LIGHT FIXTURE.
- 7. REPLACE EXISTING 480 VOLT SERVICE LATERAL CABLES FROM <u>XFMR-1B</u> (EXISTING UNDERGROUND CONDUITS TO REMAIN).
- 8. REMOVE EXISTING LIGHT SWITCH.
- 9. REMOVE ELECTRICAL CONNECTED TO EXISTING GAS UNIT HEATER.
- 10. REMOVE ELECTRICAL CONNECTED TO EXISTING MOTORIZED DAMPER.
- 11. REMOVE EXISTING CONTROL STATION.
- 12. REMOVE ELECTRICAL CONNECTED TO EXISTING EDUCTOR PUMP.
- 13. REMOVE EXISTING PULLBOX LOCATED BELOW MSWB-1B.
- 14. REMOVE ELECTRICAL CONNECTED TO EXISTING MIX TANK AGITATOR.
- 15. REMOVE ELECTRICAL CONNECTED TO EXISTING RAW WATER SUPPLY BOOSTER PUMP.
- 16. REMOVE ELECTRICAL CONNECTED TO EXISTING CHEMICAL METERING PUMP.

- 17. REMOVE ELECTRICAL CONNECTED TO ABANDONED SOLENOID VALVE.
- 18. REMOVE EXISTING DUPLEX RECEPTACLE.
- REMOVE ELECTRICAL CONNECTED TO EXISTING EXHAUST FAN NO. 6 (LOCATED ABOVE CHEMICAL ROOM).
- 20. REMOVE EXISTING CHLORINE DETECTOR PANEL.
- 21. REMOVE EXISTING GENERATOR ATS.
- 22. REPLACE EXISTING (3) LIGHTING CONTACTORS FOR OUTSIDE LIGHTS, INSIDE NORTH LIGHTS, INSIDE SOUTH LIGHTS
- 23. REMOVE EXISTING 4' FLUORESCENT LIGHT FIXTURE (LOCATED ABOVE MEZZANINE).
- 24. RELOCATE EXISTING DOOR CONTACT, ELECTRIC STRIKE, AND REQUEST—TO—EXIT DEVICE.
- 25. REMOVE EXISTING DOOR CONTACT AND REQUEST—TO—EXIT DEVICE.
- 26. RELOCATE EXISTING 4' FLUORESCENT LIGHT FIXTURE (LOCATED ABOVE MEZZANINE).
- 27. REPLACE EXISTING <u>PLC-G ENCLOSURE</u>. REMOVE STEEL TROUGH BELOW ENCLOSURE AND CUT OFF CONDUITS AT FLOOR. REPLACE LOW TEMPERATURE SENSOR MOUNTED ON ENCLOSURE. REMOVE PLC AND TURN OVER TO OWNER.
- 28. RELOCATE EXISTING CARD READER.
- 29. REPLACE EXISTING LOCAL CONTROL STATION.
- 30. RELOCATE EXISTING HID LIGHT FIXTURE.
- 31. REMOVE EXISTING SUMP PIT FLOAT.
- 32. REPLACE EXISTING HIGH TEMPERATURE SENSOR
- 33. REPLACE EXISTING LOW TEMPERATURE SENSOR.

(#) KEYNOTES

- 1. EXISTING LOW LIFT PUMP TO REMAIN.
- 2. EXISTING LOW LIFT PUMP NO. 7 VFD (LOCATED ABOVE ON MEZZANINE) TO REMAIN.
- EXISTING 480 VOLT SERVICE LATERAL CABLES IN UNDERGROUND CONDUITS FROM XFMR-1A TO REMAIN.
- 4. EXISTING TRANSFORMER XFMR-1A TO REMAIN.
- 5. EXISTING TRANSFORMER XFMR-1B TO REMAIN.
- 6. EXISTING PULLBOX LOCATED BELOW <u>MSWB-1A</u> TO REMAIN.
- 7. EXISTING HORIZONTAL SHAFT NATURAL GAS PUMP AND CONTROL PANEL TO REMAIN.
- 8. EXISTING PULLBOX LOCATED BELOW MCC-1A AND MCC-1B TO REMAIN.
- 9. EXISTING MAIN SWITCHBOARD <u>MSWB-1A</u> (LOCATED ABOVE ON MEZZANINE) TO REMAIN.
- 10. REFEED EXISTING MAIN SWITCHBOARD <u>MSWB-1B</u> (LOCATED ABOVE ON MEZZANINE).

- 11. EXISTING MOTOR CONTROL CENTER $\underline{\text{MCC}-1A}$ (LOCATED ABOVE ON MEZZANINE) TO REMAIN.
- 12. EXISTING MOTOR CONTROL CENTER MCC-1B (LOCATED ABOVE ON MEZZANINE) TO REMAIN.
- 13. EXISTING LOW LIFT PUMP NO. 2 VFD (LOCATED ABOVE ON MEZZANINE) TO REMAIN.
- 14. EXISTING HORIZONTAL SHAFT NATURAL GAS PUMP AUTOMATIC CONTROL PANEL AND 3 PHASE UNDERVOLTAGE MONITOR TO REMAIN.
- 15. EXISTING SURVEILLANCE CAMERA TO REMAIN.
- 16. EXISTING JUNCTION BOX WITH READER MODULE FOR ACCESS CONTROL TO REMAIN.
- 17. EXISTING NETWORK SWITCH AND COMMUNICATION ENCLOSURE.
- 18. EXISTING TELEPHONE CABINET.
- 19. EXISTING ACCESS CONTROL NETWORK CONTROLLER $\underline{\text{NC-5}}$ AND POWER SUPPLY $\underline{\text{PS-5}}$.
- 20. EXISTING WALL MOUNTED INTERCOM SPEAKER TO REMAIN.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY: JRF CHECKED BY: CEC

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


> LOW LIFT PUMP STATION FIRST FLOOR ELECTRICAL DEMOLITION PLAN

> > PROJECT No. 00130014

DRAWING No.

E-20-201

SHEET 066 OF 088 SHEETS



∄ KEYNOTES

- 1. EXISTING SURVEILLANCE CAMERA.
- RELOCATED DOOR CONTACT, ELECTRIC STRIKE, AND REQUEST—TO—EXIT DEVICE.
- 3. RELOCATED HID LIGHT FIXTURE. CORE HOLE THRU EXISTING CONCRETE WALL TO REFEED LIGHT FIXTURE.
- RELOCATED 4' FLUORESCENT LIGHT FIXTURE (LOCATED UP HIGH ABOVE MEZZANINE).
- 5. EXISTING 4' FLUORESCENT LIGHT FIXTURE (LOCATED UP HIGH BY CEILING).
- 6. EXISTING MAIN SWITCHBOARD $\underline{\mathsf{MSWB-1A}}$ (LOCATED ABOVE ON MEZZANINE).
- 7. EXISTING MAIN SWITCHBOARD MSWB-1B (LOCATED ABOVE ON MEZZANINE).
- EXISTING MOTOR CONTROL CENTER MCC-1A (LOCATED ABOVE ON MEZZANINE).
- 9. EXISTING MOTOR CONTROL CENTER $\underline{\mathsf{MCC}{-1B}}$ (LOCATED ABOVE ON MEZZANINE).
- 10. EXISTING LOW LIFT PUMP NO. 2 VFD (LOCATED ABOVE ON MEZZANINE).
- 11. EXISTING LOW LIFT PUMP NO. 7 VFD (LOCATED ABOVE ON MEZZANINE).
- 12. AUTOMATIC TRANSFER SWITCH ATS-102 (LOCATED ABOVE ON MEZZANINE).
- 13. MOTOR CONTROL CENTER MCC-2 (LOCATED ABOVE ON MEZZANINE).
- 14. 208Y/120V PANEL A (LOCATED ABOVE ON MEZZANINE).
- 15. PROVIDE ENCLOSURE WITH (3) 20 AMP, 3 POLE LIGHTING CONTACTORS FOR OUTSIDE LIGHTS, INSIDE NORTH LIGHTS, INSIDE SOUTH LIGHTS.
- 16. NATURAL GAS STANDBY GENERATOR GEN-102.
- 17. EXISTING LIGHT SWITCHES. REWIRE TO NEW LIGHTING CONTACTORS.
- 18. PROVIDE TEMPERATURE SENSOR TIED TO <u>PLC-G</u> FOR MONITORING ROOM TEMPERATURE AND CONTROL OF VFD-105.
- 19. EXISTING (2) LIGHT SWITCHES FOR CHEMICAL ROOM LIGHTS AND CEILING FAN.
- 20. EXISTING JUNCTION BOX WITH READER MODULE FOR ACCESS CONTROL.
- 21. RELOCATED CARD READER.
- 22. EXISTING ACCESS CONTROL NETWORK CONTROLLER $\underline{\text{NC-5}}$ AND POWER SUPPLY PS-5.
- 23. EXISTING TELEPHONE CABINET.
- 24. EXISTING NETWORK SWITCH AND COMMUNICATION ENCLOSURE.
- 25. <u>PLC-G ENCLOSURE</u>. PROVIDE DATA OUTLET IN ENCLOSURE WITH CAT 6 CABLE IN 3/4" CONDUIT TO EXISTING NETWORK SWITCH AND COMMUNICATION ENCLOSURE.
- 26. EXISTING WALL MOUNTED INTERCOM SPEAKER.
- 27. LIGHT FIXTURE SHALL BE CONTROLLED FROM "INSIDE SOUTH LIGHTS" LIGHTING CONTACTOR.
- 28. EXISTING LIGHT SWITCH FEEDING HOSE REEL LIGHT.
- 29. EXISTING RADIONICS ALARM PANEL.
- 30. PROVIDE TEMPERATURE SENSOR TIED TO $\underline{\text{PLC}}-\underline{\text{G}}$ FOR MONITORING ROOM TEMPERATURE.
- 31. PROVIDE TYPE A1 LIGHT FIXTURE ABOVE GENERATOR ROOM CEILING (PENDANT MOUNT AS HIGH AS POSSIBLE).
- 32. PROVIDE LIGHT SWITCH FOR A1 LIGHT FIXTURES LOCATED ABOVE GENERATOR ROOM CEILING.
- 33. REPLACE EXISTING EMERGENCY LIGHT WITH NEW D2 LIGHT FIXTURE.
- 34. PROVIDE D2 LIGHT FIXTURE MOUNTED TO FACE OF EXISTING CONCRETE BEAM LOCATED ABOVE MEZZANINE (WIRE TO UNSWITCHED HOT WIRE FEEDING LIGHTS ON MEZZANINE).



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY: JRF CHECKED BY: CEC

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


LOW LIFT PUMP STATION FIRST FLOOR LIGHTING AND SPECIAL SYSTEMS PLAN

PROJECT No. 00130014

0010001

E-20-301

SHEET 067 OF 088 SHEETS



- 1. NATURAL GAS STANDBY GENERATOR GEN-102.
- 4. EXISTING TRANSFORMER XFMR-1B (LOCATED ABOVE ON ELECTRICAL PLATFORM AREA). DISCONNECT EXISTING AND RECONNECT NEW SERVICE LATERAL
- 5. EXISTING TRANSFORMER XFMR-1A (LOCATED ABOVE
- 6. REPLACE EXISTING 480 VOLT SERVICE LATERAL CABLES FROM XFMR-1B IN EXISTING UNDERGROUND
- EXISTING UNDERGROUND CONDUITS WITH 480 VOLT SERVICE LATERAL CABLES TO MSWB-1A.
- 8. EXISTING PULLBOX WITH 480 VOLT FEEDER CABLES.
- 9. EXISTING PULLBOX WITH 480 VOLT SERVICE LATERAL
- 10. EXISTING MSWB-1A AND MSWB-1B (LOCATED ABOVE
- 11. ATS-102 (LOCATED ABOVE ON MEZZANINE).
- 12. MCC-2 (LOCATED ABOVE ON MEZZANINE).
- 13. EXISTING MCC-1A AND MCC-1B (LOCATED ABOVE
- 14. EXISTING LOW LIFT PUMP NO. 7 VFD (LOCATED
- 15. EXISTING LOW LIFT PUMP NO. 2 VFD (LOCATED
- 16. PROVIDE CONDUITS WITH 480 VOLT SERVICE LATERAL CABLES FROM XFMR-1B TO ATS-102. MOUNT CONDUITS UP HIGH BELOW MEZZANINE
- 17. CONCRETE ENCASEMENT FOR CONDUITS WITH 480 VOLT SERVICE LATERAL CARLES FROM EXISTING FLOOR TO MEZZANINE STRUCTURE. SEE DRAWING
- 18. PROVIDE PLC-G ENCLOSURE.
- 19. PROVIDE CONDUIT AND WIRE TO FEED RELOCATED
- 20. REPLACE WIRING FOR 480 VOLT POWER FEED TO EXISTING EQUIPMENT (REUSE EXISTING CONDUIT AND
- 21. REPLACE CONTROL WIRING FOR EXISTING EQUIPMENT (REUSE EXISTING CONDUIT AND EXTEND AS
- 22. REPLACE LOCAL CONTROL STATION HS-RWP-101, CONDUIT, AND CONTROL WIRING FOR RWP-101.
- 23. REPLACE LOCAL CONTROL STATION HS-SWP-102, CONDUIT, AND CONTROL WIRING FOR SWP-102.

- 24. EXISTING HORIZONTAL SHAFT NATURAL GAS PUMP AUTOMATIC CONTROL PANEL AND 3 PHASE UNDERVOLTAGE MONITOR. REPLACE CONTROL WIRING TO CONTROL PANEL (REUSE EXISTING CONDUIT AND EXTEND AS REQUIRED)
- 25. EXISTING HORIZONTAL SHAFT NATURAL GAS PUMP AND CONTROL PANEL.
- 26. REPLACE WIRING FOR 480 VOLT POWER FEED TO TRAVELING SCREEN SC-102 CONTROL PANEL (REUSE EXISTING CONDUIT AND EXTEND AS PROVIDE CONDUIT AND CONTROL REQUIRED) WIRING TO PLC-G.
- 27. PROVIDE 12"x12"x4" NEMA 4X JUNCTION BOX WITH INSULATED TERMINAL STRIPS FOR CONNECTION TO CARBON FEEDER CF-101 (MOUNT JUNCTION BOX AT 24" ABOVE GRADE). PROVIDE REMOVABLE KNOCKOUT ON BOTTOM OF ENCLOSURE FOR CONNECTION OF SEALTIGHT CONDUIT TO CF-101.
- 28. EXISTING WATER LEVEL DIFFERENTIAL CONTROLLER.
- 29. PROVIDE 120 VOLT DUPLEX RECEPTACLE FOR WIT-4006 (MOUNT AT 48" AFF)
- 30. PROVIDE LOCAL CONTROL STATION HS-WWP-101, CONDUIT, AND CONTROL WIRING FOR WWP-101.
- 31. REPLACE ANALOG CONTROL WIRING FROM EXISTING SHORE WELL BEFORE SCREEN LEVEL TRANSMITTER RAW WATER TEMPERATURE SENSOR TO PLC-G VIA SC-102 CONTROL PANEL (REUSE EXISTING CONDUIT AND EXTEND AS REQUIRED).
- 32. EXISTING LOW LIFT PUMP.
- 33. FUTURE LOW LIFT PUMP.
- 34. THERMOSTAT FOR GUH-102.
- 35. PROVIDE NEW OVERHEAD CONDUIT WITH WIRES TO REFEED EQUIPMENT (ABANDON EXISTING UNDERGROUND CONDUIT IN PLACE).
- 36. REPLACE LOCAL CONTROL STATION, CONDUIT, AND CONTROL WIRING FOR SC-102.
- 37. REPLACE ANALOG CONTROL WIRING FROM EXISTING RAW WATER TEMPERATURE SENSOR TO PLC-G.
- 38. REPLACE ANALOG CONTROL WIRING FROM EXISTING SHORE WELL AFTER SCREEN LEVEL TRANSMITTER TO PLC-G VIA SC-102 CONTROL PANEL (REUSE EXISTING CONDUIT AND EXTEND AS REQUIRED).
- 39. PROVIDE 120 VOLT DUPLEX RECEPTACLE (CONNECT TO EXISTING RECEPTACLE BRANCH CIRCUIT).
- 40. EXISTING SPRAY WATER SWP-102 SOLENOID VALVE.
- 41. GENERATOR BATTERY CHARGER.
- 42. GENERATOR REMOTE EMERGENCY STOP STATION.
- 43. THERMOSTAT FOR GUH-103 AND GUH-104.
- 44. REMOTE GENERATOR ANNUNCIATOR PANEL.
- 45. PROVIDE TEMPORARY 200 AMP, 3 POLE FUSIBLE DISCONNECT SWITCH FOR EXISTING NATURAL GAS GENERATOR. PROVIDE TEMPORARY CABLES AND TERMINATE ON EXISTING GENERATOR AND MCC-2 THAT WILL BE USED ONLY IF POWER IS LOST DURING CONSTRUCTION.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX · 217 373 8923





WATER and SEWER UTILITY

TER TREATMENT PLANT LOW LIFT PUMP STATION STANDBY POWER AND

DESIGNED BY: SEM RAWN BY CHECKED BY:

NOTE: DIMENSIONAL DATA SCALING ANY PORTION OF THIS DRAWING


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS REVISION

STATION SOR LAN LIFT PUMP S FIRST FLOC POWER PLA LΟW

> PROJECT No O0130014

E-20-401

SHEET 068 OF 088 SHEETS



- SEE DRAWING E-00-101 FOR ELECTRICAL GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. SEE DRAWING E-30-101 FOR EQUIPMENT CONNECTION SCHEDULE.
- 3. SEE DRAWING E-20-601 FOR POWER ONE-LINE DIAGRAM.
- 4. SEE DRAWING E-20-701 FOR PANEL A SCHEDULE AND MCC-2 SCHEDULE.
- SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF THE WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.

KEYNOTES

- 1. EXISTING MAIN SWITCHBOARD MSWB-1A.
- 2. REFEED EXISTING MAIN SWITCHBOARD MSWB-1B.
- 3. EXISTING MOTOR CONTROL CENTER MCC-1A.
- 4. EXISTING MOTOR CONTROL CENTER $\underline{MCC-1B}$.
- 5. EXISTING LOW LIFT PUMP NO. 2 VFD.
- 6. EXISTING LOW LIFT PUMP NO. 7 VFD.
- 7. AUTOMATIC TRANSFER SWITCH ATS-102.
- 8. MOTOR CONTROL CENTER MCC-2.
- 9. REPLACE EXISTING 480 VOLT SERVICE LATERAL CABLES FROM XFMR-1B IN EXISTING UNDERGROUND CONDUITS.
- 10. EXISTING UNDERGROUND CONDUITS WITH 480 VOLT SERVICE LATERAL CABLES FROM XFMR-1A TO MSWB-1A.
- 11. PROVIDE 24"W x 48"L x 24"D PULLBOX WITH SCREW ON COVER LOCATED ON SIDE (MOUNT UP HIGH BY CEILING).
- 12. EXISTING PULLBOX (LOCATED BELOW MSWB-1A).
- 13. 208Y/120V PANEL A.
- 14. EXISTING MEZZANINE.
- PROVIDE CONDUITS WITH 480 VOLT FEEDER CABLES AND CONTROL WIRING FROM MAIN CIRCUIT BREAKER AND CONTROL PANEL ON GEN-102 TO ATS-102.
- NATURAL GAS STANDBY GENERATOR GEN-102 (LOCATED BELOW IN GENERATOR ROOM).
- 17. PROVIDE CONDUITS WITH 480 VOLT FEEDER CABLES FROM $\underline{\text{MSWB-1B}}$ TO $\underline{\text{MCC-2}}.$
- 18. EXISTING PULLBOX (LOCATED BELOW <u>MSWB-1A</u>, <u>MCC-1A</u>, AND <u>MCC-1B</u>) FOR 480 VOLT FEEDER CABLES.
- 19. EXISTING TRANSFORMER XFMR-1A.
- 20. EXISTING TRANSFORMER XFMR-1B.
- 21. CORE CONCRETE CEILING AND EXTEND CONDUITS DOWN TO <u>GEN-102</u> MAIN CIRCUIT BREAKER (LOCATED BELOW IN GENERATOR ROOM).
- 22. MEZZANINE EXTENSION AND RELOCATED STAIRS.
- 23. REPLACE WIRING FOR POWER FEED TO EXISTING EQUIPMENT (REUSE EXISTING CONDUIT AND EXTEND AS REQUIRED).
- 24. REPLACE CONTROL WIRING FOR EXISTING EQUIPMENT (REUSE EXISTING CONDUIT AND EXTEND AS REQUIRED).
- 25. PROVIDE CONDUITS WITH 480 VOLT FEEDER CABLES FROM $\underline{\text{ATS}-102}$ TO $\underline{\text{MSWB}-1B}$ MAIN BREAKER.
- 26. PROVIDE 120 VOLT DUPLEX RECEPTACLE MOUNTED 12" ABOVE MEZZANINE (CONNECT TO EXISTING RECEPTACLE BRANCH CIRCUIT).
- 27. PROVIDE ELECTRICAL CONNECTION TO POTABLE WATER FLOW CONTROL VALVE.
- 28. PROVIDE ELECTRICAL CONNECTION TO GENERATOR HEAT EXCHANGER LOW COOLANT LEVEL SWITCH.
- 29. EXISTING GROUND GRID.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN RY: JRF


NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


LOW LIFT PUMP STATION MEZZANINE POWER PLAN

PROJECT No. 00130014

..........

E-20-402





- 1. EXISTING BOND TO GROUND GRID WITH EXOTHERMIC WELD.
- 2. EXISTING BOND TO BUILDING STEEL COLUMN WITH EXOTHERMIC WELD.
- 3. EXISTING BOND TO RAW WATER PIPE WITH GROUND CLAMP.
- 4. EQUIPMENT GROUND CONDUCTOR INSTALLED IN CONDUIT WITH PHASE CONDUCTORS.
- 5. EQUIPMENT GROUND CONDUCTOR INSTALLED IN CONDUIT WITH FEEDER CIRCUIT.
- 6. EXISTING NEUTRAL CONDUCTOR INSTALLED IN CONDUIT WITH PHASE CONDUCTORS.
- 7. EXISTING CONCENTRIC NEUTRAL ON MEDIUM VOLTAGE CABLE.
- 8. NEUTRAL CONDUCTOR INSTALLED IN CONDUIT WITH PHASE CONDUCTORS.

Partners in Design

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/1

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

LOW LIFT PUMP STATION GROUNDING ONE-LINE DIAGRAM

PROJECT No

O0130014

E-20-602 SHEET 071 OF 088 SHEETS

NB - NEUTRAL BUS NW - NEUTRAL WINDING ON TRANSFORMER

ENC - ENCLOSURE EBJ - ENCLOSURE BONDING JUMPER

ABBREVIATIONS

GB - GROUND BUS

SEE SPECIFICATION 01 10 00 FOR A DESCRIPTION OF THE WORK REQUIRED FOR OWNER SUPPLIED PRODUCTS AND WORK SEQUENCE.


			MC	C-2	S	CHED	ULE	-						
PANEL: LOCATION FED FROM INCIDEN		DEVICE FAMILY: 1	Breaker Bolt On	ENCLOS MOUNTI VOLTAG BOUNDA	NG: F E:	NEMA 1 Tree Star 480/277 00(mm)		MAINS WIRIN	IG:	3-P] Phase 4-Wire		CONTINUOUS(A): AIC RATING(A): FAULT CURRENT(A)	600 42000 40067
ND	DESCRIPTION	NOTES	HP	Ma× FLA	OC I	DEVICE AMPS F	SIZE	START		AC	FEEDER/RACE	WAY		
1AL 1AR 1BL 1BL 1D 1C 1D 1E 2A 2C 2D 2C 2D 3A 3A 4B 4C 4D 4EL 4ER	AIR CUMPRESSUR AC-102 SPARE PUMP ROUM HOIST H-101 SCREEN HOIST H-102 SCREEN SC-102 EXHAUST FAN EF-106 WW PUMP WWP-101 POWER FAILURE CONTROL RW SUPPLY PUMP P-4004 EDUCTOR PUMP P-4003 TANK AGITATOR M-4007 RW SAMPLE PUMP RWP-101 SW PUMP SWP-102 PANEL A XFMR-3 MAIN LUGS SCREEN SC-101 EXHAUST FAN EF-105 SPACE XFMR-3 BREAKER SPARE	SEE NOTE 1 SEE NOTE 3 SEE NOTE 4	3 1. 5 2 0 7. 5 5 0 3 3 2 1 15	4. 8 3 3. 4 11 7. 6 4. 8 4. 8 3. 4 2. 1 21 44. 99 0. 001 1. 6	RRRBKKRPPMCCPMCCPMCCPMCCPMCCPMCCPMCCPMCCPMCCPM	15 15 15 15 15 20 15 15 15 15 15 20 25 25	8	FVNR FVNR FVNR FVNR FVNR FVNR FVNR FVNR						
ALL CONI TOTAL CI TOTAL DI TOTAL DI	DNNECTED 96, 88 EMAND 96, 88	AX PH AMPS 121. 0 121. 0 133. 7	* PHASE * A-N * B-N * C-N		33525. 31336. 32057.	1 1	AMPS .21. 0 .13. 1 .15. 7		CDN DEN	S TO NNEC MAND SIGN	TED 96.	KVA 88 88 00		


- NOTES:


 1. PROVIDE RELAYS AS REQUIRED TO MATCH EXISTING INTERFACE TO HORIZONTAL SHAFT NATURAL GAS PUMP CONTROL PANEL RELAYS.

 2. PROVIDE 2 SETS OF LUGS FOR MAIN LUGS, ONE THAT CAN BE USED FOR PERMANENT WIRING AND OTHER TO BE USED FOR TEMPORARY WIRING FROM 75 KW NATURAL GAS GENERATOR DURING CONSTRUCTION.
- 3. PROVIDE PHASE LOSS RELAY.
- 4. PROVIDE 2 SPEED, 2 WINDING STARTER.

				PAN	EL A	A SC	HEDI	JLE				
FED	EL: A ATION: MCC-2 FROM: XFMR-3 SEC IDENT ENERGY: 0.00 J/c	DC DEVIO		aker t On	ENCLOSI MOUNTIN VOLTAGE BOUNDAR	NG: Flu	08/120	WIF	INS(A): 150A BI RING: 3-Phase Category:	KR e 4-Wire	AIC RATING(A): 10	225 000 580
СКТ	DESCRIPTION	NOTES	DEMAND CODE	VA	DC AMPS P	PHASE	DC AMPS P	VA	DEMAND CODE	NOTES	DESCRIPTION	СКТ
1 3 5 7 9 11 13 15 17 19 22 23 25 27 29 31 33 33 37 34 1	LTS-PUMP RM RUW 1 LTS-PUMP RM RUW 1 LTS-PUMP RM RUW 3 LTS-PUMP RM RUW 4 SPARE RECP - PUMP RM EF-107 LTS-CHEM RM, DROP LT ESEW-1 RAW WATER TEMP SENS SPARE MD-105A/B/C MD-107 RECP - GENERATOR RM CHEM FEED PMP P-4010 CHEM FEED PMP P-4011 WIT-4006, WIT-4007, LIT WH-102 GUH-103 GUH-104	⁻ -4007	LTS LTS LTS LTS SPARE REC CDDLING LTS GEN GEN SPARE CDDLING CDDLING GEN GEN GEN GEN GEN HEATING HEATING	961 961 961 961 960 900 900 1201 1201 120 120 360 120 120 120 120 120 120	20 1 20 1 20 1 20 1 20 1 20 1 20 1 20 1	A B C A B C	20 1 20 1 20 1 20 1 20 1 20 1 20 1 20 1	3125 1500 240 240 120 120 240 600	LTS LTS LTS LTS LTS REC GEN GEN HEATING HEATING GEN GEN GEN GEN GEN GEN GEN GEN GEN G		LTS-PUMP RM ROW 2 LTS-PUMP RM ROW 2 LTS-PUMP RM ROW 5 LTS-GENERATOR RM LTS-UTSIDE RECP - PUMP RM NC-5, PS-5 PLC-G GENERATOR JWH-102 GENERATOR SH-102 LLP-1 PUMP CONTROL HOR SHAFT PUMP CONT MD-106A/B EAST OVERHEAD FAN GENERATOR BATTERY CH SPARE SC-102 CONTROL PANEL CARBON FEEDER CF-1	38
TOT TOT	CONNECTED KY AL CONNECTED 27.4 AL DEMAND 27.4 AL DESIGN 32.6	14 84. 14 84.	9 * 9 *	PHASE T A-N B-N C-N		VA 10190. 4 8835. 0 8764. 7	84 73	1PS 1. 9 3. 6 3. 0	BUS TOTAL: CONNECTED DEMAND DESIGN			
<u>N□T</u> 1.	<u>ES:</u> EXISTING LOADS FED FR	OM PANEL A SHAL	L BE REFED W	ITH NEW	WIRE.	REUSE EX	ISTING	CONDUIT	WHERE POSSIBL	E AND EXTEND	AS REQUIRED.	









DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION


LOW LIFT PUMP STATION MCC-2, ATS-102, AND PANEL A SCHEDULE AND ELEVATION

O0130014

DRAWING No.

E-20-701

SHEET 072 OF 088 SHEETS







WATER and SEWER UTILITY

EQUIPMENT CONNECTION SCHEDULE																
710	EQUIPMENT	0717110	LOGITION			OR LOAD		NNECT SWITCH	_	SOURCE	710		NTROL PANEL	DIAGRAM	PLC	NOTES
TAG	DESCRIPTION	STATUS	LOCATION	FLA	HP	VOLTS/ø	SIZE	ENCLOSURE	EXISTING	NEW	TAG	ENCLOSURE	LOCATION			+
AC-101	AIR COMPRESSOR	RELOCATED	WTP - PIPE GALLERY	1.6	0.75	480/3			MCC-4	MCC-8				l		
AC-102	AIR COMPRESSOR	RELOCATED	LLPS- PUMP ROOM	4.8		480/3	30A	W/LCP	MCC-3	MCC-2		EXISTING	LLPS - PUMP ROOM			
		255: 1255				100/1			1							
B-101	BOILER	REPLACED	WTP - MECHANICAL ROOM	5		120/1	30A	W/LCP	MCC-4	A	TC PANEL	REPLACED	WTP - MECHANICAL ROOM	23		
CF-101	CARBON FEEDER	EXISTING	LLPS - EXTERIOR	16	1	120/1	30A	W/LCP	A	A		EXISTING	LLPS - EXTERIOR	22	PLC-G	2#10,1#10G
				1		1 2 3/ 1		,	1							
EF-101	EXHAUST FAN	NEW	WTP- ELECTRICAL ROOM	3	1.5	480/3	30A	NEMA 3R		MCC-4				1		
EF-102	EXHAUST FAN	NEW	WTP- ELECTRICAL ROOM	3	1.5	480/3	30A	NEMA 3R		MCC-4				2		
EF-103 EF-104	EXHAUST FAN	NEW NEW	WTP- ELECTRICAL ROOM WTP- MECHANICAL ROOM	3 0.25	1.5	480/3 480/3	30A 30A	NEMA 3R NEMA 3R		MCC-4		 		2		+
EF-104 EF-105	EXHAUST FAN	NEW	LLPS - PUMP ROOM		10.23		30A	W/LCP	 	MCC-4	VFD-105	NEMA 12	LLPS - PUMP ROOM (MCC-2)	20		+
EF-106	AXIVANE EXHAUST FAN	EXISTING	LLPS - PUMP ROOM		7.5	480/3			MCC-3	MCC-2				3		+
EF-107	EXHAUST FAN	EXISTING	LLPS - CHEMICAL ROOM		0.5	120/1			Α	Α				7		2#12,1#12G
						·										
GEN-101	STANDBY GENERATOR	NEW	WTP - ELECTRICAL ROOM			2.4KV/3								21	PLC-A	
GEN-102	STANDBY GENERATOR	NEW	LLPS - GENERATOR ROOM			480/3	2000A	GENSET MTD.						21	PLC-G	
GUH-101	GAS FIRED UNIT HEATER	NEW	WTP- ELECTRICAL ROOM	0.5	0.1	120/1	20A	NEMA 12		B-RIGHT				30		2#12,1#12G
GUH-101	GAS FIRED UNIT HEATER	REPLACED	LLPS — GENERATOR ROOM		0.1	120/1	20A	NEMA 12		Δ B-RIGHT	1	 		30		2#12,1#12G
GUH-103	GAS FIRED UNIT HEATER	EXISTING	LLPS - PUMP ROOM		0.1	120/1			A	A				30		2#12,1#12G
GUH-104	GAS FIRED UNIT HEATER	EXISTING	LLPS - PUMP ROOM		0.1	120/1			A	A		 		30		2#12,1#12G
H-101	PUMP ROOM HOIST	EXISTING	LLPS - PUMP ROOM		1.5	480/3			MCC-3	MCC-2		EXISTING	LLPS - PUMP ROOM			
H-102	SCREEN BASKET TROLLEY AND HOIST	EXISTING	LLPS - PUMP ROOM	3.4	2	480/3			MCC-3	MCC-2		EXISTING	LLPS - PUMP ROOM			
HWP-101	HEATING WATER PUMP (KATHABAR)	REPLACED	WTP - MECHANICAL ROOM	7.6	5	480/3	30A	NEMA 12	MCC-4	MCC-4	TC PANEL	REPLACED	WTP - MECHANICAL ROOM	1		+
HWP-101	HEATING WATER PUMP	REPLACED	WTP - MECHANICAL ROOM WTP - MECHANICAL ROOM		5	480/3	30A	NEMA 12	MCC-4	MCC-4	TC PANEL	REPLACED	WTP - MECHANICAL ROOM	4		+
HWP-103	HEATING WATER PUMP	REPLACED	WTP - MECHANICAL ROOM	7.6		480/3	30A	NEMA 12	MCC-4	MCC-4	TC PANEL	REPLACED	WTP - MECHANICAL ROOM	4		+
MD-101	MOTORIZED DAMPER	NEW	WTP - ELECTRICAL ROOM			120/1				MCC-4				1		2#12,1#12G
MD-102	MOTORIZED DAMPER	NEW	WTP - ELECTRICAL ROOM			120/1				MCC-4				2		2#12,1#12G
MD-103	MOTORIZED DAMPER	NEW	WTP - ELECTRICAL ROOM	0.1	1/30	120/1				MCC-4				2		2#12,1#12G
MD-104 MD-105A	MOTORIZED DAMPER MOTORIZED DAMPER	NEW NEW	WTP - MECHANICAL ROOM LLPS - GENERATOR ROOM) 120/1		 		MCC-4	1	+		20		2#12,1#12G 2#12,1#12G
MD-105B	MOTORIZED DAMPER	NEW	LLPS — GENERATOR ROOM) 120/1		1	1	A		 		20		2#12,1#12G
	MOTORIZED DAMPER	NEW	LLPS - GENERATOR ROOM) 120/1			 	A				20		2#12,1#12G
MD-106A	MOTORIZED DAMPER	EXISTING	LLPS - PUMP ROOM			240/1				A				3		2#12,1#12G
MD-106B	MOTORIZED DAMPER	EXISTING	LLPS - PUMP ROOM			240/1				А				3		2#12,1#12G
MD-107	MOTORIZED DAMPER	EXISTING	LLPS - CHEMICAL ROOM	0.1	1/30	120/1			<u> </u>	A				7		2#12,1#12G
JWH-101A	GENERATOR JACKET WATER HEATER	NEW	WTP - ELECTRICAL ROOM	24	5KW	208/1				B-RIGHT	GEN-101	NEMA 1	WTP - ELECTRICAL ROOM	21		2#10,1#10G
JWH-101A	GENERATOR JACKET WATER HEATER	NEW	LLPS — GENERATOR ROOM	24		208/1			 	Δ	GEN-101	NEMA 1	LLPS - GENERATOR ROOM	21		2#10,1#10G
SH-101	GENERATOR STRIP HEATER	NEW	WTP - ELECTRICAL ROOM	10		W 120/1			-	B-RIGHT	GEN-101	NEMA 1	WTP - ELECTRICAL ROOM	21		2#12,1#12G
SH-102	GENERATOR STRIP HEATER	NEW	LLPS - GENERATOR ROOM	10		W 120/1			 	A	GEN-102	NEMA 1	LLPS - GENERATOR ROOM	21		2#12,1#12G
	EDUCTOR PUMP	RELOCATED	LLPS - PUMP ROOM	4.8	_				MCC-3	MCC-2	HS-4003		LLPS - PUMP ROOM	5	PLC-G	
P-4004	RAW WATER SUPPLY BOOSTER PUMP	RELOCATED	LLPS - PUMP ROOM		3	480/3			MCC-3	MCC-2	HS-4004	NEMA 12	LLPS - PUMP ROOM	5	PLC-G	
M-4007 P-4010	POTASSIUM PERMANGANATE MIX TANK AGITATOR POTASSIUM PERMANGANATE CHEMICAL METERING PUMP	REPLACED REPLACED	LLPS — PUMP ROOM LLPS — PUMP ROOM	3.4		480/3 120/1		W/LCP	MCC-3	MCC-2	HS-4007 SIC-4010	NEMA 12 NEMA 12	LLPS - PUMP ROOM	5 25	PLC-G	2#12,1#12G
P-4011	POTASSIUM PERMANGANATE CHEMICAL METERING PUMP	NEW	LLPS - PUMP ROOM	0.6	+ -			W/LCP	A	A	SIC-4011	NEMA 12	LLPS - PUMP ROOM	25		2#12,1#12G
LIT-4007	CHEMICAL TANK LEVEL TRANSMITTER	NEW	LLPS - PUMP ROOM			120/1				A	LIT-4007	NEMA 12	LLPS - PUMP ROOM	28		2#12,1#12G
	RAW WATER TEMPERATURE SENSOR	EXISTING	LLPS - PUMP ROOM	0.1		120/1				A		 				2#12,1#12G
	RAW WATER SAMPLE PUMP	EXISTING	LLPS - PUMP ROOM	2.1		480/3			MCC-3	MCC-2	HS-RWP-101	NEMA 12	LLPS - PUMP ROOM	6	PLC-G	
SWP-102	SPRAY WATER PUMP	EXISTING	LLPS - PUMP ROOM		15	480/3			MCC-3	MCC-2	HS-SWP-102	NEMA 12	LLPS - PUMP ROOM	6		3#10,1#10G
WWP-101	WASH WATER PUMP	EXISTING	LLPS - PUMP ROOM	7.6	12	480/3			MCC-3	MCC-2	HS-WWP-101	NEMA 12	LLPS - PUMP ROOM	6	PLC-G	+
SC-101	TRAVELING SCREEN	EXISTING	LLPS - PUMP ROOM	3.4	2 &	0.4580/3	 	1	MCC-3	MCC-2	EXISTING	EXISTING	LLPS - PUMP ROOM	8	PLC-G	6#12,1#12G
SC-101	TRAVELING SCREEN	EXISTING	LLPS — PUMP ROOM	2.1	1	480/3			MCC-3	MCC-2	LCP-SC-102	EXISTING	LLPS - PUMP ROOM	9 & 26		
WH-102	DOMESTIC WATER HEATER	NEW	LLPS - PUMP ROOM	1		120/1	20A	NEMA 12		Α						2#12,1#12G

NOTES:

1. ALL POWER WIRING SHALL BE 3#12, 1#12G IN 3/4" CONDUIT, UNLESS OTHERWISE NOTED.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE: 217.373.8900 FAX: 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

EQUIPMENT CONNECTION SCHEDULE


PROJECT No. O0130014

E-30-101


SHEET 074 OF 088 SHEETS

	LIGHT FIXTURE SCHEDULE								
ITEM	DESCRIPTION	LAMP	MOUNTING	COMMENTS	MANUFACTURER	SERIES/MODEL NO.			
A1	4' INDUSTRIAL FLUOR. FIXTURE WITH BAKED WHITE ENAMEL 10% UPLIGHT REFLECTOR	3 - F32T8	PENDANT MOUNT AT 9' AFF		LITHONIA METALUX COLUMBIA	AF10 332 MVOLT GEB10RS EQUIVALENT EQUIVALENT			
A2	4' INDUSTRIAL FLUOR. FIXTURE WITH BAKED WHITE ENAMEL 10% UPLIGHT REFLECTOR AND EMERGENCY BATTERY PACK	3 - F32T8	PENDANT MOUNT AT 9' AFF		LITHONIA METALUX COLUMBIA	AF10 332 MVOLT GEB10RS EQUIVALENT EQUIVALENT			
B1	4' VAPORTIGHT FLUOR. FIXTURE WITH ACRYLIC LENS AND FIBERGLASS HOUSING	3 - F32T8	CEILING MOUNT		LITHONIA METALUX COLUMBIA	DM-332-AR-MVOLT-GEB10RS EQUIVALENT EQUIVALENT			
B2	4' VAPORTIGHT FLUOR. FIXTURE WITH ACRYLIC LENS AND FIBERGLASS HOUSING	3 - F32T8	WALL MOUNT SEE DETAIL		LITHONIA METALUX COLUMBIA	DM-332-AR-MVOLT-GEB10RS EQUIVALENT EQUIVALENT			
C1	LED TYPE EXIT LIGHT FIXTURE, SINGLE FACE, SELF—CONTAINED BATTERY AND CHARGER, AND STENCIL RED FACE	LED EXIT	WALL MOUNT	PROVIDE HIGH OUTPUT BATTERY TO POWER REMOTE HEAD	LITHONIA	LHQM SW3R 120/277 HO			
D1	2 HEAD EMERGENCY LIGHT, FIBERGLASS WITH SWIVEL LAMP SOCKETS	2 - 6W HALOGEN	WALL MOUNT AT 8' AFF	PROVIDE WET LOCATION RATED	LITHONIA	ELA NX H0606			
D2	2 HEAD EMERGENCY LIGHT, FIBERGLASS WITH SWIVEL LAMP SOCKETS	2 – 20W HALOGEN	WALL MOUNT	PROVIDE WET LOCATION RATED	LITHONIA	IND 654 H2006			


DUCTBANK CABLE SCHEDULE							
MARK	FROM	ТО	WIRE				
Α	XFMR-3A WEST	ATS-101	4#500, 1#3/0G (5KV)				
В	ATS-101	2.4KV SWITCHGEAR	3#500, 1#3/0G (5KV)				
С	COPPER GROUND BAR	GROUND GRID	1#3/0				
D	GEN-101	ATS-101	4#500, 1#3/0G (5KV)				
E	COPPER GROUND BAR	WATER PIPE	1#3/0				
F	FUTURE XFMR-3B EAST	FUTURE ATS-103					
















D CONDUIT SECTION
NO SCALE



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

21/11 ISSUED FOR CONST. 3/11 ISSUED FOR BIDS

3/21/11 2/3/11 ISSUED FOR CONST. ISSUED FOR BIDS REVISION

> LIGHT FIXTURE SCHEDULE, DUCTBANK SCHEDULE, AND SECTIONS


PROJECT No. 00130014


DRAWING N

E-30-102

SHEET 075 OF 088 SHEETS

ACCESS CONTROL/VIDEO MONITORING CONNECTION SCHEDULE EQUIPMENT COMPONENTS LOCATION AREA CONTROLLED NOTES NORTH GATE (EXTERIOR) WATER TREATMENT PLANT PS-3 00-NEXT NORTH GATE (INTERIOR) WATER TREATMENT PLANT 00-NINT ADMINISTRATION AND FILTRATION FACILITY ELECTRICAL ROOM 70-107A GENERATOR ROOM NC-5 NC-5 LOW LIFT PUMP STATION 80-102A 80-102B LOW LIFT PUMP STATION GENERATOR ROOM ADMINISTRATION AND FILTRATION FACILITY ELECTRICAL ROOM





TYPICAL DOOR READER MODULE

NO SCALE

TYPICAL FOR THE FOLLOWING:
- NC-2,NC-3,NC-4,NC-5,NC-6

NORTH GATE OPENER, READER, AND INTERCOM
NO SCALE



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

Partners in Design



WATER and SEWER UTILITY

WATER TREATMENT PLANT
AND LOW LIFT PUMP STATION
STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.


3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION


ACCESS CONTROL/VIDEO
MONITORING CONNECTION
SCHEDULE AND
INTERCONNECT DIAGRAM

PROJECT No.
00130014

DRAWING No.

E-30-103
SHEET 076 OF 088 SHEETS





LEGEND Δ = REMOTE MOUNTED DEVICE. □ = DEVICE LOCATED IN LOCAL PANEL. MOTOR MOTOR MAINTAINED CONTACT EMERGENCY STOP— MAINTAINED CONTACT EMERGENCY STOP— XMFR XMFR HAND HAND AUTO START START AUTO "AUTO POSITION"
TO PLC "AUTO POSITION" TO PLC "RUN" "RUN" ЕТМ SPRAY WATER SCREEN WASH WATER

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/1:

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

ELECTRICAL CONTROL DIAGRAMS

PROJECT No. O0130014

E-30-203

SHEET 079 OF 088 SHEETS

NOTES:

1. CONTRACTOR SHALL CONFIRM CONTROL WIRING INTERFACE
TO EXISTING EQUIPMENT AND MODIFY AS REQUIRED.

2. CR1 IS FROM "SPRAY WATER PUMP RELAY" IN SC-102
CONTROL PANEL. SPRAY WATER PUMP SWP-102

"RUN" TO PLC

SOLENOID VALVE

NOTES:


1. CONTRACTOR SHALL CONFIRM CONTROL WIRING INTERFACE
TO EXISTING EQUIPMENT AND MODIFY AS REQUIRED.


2. CR1 IS FROM "SCREEN WASH WATER SOLENOID" SIGNAL IN
WATER LEVEL DIFFERENTIAL CONTROLLER.

"RUN" TO PLC

WASH WATER PUMP WWP-101

SOLENOID VALVE






SINGLE RACK


- 1. LENGTH VARIES WITH NUMBER OF CONDUITS TO BE SUPPORTED AND SPACING BETWEEN CONDUITS.
- 2. DETERMINE SPAN AND TYPE OF SUPPORTS, LOCATE SUPPORTS, AND SIZE SUPPORT RODS, CONNECTIONS AND BRACES PER MANUFACTURER'S RECOMMENDATIONS AND SEISMIC REQUIREMENTS.
- AT STEEL STRUCTURE, USE GRINNEL MALLEABLE BEAM CLAMP. AT CONCRETE STRUCTURE, USE UNIVERSAL CONCRETE INSERT, UNISTRUT CHANNEL WITH #4 x 3'-0" BELOW, OR GRINNEL FIGURE 52 ATTACHMENT PLATE, SIMILAR. TYPE AND SIZE AS REQUIRED BY TOTAL LOADS.
- USE STAINLESS STEEL HARDWARE IN WET AND/OR CORROSIVE AREAS.
- 5. SPACE CONDUIT SUFFICIENTLY TO ALLOW REMOVAL OF ONE CONDUIT WITHOUT DISTURBING ADJACENT CONDUITS.






- 1. INSTALL CONDUITS THROUGH EXISTING WALLS IN ACCORDANCE WITH THIS DETAIL IF NOT OTHERWISE INDICATED.
- 2. DRILL HOLE USING METHODS THAT LEAVE A SMOOTH OPENING. SEAL OPENING AROUND CONDUIT, INSIDE AND OUTSIDE, WITH ONE PART POLYURETHANE IMMERSIBLE SEALANT.






CONDUITS WHICH INDIVIDUALLY PASS THRU AN INTERIOR WALL SHALL BE INSTALLED IN ACCORDANCE WITH THIS DETAIL. IF WALL IS A FIRE WALL, FILL CAVITY WITH FIRE STOP SEALANT SPECIFIED IN SECTION 07 84 00.





1. ALL CONDUITS THROUGH WALL WITH EXCAVATED FILL ON EACH SIDE OF WALL SHALL BE INSTALLED IN ACCORDANCE WITH THIS DETAIL.






NOTES:

1. USE WATERTIGHT CONDUIT SEAL WHERE CONDUIT PENETRATIONS OF BUILDING EXTERIOR WALLS ARE BELOW GRADE AND CONDUIT FEEDS INTO INTERIOR EXPOSED SPACE.





ALL CONDUITS THROUGH CONCRETE FLOOR SLABS AND EQUIPMENT PADS SHALL BE INSTALLED IN ACCORDANCE WITH THIS DETAIL.





DESIGN FIRM REGISTRATION

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY:


NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

3/21/11 ISSUED FOR CONST. 2/3/11 ISSUED FOR BIDS DATE REVISION

DETAIL(ELECTRICAL


PROJECT No. O0130014

E-30-301 SHEET 082 OF 088 SHEETS




NOTES:

LOCATE PULLBOX WITH READER MODULE 12" ABOVE DOOR OR
 6" ABOVE DROP CEILING IF DROP CEILING IS PRESENT.




NOTE:
PROVIDE 2 MOUNTING BRACKETS
PER LIGHT FIXTURE.



ACCESS CONTROL EQUIPMENT MOUNTING

TYPE B2 LIGHT FIXTURE INSTALLATION





1. BACKFILL WITH SAND AROUND CONDUITS AND UP TO 4" ABOVE CONDUITS.





PROJECT No. O0130014

ELECTRICAL DETAILS

DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923

PartnersinDesign

WATER and SEWER UTILITY


WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC
DATE CHECKED: 01/1

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.

3/21/11 2/3/11 DATE ISSUED FOR CONST. ISSUED FOR BIDS REVISION

E-30-302 SHEET 083 OF 088 SHEETS



NOTES

- 1. SEE DRAWINGS E-00-101, P-00-101, AND HV-00-101 FOR GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. EXPOSED INSULATED COOLANT PIPING IN ELECTRICAL ROOM SHALL HAVE STAINLESS STEEL JACKET FROM FLANGE CONNECTION ON GENERATOR DOWN TO FLOOR AND EXTEND 2" BELOW ALUMINUM PLATE ON TRENCH. JACKET SEAM SHALL BE ON GENERATOR SIDE OF PIPE.
- 3. GENERATOR SHALL BE MOVED TO THE EAST IN THE ELECTRICAL ROOM TO PROVIDE 36" CLEARANCE BETWEEN GENERATOR CONTROL PANEL AND OPENED DAMPER BLADES AND ACTUATOR. FINAL LOCATION SHALL BE DETERMINED IN THE FIELD.

KEYNOTES

- 1. GENERATOR GEN-101.
- 2. GENERATOR SILENCER.
- 3. INSULATED 12" DIAMETER EXHAUST PIPING.
- 4. 3" GAS PIPING TO GENERATOR.
- 5. 4" POTABLE WATER PIPING.
- 6. JACKET WATER HEAT EXCHANGER HX-101A.
- 7. AFTER COOLER HEAT EXCHANGER HX-101B.
- 8. JACKET WATER LOOP EXPANSION TANK.
- 9. AFTER COOLER LOOP EXPANSION TANK.
- 10. PIPE TRENCH.
- 11. INSULATED 6" JACKET WATER COOLANT SUPPLY PIPING.
- 12. INSULATED 6" JACKET WATER COOLANT RETURN PIPING.
- 13. 4" POTABLE WATER PIPING FOR JACKET WATER HEAT EXCHANGER.
- 14. 4" DRAIN PIPING FOR JACKET WATER HEAT EXCHANGER.
- 15. INSULATED 3" AFTER COOLER COOLANT SUPPLY PIPING.
- 16. INSULATED 3" AFTER COOLER COOLANT RETURN PIPING.
- 17. 2" POTABLE WATER PIPING FOR AFTER COOLER HEAT EXCHANGER.
- 18. 2" DRAIN PIPING FOR AFTER COOLER HEAT EXCHANGER.
- 19. SUMP PIT.
- 20. ALUMINUM GRATING ON STAINLESS STEEL SUPPORT RACK.
- 21. GENERATOR CONTROL PANEL.
- 22. BATTERY CHARGER.
- 23. BATTERY RACK.
- 24. GENERATOR EQUIPMENT PAD.
- 25. ALUMINUM GRATING OVER PIPE TRENCH.
- 26. INTAKE AIR LOUVER AND MOTORIZED DAMPER.
- 27. ALUMINUM PLATE OVER PIPE TRENCH.
- 28. CONDUITS FOR 120 VOLT POWER AND CONTROL WIRING.
- 29. 2" PIPING FOR CRANKCASE FUME DISPOSAL.
- 30. 2" PIPING WITH VALVE FOR CRANKCASE DRIP COLLECTOR.
- 31. AUTOMATIC BREATHER VALVE FOR AIR BLEED.
- 32. 6" SANITARY PIPING.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM/JRF
DRAWN BY: JRF
CHECKED BY: CEC

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

ADMINISTRATION AND FILTRATION FACILITY BUILDING SECTIONS

PROJECT No. 00130014

DRAWING No.

S-10-101 SHEET 084 OF 088 SHEETS

NOTES

- SEE DRAWINGS E-00-101, P-00-101, AND HV-00-101 FOR GENERAL NOTES, LEGEND, AND ABBREVIATIONS.
- 2. EXPOSED INSULATED COOLANT PIPING IN ELECTRICAL ROOM SHALL HAVE STAINLESS STEEL JACKET FROM FLANGE CONNECTION ON GENERATOR DOWN TO FLOOR AND EXTEND 2" BELOW ALUMINUM PLATE ON TRENCH. JACKET SEAM SHALL BE ON GENERATOR SIDE OF PIPE.

KEYNOTES

- 1. GENERATOR GEN-101
- 2. GENERATOR SILENCER.
- 3. INSULATED 12" DIAMETER EXHAUST PIPING.
- 4. 3" GAS PIPING TO GENERATOR.
- 5. 4" POTABLE WATER PIPING.
- 6. JACKET WATER HEAT EXCHANGER HX-101A.
- 7. AFTER COOLER HEAT EXCHANGER <u>HX-101B</u>.
- 8. JACKET WATER LOOP EXPANSION TANK.
- 9. AFTER COOLER LOOP EXPANSION TANK.
- 10. PIPE TRENCH.
- 11. INSULATED 6" JACKET WATER COOLANT SUPPLY PIPING.
- 12. INSULATED 6" JACKET WATER COOLANT RETURN PIPING.
- 13. INSULATED 3" AFTER COOLER COOLANT SUPPLY PIPING.
- 14. 2" POTABLE WATER PIPING FOR AFTER COOLER HEAT EXCHANGER.
- 15. 2" DRAIN PIPING FOR AFTER COOLER HEAT EXCHANGER.
- 16. SUMP PIT.
- 17. ALUMINUM GRATING ON STAINLESS STEEL SUPPORT RACK.
- 18. BATTERY RACK.
- 19. EQUIPMENT PAD.
- 20. ATS-101 AND WE ENERGIES METERING SECTION.
- 21. CONCRETE ENCASED UNDERGROUND CONDUITS WITH 5KV CABLES.
- 22. GAS VALVE AND REGULATOR.
- 23. 4" GAS PIPING TO GAS METER.
- 24. ALUMINUM PLATE OVER PIPE TRENCH.
- 25. ALUMINUM GRATING OVER PIPE TRENCH.
- 26. 6" SANITARY PIPING.
- 27. MOTORIZED DAMPERS.
- 28. 2" PIPING FOR CRANKCASE FUME DISPOSAL.
- 29. AUTOMATIC BREATHER VALVE FOR AIR BLEED.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM/JRF
DRAWN BY: JRF
CHECKED BY: CEC

DATE CHECKED: 01/11

NOTE: DIMENSIONAL DATA
IS NOT TO BE OBTAINED BY
SCALING ANY PORTION OF
THIS DRAWING.


ADMINISTRATION AND FILTRATION FACILITY BUILDING SECTION


PROJECT No

O0130014

S-10-102

SHEET 085 OF 088 SHEETS







WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM DRAWN BY: JRF

SCALING ANY PORTION OF

PROJECT No.

S-20-101

EXISTING CONCRETE BEAM موو -000 000 - EXISTING EXTERIOR WALL (10) $\langle 13 \rangle$ (12)-EXISTING ELECTRICAL PLATFORM AREA (ELEV. 21.0') CONCRETE FLOOR (ELEV. 12.0')

DEMOLITION KEYNOTES

1. REMOVE EXISTING PULLBOX AND SERVICE LATERAL CABLES FROM TRANSFORMER XFMR-1B TO MAIN SWITCHBOARD MSWB-1B.

KEYNOTES

- 1. EXISTING TRANSFORMER XFMR-1B.
- 2. REPLACE EXISTING 480 VOLT SERVICE LATERAL CABLES IN UNDERGROUND CONDUITS.
- 3. CONNECT NEW CONDUITS TO EXISTING CONDUITS WHERE THEY PENETRATE EXISTING EXTERIOR WALL.
- 4. CONCRETE WALL TO ENCASE SERVICE LATERAL CONDUITS.
- 5. EXISTING MAIN SWITCHBOARD MSWB-1B.
- 6. CONDUITS WITH 480 VOLT SERVICE LATERAL CABLES ENCASED IN CONCRETE TO AUTOMATIC TRANSFER SWITCH ATS-102.
- 7. AUTOMATIC TRANSFER SWITCH ATS-102.
- 8. CONDUITS WITH 480 VOLT FEEDER CABLES TO EXISTING MAIN SWITCHBOARD MSWB-1B.
- 9. CONDUITS WITH 480 VOLT FEEDER CABLES FROM NATURAL GAS STANDBY GENERATOR GEN-102.
- 10. EXISTING 36" RAW WATER PIPE.
- 11. EXISTING MEZZANINE.
- 12. NEW MEZZANINE AND HANDRAIL.
- 13. PROVIDE STEEL PLATE IN BOTTOM OF $\underline{\text{MSWB}}-1\underline{\text{B}}$ TO COVER OPENING WHERE CABLES ENTERED BOTTOM OF EQUIPMENT.
- 14. EXISTING CONDUITS WITH 480 VOLT FEEDER CONDUCTORS.



DESIGN FIRM REGISTRATION No. 184-000450

125 WEST CHURCH STREET CHAMPAIGN, IL 61820 PHONE : 217.373.8900 FAX : 217.373.8923





WATER and SEWER UTILITY

WATER TREATMENT PLANT AND LOW LIFT PUMP STATION STANDBY POWER

DESIGNED BY: SEM
DRAWN BY: JRF
CHECKED BY: CEC

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

| 3/21/11 | ISSUED FOR CONST. | 2/3/11 | ISSUED FOR BIDS | DATE | REVISION |

STATION LOW LIFT PUMP S BUILDING SEC

PROJECT No. O0130014

S-20-102

SHEET 087 OF 088 SHEETS

